

HDL-06-24-250-CV



ءارضخلا تاحطسمل ير :ءيراجتلاةمالعلا

طيقن تل اب ير : تاجت نمل ا طخ

HDL: جتنم لارط

HDL0624250CV: نوزخ ملاب طاقت حال اءحو

ضريوعات ةزيم عم دادترالال عنام سببحم، Hunter نم طيقننتلاب يرطخ :فصولا

Shipping Information

UPC-A: 0611698514641

1: **ةبيق حلا/ةيمكلا**

٥١٦

44: يطيحم حول

36: يضرأ حول

1: ةيسيئر ةنوترك

Additional Information

0.6 GPH: قفدت لادعم

250' : فلما لوط

24" طيقننتلا تادحو دعابت

0.6 GPH: قفدت لادعم

بيبان ألاب ةجدم تاطاقنب يرلا: Drip irrigation

بيبانأل: بيبانأل حطس ىلع تاطا قنب يرلا

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	206
3.0	129	210	280
4.0	167	295	399

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	389

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/ar/irrigation-product/hdl/hdl-06-24-250-cv>
020326