



I-20-04-PRB

ءارضال اءاطسمل ار :ءيراءءال ءمءالءال

ءراوء ءاشاءر :ءاءءنمءال طء

ءءنمءال زارط : PGP Ultra & I-20 PRB

نوزءملاب طاءءءال ءءو : I2004PRB

ءءء ءءءرء 360 ءل 50 نمل ءلءءلل لءاق ءمس 10 ء-20 ءراوء ءاشاءر :ءصوءل
طءضلل مطنم لكئه ءاءءرلل عنام سءءم ءصوب 3/4 لءاء

Dimensions

ءاءءرءال : 209.55 مم


ءلءمءال ءاءءرءال : 18 cm

زفاءل ءاءءرءال : 4"

رطق : 44.45 مم

ءوءءكمءال رطقل : 44.45 مم

لءءءمءال ءءء : 3/4"



Operating Specifications

Arc: 50° to 360°

Operating Pressure: 4.1 ءل 7.0 bar; 410 ءل 700 لاءسابلءل ك

Precipitation Rate: 10 ءعاس/ملم

Radius: 4.9 ءل 14.0 م

Flow: 0.07 نمل ءل 2.22 م3/ءعاس; 1.2 نمل ءل 36.0 ءقءءرءل

Shipping Information

UPC-A: 0611698060162

ءبءقءلءl

ءلءl


ءلءلءلءلءلءلءلءلءلءلءلءلءلءl

ءلءلءلءلءلءلءلءلءلءl


[illegible]

لزون الاءا تاناي ب PGP Ultra / I-20 / PRB دوسال رطلال فصن ري صق							
لزون ال	طغ صال		فصن رطلال	ق فدتال		لدغم بئسرتال س/م ل	
	bar	kPa	م	هعاسال/ل ³ رتم	هقئقذل/رتل	■	▲
.50 SR ● دوسأ	1.7	170	4.9	0.07	1.2	6	7
	2.0	200	5.2	0.08	1.3	6	7
	2.5	250	5.2	0.09	1.5	7	8
	3.0	300	5.2	0.10	1.7	8	9
	3.5	350	5.5	0.12	1.9	8	9
	4.0	400	5.5	0.13	2.1	8	10
	4.5	450	5.5	0.14	2.3	9	10
1.0 SR ● دوسأ	1.7	170	4.9	0.16	2.7	14	16
	2.0	200	5.2	0.17	2.9	13	15
	2.5	250	5.2	0.19	3.2	14	17
	3.0	300	5.2	0.21	3.6	16	18
	3.5	350	5.5	0.23	3.8	15	18
	4.0	400	5.5	0.25	4.1	16	19
2.0 SR ● دوسأ	4.5	450	5.5	0.26	4.3	17	20
	1.7	170	4.9	0.28	4.7	24	27
	2.0	200	5.2	0.31	5.2	23	27
	2.5	250	5.2	0.36	6.0	27	31
	3.0	300	5.2	0.41	6.9	31	35
	3.5	350	5.5	0.45	7.6	30	35
.75 SR ● دوسأ	4.0	400	5.5	0.49	8.2	33	38
	4.5	450	5.5	0.53	8.9	35	41
	1.7	170	6.7	0.12	2.0	5	6
	2.0	200	7.0	0.13	2.2	5	6
	2.5	250	7.0	0.15	2.4	6	7
	3.0	300	7.3	0.16	2.7	6	7
1.5 SR ● دوسأ	3.5	350	7.6	0.17	2.9	6	7
	4.0	400	7.6	0.19	3.1	6	7
	4.5	450	7.6	0.20	3.3	7	8
	1.7	170	6.7	0.23	3.8	10	12
	2.0	200	7.0	0.25	4.1	10	12
	2.5	250	7.0	0.28	4.6	11	13
3.0 SR ● دوسأ	3.0	300	7.3	0.31	5.2	12	13
	3.5	350	7.6	0.34	5.6	12	13
	4.0	400	7.6	0.36	6.0	12	14
	4.5	450	7.6	0.39	6.4	13	15
	1.7	170	6.7	0.53	8.9	24	27
	2.0	200	7.0	0.56	9.3	23	26
2.5 SR ● دوسأ	2.5	250	7.0	0.60	10.0	24	28
	3.0	300	7.3	0.64	10.7	24	28
	3.5	350	7.6	0.67	11.2	23	27
	4.0	400	7.6	0.70	11.7	24	28
	4.5	450	7.6	0.73	12.1	25	29
	هطاحالم: تاللدغم باسحل .هجره 180 هئوارب لئغشتلل بئسرتال تاللدغم عئم باسحل م 2. لئل هئقئلال هئسق مئ، هجره 360 هئوارب شاسرلل بئسرتال						

PGP Ultra / I-20 / PRB Gray Low Angle Nozzle Performance Data					
Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
2.0 LA ● Gray	30	25	1.6	0.49	0.57
	40	27	1.9	0.50	0.58
	50	28	2.1	0.52	0.60
	60	30	2.3	0.49	0.57
2.5 LA ● Gray	30	27	2.1	0.55	0.64
	40	30	2.5	0.53	0.62
	50	33	2.8	0.49	0.57
	60	35	3.0	0.47	0.54
3.5 LA ● Gray	30	29	2.8	0.64	0.74
	40	32	3.1	0.58	0.67
	50	35	3.5	0.55	0.64
	60	37	3.8	0.53	0.62
4.5 LA ● Gray	30	29	3.4	0.78	0.90
	40	32	3.9	0.73	0.85
	50	35	4.4	0.69	0.80
	60	37	4.7	0.66	0.76
Notes: Bold = Recommended pressure. All precipitation rates calculated for 180 degree operation. For the precipitation rate for a 360 degree sprinkler, divide by 2.					

PGP ULTRA / I-20 / PRB MPR-25 RED NOZZLE PERFORMANCE DATA					
Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
 Red 90°	25	23	0.74	0.54	0.62
	35	24	0.88	0.59	0.68
	45	25	1.00	0.62	0.71
	55	25	1.11	0.68	0.79
	65	25	1.21	0.75	0.86
 Red 120°	25	23	1.00	0.55	0.63
	35	24	1.21	0.61	0.70
	45	25	1.38	0.64	0.74
	55	25	1.53	0.71	0.82
	65	25	1.67	0.77	0.89
 Red 180°	25	23	1.44	0.52	0.61
	35	24	1.73	0.58	0.67
	45	25	1.98	0.61	0.70
	55	25	2.21	0.68	0.79
	65	25	2.41	0.74	0.86
 Red 360°	25	23	2.78	0.51	0.58
	35	24	3.34	0.56	0.64
	45	25	3.82	0.59	0.68
	55	25	4.25	0.65	0.76
	65	25	4.63	0.71	0.82

PGP ULTRA / I-20 / PRB MPR-30 LT. GREEN NOZZLE PERFORMANCE DATA					
Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
 Lt. Green 90°	25	29	1.03	0.47	0.54
	35	30	1.23	0.53	0.61
	45	30	1.40	0.60	0.69
	55	30	1.56	0.67	0.77
	65	30	1.69	0.72	0.83
 Lt. Green 120°	25	29	1.34	0.46	0.53
	35	30	1.62	0.52	0.60
	45	30	1.85	0.59	0.69
	55	30	2.06	0.66	0.76
	65	30	2.24	0.72	0.83
 Lt. Green 180°	25	29	2.15	0.49	0.57
	35	30	2.59	0.55	0.64
	45	30	2.96	0.63	0.73
	55	30	3.30	0.71	0.82
	65	30	3.60	0.77	0.89
 Lt. Green 360°	25	29	4.24	0.49	0.56
	35	30	5.08	0.54	0.63
	45	30	5.78	0.62	0.71
	55	30	6.39	0.68	0.79
	65	30	6.92	0.74	0.85

PGP ULTRA / I-20 / PRB MPR-35 BEIGE NOZZLE PERFORMANCE DATA					
Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
 Beige 90°	25	32	1.40	0.53	0.61
	35	34	1.67	0.56	0.64
	45	35	1.92	0.60	0.70
	55	35	2.13	0.67	0.77
	65	35	2.31	0.73	0.84
 Beige 120°	25	32	1.77	0.50	0.58
	35	34	2.15	0.54	0.62
	45	35	2.46	0.58	0.67
	55	35	2.74	0.65	0.75
	65	35	2.99	0.70	0.81
 Beige 180°	25	32	2.75	0.52	0.60
	35	34	3.33	0.55	0.64
	45	35	3.81	0.60	0.69
	55	35	4.23	0.66	0.77
	65	35	4.62	0.73	0.84
 Beige 360°	25	32	5.36	0.50	0.58
	35	34	6.62	0.55	0.64
	45	35	7.58	0.60	0.69
	55	35	8.43	0.66	0.76
	65	35	9.18	0.72	0.83

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.