



I-20-06-R زارط

ءارضخ لآ اآاطس م لآ یر :ءیراآ لآ ةم ال ع لآ

ة راو د آاشا شر :آاآ لآ م لآ ط آ

آآ لآ م لآ زارط : I-25

نوزخ م لآ ب طاف آ لآ ة د ح و : I2506R

ة آ آ ف ، ة آ ر د 360 ى ل إ 50 ن م لآ ة د ع ل ل ل ب آ ق ، م س 15 ، I-25 راو د ش ا ش ر : ف ص و ل آ
ف ر غ م ، د ا د ر ا ل ل ع ن ا م س ب ح م ، ى ك ى ت س ا ل ب ق ث ب ن م ب و ب ن أ ، (م م 25) ة ص و ب 1 ل آ ا د
آ ا ل ز و ن ة س م خ ع م ى ت أ ى ، ة آ ل آ ع م ل آ ه ا ى م ل آ

Dimensions

م م 260.35 : ع ا ف آ ر ا ل آ

6" : ز ف ا ق ا ل آ ع ا ف آ ر ا

م م 44.45 : ر ط ق

م م 44.45 : ف و ش ك م ل آ ر ط ق ل آ



Operating Specifications

Arc: 50° to 360°

Operating Pressure: ل آ ك س ا ب و ل ى ك 700 ى ل إ 250 ن م ؛ ر ا ب 7.0 ى ل إ 2.5 ن م

Precipitation Rate: 10 ة ع ا س / م ل م

Radius: 11.9 ى ل إ 21.6 م

Flow: 0.82 ى ل إ 7.24 م 3 / ة ع ا س ؛ 13.6 ى ل إ 120.2 ة ق ى ق د / ر ت ل

Shipping Information

UPC-A: 0611698156421

ة ب ى ق ح ل / ة ى م ك ل آ : 12

ك ى س ك م ل آ ى ف ع ن ص : ل ص أ ل آ

ى ط ى ح م ح و ل : 1260

ى ض ر أ ح و ل : 1080

ة ى س ى ئ ر ة ن و ت ر ك : 12

25-1 تالزونول ءادال تانايب							
لرونل	طغصل		فصن رطقل	ققدتل		لدعم ببسرتل س/م لم	
						▲	■
	راب	لاكسابوليك	م	هعاسل/لرتم	هقيقدل/رتل		
4 ● رفصأ	2.5	250	11.9	0.82	13.6	12	13
	3.0	300	12.2	0.91	15.2	12	14
	3.5	350	12.5	0.98	16.4	13	15
	4.0	400	12.5	1.05	17.5	13	16
	4.5	450	12.8	1.11	18.6	14	16
	5.0	500	13.1	1.18	19.6	14	16
	5.5	550	13.4	1.24	20.7	14	16
7 ● يلاقترب*	2.5	250	13.4	1.44	24.0	16	19
	3.0	300	14.0	1.54	25.6	16	18
	3.5	350	14.3	1.61	26.9	16	18
	4.0	400	14.3	1.68	28.0	16	19
	4.5	450	14.6	1.75	29.1	16	19
	5.0	500	14.9	1.81	30.1	16	19
	5.5	550	15.2	1.87	31.1	16	19
8 ● يحب حتاف	2.5	250	14.0	1.65	27.5	17	19
	3.0	300	14.3	1.81	30.1	18	20
	3.5	350	14.9	1.94	32.3	17	20
	4.0	400	15.2	2.05	34.2	18	20
	4.5	450	15.2	2.16	36.0	19	22
	5.0	500	15.5	2.27	37.8	19	22
	5.5	550	15.8	2.38	39.6	19	22
10 ● رضخأ حتاف*	3.0	300	15.2	2.15	35.8	18	21
	3.5	350	15.5	2.32	38.6	19	22
	4.0	400	15.8	2.48	41.3	20	23
	4.5	450	16.2	2.63	43.9	20	23
	5.0	500	16.2	2.78	46.3	21	25
	5.5	550	16.5	2.94	48.9	22	25
	6.0	600	16.8	3.07	51.1	22	25
13 ● حتاف قورزا	3.0	300	15.8	2.38	39.6	19	22
	3.5	350	16.2	2.57	42.8	20	23
	4.0	400	16.5	2.75	45.7	20	23
	4.5	450	16.5	2.91	48.5	21	25
	5.0	500	16.8	3.07	51.2	22	25
	5.5	550	16.8	3.24	54.0	23	27
	6.0	600	17.1	3.39	56.4	23	27
15 ● يدامر*	3.0	300	16.8	2.86	47.7	20	24
	3.5	350	17.1	3.05	50.8	21	24
	4.0	400	17.4	3.22	53.7	21	25
	4.5	450	17.4	3.38	56.3	22	26
	5.0	500	17.4	3.53	58.8	23	27
	5.5	550	17.7	3.69	61.5	24	27
	6.0	600	18.0	3.82	63.7	24	27
18 ● رمحأ	6.2	620	18.3	3.88	64.6	23	27
	3.0	300	17.4	3.08	51.4	20	24
	3.5	350	17.7	3.31	55.2	21	24
	4.0	400	18.0	3.52	58.7	22	25
	4.5	450	18.3	3.72	62.0	22	26
	5.0	500	18.9	3.91	65.2	22	25
	5.5	550	19.2	4.11	68.5	22	26
20 ● ينب نكاد*	6.0	600	19.5	4.28	71.4	23	26
	6.2	620	19.5	4.35	72.5	23	26
	3.5	350	18.0	3.72	62.1	23	27
	4.0	400	18.6	3.97	66.2	23	27
	4.5	450	18.9	4.2	70.1	24	27
	5.0	500	19.2	4.42	73.7	24	28
	5.5	550	19.5	4.66	77.7	25	28
23 ● نكاد رضخأ	6.0	600	19.8	4.86	81.0	25	29
	6.5	650	20.1	5.05	84.2	25	29
	6.9	690	20.4	5.21	86.8	25	29
	3.5	350	18.6	4.56	76.0	26	30
	4.0	400	19.2	4.88	81.3	26	31
	4.5	450	19.5	5.18	86.3	27	31
	5.0	500	19.8	5.47	91.1	28	32
	5.5	550	20.1	5.78	96.3	29	33

6.0	600	20.1	6.04	100.6	30	34	
6.5	650	20.4	6.29	104.8	30	35	
6.9	690	20.7	6.5	108.3	30	35	
25 ● نكاد قرراً*	3.5	350	19.2	4.86	80.9	26	30
	4.0	400	19.8	5.23	87.1	27	31
	4.5	450	20.1	5.58	93.1	28	32
	5.0	500	20.4	5.92	98.7	28	33
	5.5	550	21.0	6.29	104.9	28	33
	6.0	600	21.0	6.6	110.0	30	34
	6.5	650	21.3	6.9	115.1	30	35
	6.9	690	21.6	7.15	119.2	31	35
28 ● دوساً	3.5	350	18.3	5.31	88.5	32	37
	4.0	400	19.2	5.63	93.8	31	35
	4.5	450	20.1	5.93	98.8	29	34
	5.0	500	20.7	6.21	103.5	29	33
	5.5	550	21.3	6.52	108.6	29	33
	6.0	600	21.3	6.77	112.8	30	34
	6.5	650	21.6	7.01	116.9	30	35
	6.9	690	21.6	7.21	120.2	31	36
*شاشر لك عم ةقفرم ةيسايق تالزون 5 هطحالم: بيسرتل تالدعم باسحل .ةجرد 180 ةيوازب ليغشتلل بيسرتل تالدعم عيمج باسح مت 2. يل ةمقيلا ةمسق متت ،ةجرد 360 ةيوازب شاشرللل							

ةعرسلا يلاع 1-25 لرون ءادا تانايب							
لرونلا	طغصلال		فصن رطقلا	ق فدتلا		لدعم بيسرتلا م/س لم	
	راب	لاكسابوليك	م	ةعاسلا/ترتم	ةقيقدلا/رتل	▲	■
4 ● رفصاً	2.5	250	11.0	0.81	13.6	14	16
	3.0	300	11.3	0.91	15.1	14	16
	3.5	350	11.6	0.99	16.4	15	17
	4.0	400	11.6	1.06	17.6	16	18
	4.5	450	11.6	1.13	18.8	17	19
	5.0	500	11.9	1.19	19.9	17	19
7 ● يل اقتررب*	5.5	550	11.9	1.26	21.1	18	21
	2.5	250	11.9	1.32	22.0	19	22
	3.0	300	12.2	1.46	24.3	20	23
	3.5	350	12.5	1.57	26.2	20	23
	4.0	400	12.8	1.68	27.9	20	24
	4.5	450	13.1	1.78	29.6	21	24
8 ● ينب حتاف	5.0	500	13.4	1.87	31.1	21	24
	5.5	550	13.4	1.97	32.8	22	25
	2.5	250	12.5	1.54	25.7	20	23
	3.0	300	12.8	1.72	28.6	21	24
	3.5	350	13.1	1.86	31.0	22	25
	4.0	400	13.4	2.00	33.3	22	26
10 ● رضحاً حتاف*	4.5	450	13.4	2.13	35.4	24	27
	5.0	500	13.7	2.25	37.5	24	28
	5.5	550	13.7	2.38	39.7	25	29
	3.0	300	13.7	2.15	35.8	23	26
	3.5	350	14.0	2.32	38.6	24	27
	4.0	400	14.3	2.48	41.3	24	28
13 ● حتاف قرراً	4.5	450	14.6	2.63	43.9	25	28
	5.0	500	14.9	2.78	46.3	25	29
	5.5	550	15.2	2.94	48.9	25	29
	6.0	600	15.2	3.07	51.1	26	31
	3.0	300	14.3	2.38	39.6	23	27
	3.5	350	14.6	2.57	42.8	24	28
15 ● ي دامر*	4.0	400	14.9	2.75	45.7	25	28
	4.5	450	15.2	2.91	48.5	25	29
	5.0	500	15.5	3.07	51.2	25	29
	5.5	550	15.5	3.24	54.0	27	31
	6.0	600	15.5	3.39	56.4	28	32
	3.0	300	14.6	2.86	47.7	27	31
18 ● رحأ	3.5	350	14.9	3.05	50.8	27	32
	4.0	400	15.2	3.22	53.7	28	32
	4.5	450	15.5	3.38	56.3	28	32
	5.0	500	16.2	3.53	58.8	27	31
	5.5	550	16.5	3.69	61.5	27	31
	6.0	600	16.5	3.82	63.7	28	33
20 ● ينب نكاد*	6.2	620	16.5	3.88	64.6	29	33
	3.0	300	14.9	3.08	51.4	28	32
	3.5	350	15.2	3.31	55.2	29	33
	4.0	400	15.5	3.52	58.7	29	34
	4.5	450	16.2	3.72	62.0	29	33
	5.0	500	16.8	3.91	65.2	28	32
23 ● نكاد رضحاً	5.5	550	17.4	4.11	68.5	27	31
	6.0	600	17.4	4.28	71.4	28	33
	6.2	620	17.4	4.35	72.5	29	33
	3.5	350	15.5	3.72	62.1	31	36
	4.0	400	16.2	3.97	66.2	30	35
	4.5	450	16.5	4.20	70.1	31	36
	5.0	500	17.1	4.42	73.7	30	35
	5.5	550	17.7	4.66	77.7	30	34
	6.0	600	17.7	4.86	81.0	31	36
	6.5	650	18.0	5.05	84.2	31	36
	6.9	690	18.0	5.21	86.8	32	37
	3.5	350	16.5	4.56	76.0	34	39
	4.0	400	17.1	4.88	81.3	33	39
	4.5	450	17.4	5.18	86.3	34	40
	5.0	500	17.7	5.47	91.1	35	40
	5.5	550	18.3	5.78	96.3	35	40
	6.0	600	18.3	6.04	100.6	36	42
	6.5	650	18.6	6.29	104.8	36	42
	6.9	690	18.6	6.50	108.3	38	43
	3.5	350	17.1	4.86	80.9	33	38

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/ar/irrigation-product/i-25/traz-i-20-06-r020326>