



I-40-06-SS-R

ءارضخ لآ اآاطس م لآ یر :ءیراآ آ لآ ةم لآ علآ

ة راوآ آ اش اش ر :آ آ آ ن م لآ ط آ

آ آ ن م لآ رار ط : I-40

نوز آ م لآ ب طاف آ آ لآ ة آ آ و : I4006SSR

ة آ آ ف ، ة آ رآ 360 ى لآ 50 ن م لآ ة آ ل ل لآ ب آ ق ، م س 15 ، I-40 راوآ ش اش ر : ف ص و لآ
ءاآ آ ر ل ل ع ن آ م س ب آ م ، أ ء ص ل ل م و آ ق م لآ ذ ل و ف لآ ن م ب و ب ن أ ، (م م 25) ة ص و ب 1 ل آ آ آ
آ ل ز و ن ة آ س ع م ى آ آ ى ، ة آ ل ل آ ع م لآ ه آ ى م لآ ف ر ع م

Dimensions

م م 260.35 : ع آ ف آ ر ل لآ

6" : ز ف آ ق ل لآ ع آ ف آ ر ل

م م 50.80 : ر ط ق

م م 50.80 : ف و ش آ م لآ ر ط ق ل لآ



Operating Specifications

Arc: 50° to 360°

لآ ك س آ ب و ل ى ك 700 ى لآ 250 ن م ؛ ر آ ب 7.0 ى لآ 2.5 ن م : Operating Pressure

ة ع آ س / م ل م 10 : Precipitation Rate

م 23.2 ى لآ 13.1 : Radius

ة ق ى ق آ ر آ ل 114.1 ى لآ 27.2 ؛ ة ع آ س / م 3 6.84 ى لآ 1.63 : Flow

Shipping Information

UPC-A: 0611698156698

ة ب ى ق آ ل / لآ ة ى م ك لآ : 12

ك ى س ك م لآ ى ف ع ن ص : ل ص أ لآ

ى ط ى آ م آ و ل : 1440

ى ص ر آ آ و ل : 1080

12 : ة ى س ى ئ ر ة ن و آ ر ك

I-40 تالزونل ءادال تانايب							
لرونل	طغصل		فصن رطقل	ققدتل		لدعم بيسرتل س/م/م	
	راب	لاكسابوليك	م	ءعاسل/ل ³ رتم	ءقيدل/رتل	▲	■
8 ينب (40) حتاف	2.5	250	13.1	1.63	27.2	19	22
	3.0	300	13.4	1.80	30.0	20	23
	3.5	350	13.7	1.94	32.3	21	24
	4.0	400	14.0	2.06	34.4	21	24
	4.5	450	14.0	2.18	36.3	22	26
	5.0	500	14.3	2.29	38.2	22	26
	5.5	550	14.6	2.41	40.2	23	26
10 رضخ (41) حتاف	3.0	300	14.6	2.20	36.6	21	24
	3.5	350	14.9	2.37	39.4	21	24
	4.0	400	15.2	2.52	42.0	22	25
	4.5	450	15.5	2.67	44.5	22	25
	5.0	500	15.5	2.81	46.8	23	27
	5.5	550	15.8	2.96	49.3	24	27
	6.0	600	16.2	3.08	51.4	24	27
13 قرزأ (42) حتاف	3.0	300	14.9	2.36	39.4	21	24
	3.5	350	15.2	2.55	42.6	22	25
	4.0	400	15.5	2.73	45.5	23	26
	4.5	450	15.5	2.90	48.3	24	28
	5.0	500	15.8	3.06	51.0	24	28
	5.5	550	16.2	3.23	53.9	25	29
	6.0	600	16.5	3.38	56.3	25	29
15 يدامر (43)	3.0	300	16.2	2.93	48.8	22	26
	3.5	350	16.5	3.19	53.2	24	27
	4.0	400	16.8	3.44	57.3	24	28
	4.5	450	17.1	3.67	61.2	25	29
	5.0	500	17.4	3.89	64.9	26	30
	5.5	550	18.0	4.14	68.9	26	30
	6.0	600	18.3	4.34	72.4	26	30
23 رضخ (44) نكاد	6.2	650	18.3	4.43	73.8	26	31
	3.5	350	18.6	4.48	74.6	26	30
	4.0	400	18.9	4.76	79.4	27	31
	4.5	450	19.2	5.03	83.9	27	32
	5.0	500	19.5	5.29	88.1	28	32
	5.5	550	19.8	5.56	92.7	28	33
	6.0	600	20.1	5.79	96.5	29	33
25 قرزأ (45) نكاد	6.2	620	20.1	5.89	98.1	29	34
	6.5	650	20.1	6.01	100.2	30	34
	6.9	690	20.4	6.19	103.2	30	34
	3.5	350	19.8	4.98	83.0	25	29
	4.0	400	20.1	5.33	88.7	26	30
	4.5	450	20.4	5.65	94.2	27	31
	5.0	500	20.7	5.96	99.3	28	32
	5.5	550	21.0	6.29	104.9	28	33
	6.0	600	21.0	6.57	109.6	30	34
	6.2	620	21.0	6.69	111.5	30	35
	6.5	650	21.3	6.84	114.1	30	35
	6.9	690	21.3	7.07	117.8	31	36

ءوطحالم:

بيسرتل تالدمم باسحل .ءجرد 180 ءيوازب ليغشتلل بيسرتل تالدمم عيمج باسح م 2. يل عمةيقلا ءمسق متت ،ءجرد 360 ءيوازب شاشرلل

ءعرسل ءيلاع I-40 تالزونل ءادال تانايب							
لرونل	طغصل		فصن رطقل	ققدتل		لدعم بيسرتل س/م/م	
	راب	لاكسابوليك	م	ءعاسل/ل ³ رتم	ءقيدل/رتل	▲	■
8 ينب (40) حتاف	2.5	250	12.2	1.63	27.2	22	25
	3.0	300	12.5	1.80	30.0	23	27
	3.5	350	12.8	1.94	32.3	24	27
	4.0	400	12.8	2.06	34.4	25	29
	4.5	450	13.1	2.18	36.3	25	29
	5.0	500	13.4	2.29	38.2	25	29
	5.5	550	13.4	2.41	40.2	27	31
10 رضخ (41) حتاف	3.0	300	13.4	2.20	36.6	24	28
	3.5	350	13.7	2.37	39.4	25	29
	4.0	400	14.0	2.52	42.0	26	30
	4.5	450	14.0	2.67	44.5	27	31
	5.0	500	14.3	2.81	46.8	27	32
	5.5	550	14.6	2.96	49.3	28	32
	6.0	600	14.6	3.08	51.4	29	33
13 قرزأ (42) حتاف	3.0	300	13.7	2.36	39.4	25	29
	3.5	350	14.0	2.55	42.6	26	30
	4.0	400	14.3	2.73	45.5	27	31
	4.5	450	14.3	2.90	48.3	28	33
	5.0	500	14.6	3.06	51.0	29	33
	5.5	550	14.9	3.23	53.9	29	33
	6.0	600	14.9	3.38	56.3	30	35
15 يدامر (43)	3.0	300	15.2	2.93	48.8	25	29
	3.5	350	15.5	3.19	53.2	26	30
	4.0	400	15.8	3.44	57.3	27	32
	4.5	450	15.8	3.67	61.2	29	34
	5.0	500	16.2	3.89	64.9	30	34
	5.5	550	16.5	4.14	68.9	31	35
	6.0	600	16.5	4.34	72.4	32	37
23 رضخ (44) نكاد	6.2	620	16.5	4.43	73.8	33	38
	3.5	350	16.8	4.48	74.6	32	37
	4.0	400	17.4	4.76	79.4	32	36
	4.5	450	17.7	5.03	83.9	32	37
	5.0	500	17.7	5.29	88.1	34	39
	5.5	550	18.0	5.56	92.7	34	40
	6.0	600	18.3	5.79	96.5	35	40
25 قرزأ (45) نكاد	6.2	620	18.6	5.89	98.1	34	39
	6.5	650	18.6	6.01	100.2	35	40
	6.9	690	18.6	6.19	103.2	36	41
	3.5	350	17.4	4.98	83.0	33	38
	4.0	400	18.0	5.33	88.7	33	38
	4.5	450	18.3	5.65	94.2	34	39
	5.0	500	18.6	5.96	99.3	34	40
	5.5	550	18.9	6.29	104.9	35	41
	6.0	600	19.2	6.57	109.6	36	41
	6.2	620	19.5	6.69	111.5	35	41
	6.5	650	19.5	6.84	114.1	36	42
	6.9	690	19.5	7.07	117.8	37	43

ءوطحالم:

بيسرتل تالدمم باسحل .ءجرد 180 ءيوازب ليغشتلل بيسرتل تالدمم عيمج باسح م 2. يل عمةيقلا ءمسق متت ،ءجرد 360 ءيوازب شاشرلل

1-40 لرون ءادأ تانايب ةجودرم ل ةلباقتم ل							
لرون ل	طغصل		فصن رطق ل	ق فدت ل		لدعم ب سرتل م/س	
	راب	لاكسابوليك		ةعاسل/ل ³ رتم	ةق قدل/رتل	■	▲
15 يدامر	3.0	300	15.2	2.75	45.8	12	14
	3.5	350	15.8	2.91	48.5	12	13
	4.0	400	16.2	3.06	51.0	12	14
	4.5	450	16.8	3.20	53.3	11	13
	5.0	500	17.1	3.32	55.4	11	13
	5.5	550	17.4	3.46	57.7	11	13
	6.0	600	17.7	3.58	59.6	11	13
18 رحأ	6.2	620	17.7	3.62	60.4	12	13
	3.0	300	17.4	2.90	48.3	10	11
	3.5	350	17.7	3.15	52.5	10	12
	4.0	400	18.0	3.38	56.4	10	12
	4.5	450	18.0	3.61	60.1	11	13
	5.0	500	18.3	3.82	63.7	11	13
	5.5	550	18.9	4.05	67.5	11	13
20 نكاد ينب	6.0	600	19.2	4.25	70.8	12	13
	6.2	620	19.2	4.33	72.1	12	14
	6.5	650	19.5	4.43	73.9	12	13
	3.5	350	18.3	3.98	66.2	12	14
	4.0	400	18.9	4.26	71.1	12	14
	4.5	450	19.2	4.54	75.6	12	14
	5.0	500	19.5	4.80	80.0	13	15
23 نكاد رضحأ	5.5	550	20.1	5.08	84.7	13	15
	6.0	600	19.8	5.32	88.7	14	16
	6.2	620	19.8	5.42	90.4	14	16
	6.5	650	20.1	5.55	92.5	14	16
	6.9	690	20.1	5.74	95.7	14	16
	3.5	350	18.9	4.23	70.6	12	14
	4.0	400	19.5	4.55	75.8	12	14
25 نكاد قرزأ	4.5	450	19.8	4.85	80.8	12	14
	5.0	500	20.1	5.14	85.6	13	15
	5.5	550	20.4	5.45	90.8	13	15
	6.0	600	20.7	5.71	95.1	13	15
	6.2	620	20.7	5.82	97.0	14	16
	6.5	650	20.7	5.96	99.4	14	16
	6.9	690	21.0	6.17	102.9	14	16
28 دوسأ	3.5	350	19.5	4.60	76.7	12	14
	4.0	400	20.1	4.92	82.1	12	14
	4.5	450	20.4	5.23	87.2	13	14
	5.0	500	20.7	5.52	92.0	13	15
	5.5	550	21.0	5.84	97.3	13	15
	6.0	600	21.3	6.10	101.7	13	15
	6.2	620	21.3	6.22	103.6	14	16
	6.5	650	21.3	6.36	106.0	14	16
	6.9	690	21.6	6.57	109.5	14	16
	3.5	350	19.8	5.73	95.5	15	17
	4.0	400	20.4	6.07	101.1	15	17
	4.5	450	21.0	6.38	106.4	14	17
	5.0	500	21.3	6.68	111.3	15	17
	5.5	550	21.9	7.00	116.7	15	17
	6.0	600	22.3	7.27	121.1	15	17
	6.2	620	22.3	7.38	122.9	15	17
	6.5	650	22.6	7.52	125.3	15	17
	6.9	690	23.2	7.73	128.8	14	17
ةطحال م: ةجود 360 ةيوازب ليغشتل ل ب سرتل تالدمع عيمج باسح م							

ةجودرم ل او ةلباقتم ل 1-40 لرون ءادأ تانايب ةعسرل ةيلاع							
لرون ل	طغصل		فصن رطق ل	ق فدت ل		لدعم ب سرتل م/س	
	Bar	لاكسابوليك		ةعاسل/ل ³ رتم	ةق قدل/رتل	■	▲
15 يدامر	3.0	300	13.7	2.75	45.8	15	17
	3.5	350	14.0	2.91	48.5	15	17
	4.0	400	14.3	3.06	51.0	15	17
	4.5	450	14.6	3.20	53.3	15	17
	5.0	500	14.9	3.32	55.4	15	17
	5.5	550	15.2	3.46	57.7	15	17
18 رحأ	3.0	300	14.6	2.90	48.3	14	16
	3.5	350	14.9	3.15	52.5	14	16
	4.0	400	15.2	3.38	56.4	15	17
	4.5	450	15.4	3.61	60.1	15	18
	5.0	500	15.6	3.82	63.7	16	18
20 نكاد ينب	5.5	550	15.8	4.05	67.5	16	19
	4.0	400	15.8	4.27	71.1	17	20
	4.5	450	16.0	4.54	75.6	18	20
	5.0	500	16.2	4.80	80.0	18	21
	5.5	550	16.4	5.08	84.7	19	22
	6.0	600	16.6	5.32	88.7	19	22
23 نكاد رضحأ	6.5	650	16.9	5.55	92.5	19	22
	4.0	400	16.5	4.55	75.8	17	19
	4.5	450	16.7	4.85	80.8	17	20
	5.0	500	16.9	5.14	85.6	18	21
	5.5	550	17.1	5.45	90.8	19	22
	6.0	600	17.3	5.71	95.1	19	22
25 نكاد قرزأ	6.5	650	17.6	5.96	99.4	19	22
	4.0	400	16.8	4.93	82.1	18	20
	4.5	450	17.0	5.23	87.2	18	21
	5.0	500	17.2	5.52	92.0	19	22
	5.5	550	17.4	5.84	97.3	19	22
	6.0	600	17.6	6.10	101.7	20	23
28 دوسأ	6.5	650	17.9	6.36	106.0	20	23
	4.5	450	17.5	6.38	106.4	21	24
	5.0	500	17.7	6.68	111.3	21	25
	5.5	550	18.0	7.00	116.7	22	25
	6.0	600	18.1	7.27	121.1	22	26
	6.5	650	18.4	7.52	125.3	22	26
	7.0	696	18.7	7.76	129.4	22	26
ةطحال م: ةجود 180 اهرادقم ليغشت ةيوازب ب سرتل تالدمع عيمج باسح م تي 2. يلغ مقرل مسقا ،ةجود 360 ةيوازب شاشرل ب سرتل لدعلم							