

MP-820-210



تالزون لة راودل تاشاشرل: تاجت نمل طخ

MP Rotator راودل شاشرلل MP800 لزون: جت نمل زارط

MP820210: نورخم لاب طاقت حاله دحو

فصن، س/م لم 20: بيسرت لدغم MP Rotator راودل شاشرلل لزون: فصولا
ةجرد 270 ىل 210 ن: طبضلل لباقلا يرلا سوق، م 7.3 ىل 4.6 م: رطقل
رضخأو يدامر، ىثنأ يبلول نس

Dimensions

م لم 25.40: رطق



Operating Specifications

Arc: 210° to 270°

Operating Pressure: 2.8 راب؛ 280 لاساب وليك

Precipitation Rate: 20 م/س/م لم

Radius: 1.8 ىل 7.3 م

Flow: 0.44 ىل 0.60 م3/س؛ 7.34 ىل 10.06 لقيق/درتل

Shipping Information

UPC-A: 196055004817

ةيكيرمألا دحتمل تايالولا يف عنص: لصلألا

ةيسير ةنوترك: 200

Additional Information

يرلا سوق رايخ: 210° - 270°

رطقلا فصن: 15' - 24'

?????? ?????? ?????? MP ROTATOR - ?????? ??????*

MP800SR

??? ?????: 1.8 ??? 3.5 ?
??? ????? ??????
???????? ??????: 90° ??? 210°
???? ??????: 360°

				ىصقأال رطقل فصن						ىنأال رطقل فصن		
سوق يرلا	طغصلا				فصن ال رطقل	قو فءءال		ل دع م ب س ر س ل م / س		فصن ال رطقل	قو فءءال	
	راب	لا ك س اب و ل ي ك			م	ع ءع اس ل / م3	ع ق ي ق د ل / ر ت ل	■	▲	م	ع ءع اس ل / م3	ع ق ي ق د ل / ر ت ل
90° 	2.1	200			2.6	0.04	0.61	22	25	1.8	0.03	0.49
	2.5	250			2.9	0.04	0.72	21	24	2.1	0.03	0.55
	2.8	280			3.1	0.05	0.87	21	24	2.4	0.04	0.61
	3.0	300			3.4	0.06	0.95	20	23	2.4	0.04	0.68
	3.5	350			3.5	0.06	1.02	20	23	2.7	0.04	0.72
	3.8	380			3.5	0.06	1.06	20	23	3.0	0.05	0.76
180° 	2.1	200			2.6	0.07	1.21	22	25	1.8	0.06	0.98
	2.5	250			2.8	0.08	1.40	21	24	2.1	0.07	1.10
	2.8	280			3.0	0.10	1.59	21	24	2.4	0.07	1.21
	3.0	300			3.3	0.10	1.74	19	22	2.4	0.08	1.36
	3.5	350			3.4	0.11	1.82	19	22	2.7	0.09	1.44
	3.8	380			3.5	0.11	1.89	18	21	3.0	0.09	1.51
210° 	2.1	200			2.6	0.08	1.40	22	25	1.8	0.07	1.15
	2.5	250			2.8	0.10	1.67	22	25	2.1	0.08	1.28
	2.8	280			3.0	0.11	1.85	21	24	2.4	0.08	1.41
	3.0	300			3.2	0.12	2.01	20	23	2.4	0.10	1.59
	3.5	350			3.4	0.13	2.12	19	22	2.7	0.10	1.68
	3.8	380			3.5	0.13	2.20	18	21	3.0	0.11	1.77
360° 	2.1	200			2.6	0.14	2.38	22	25	1.8	0.11	1.78
	2.5	250			2.8	0.16	2.65	20	23	2.1	0.12	1.97
	2.8	280			3.0	0.18	2.95	20	23	2.4	0.13	2.12
	3.0	300			3.1	0.19	3.22	20	23	2.4	0.13	2.23
	3.5	350			3.3	0.20	3.33	19	21	2.7	0.14	2.38
	3.8	380			3.5	0.22	3.71	18	21	3.0	0.16	2.65

عمق ال كالت الى لوصول نكم. لأكسابوليك 280 راب 2.8 وه MP Rotator راولد شاشرلل لثمأل طغضال = قماعال دوسأل طخال
280 راب 2.8 لدع م طغضال ميطنن ةفيطوب زميتي ذلوا، رتنه نم PRS40 عم MP Rotator راولد شاشرلل م ادختسا قيرط نع ةلوهسب
لاكسابوليك.

رطقال فصن ضافخال ةجيتن بيسرل او قفتال تال ددعم ريغتت دق *

MP815

??? ?????: 2.5 ??? 4.9 ?
??? ?? ??? ????? ????? ??????
????? ?????? ??????: 90° ??? 210°
?????? ?????? ??????: 210° ??? 270°
????????? ??????: 360°

سوق يرلا	طغضال				رطقال فصن		قفتال		عأسال/مصوب بيسرل لدع م	
										
90° 	راب	لاكسابوليك			م	م/س3	عقيدل/رتل			
	2.1	210			4.3	0.10	1.59	21		24
	2.5	250			4.5	0.10	1.74	21		24
	2.8	280			4.6	0.11	1.85	21		24
	3.1	310			4.8	0.12	1.97	21		24
	3.5	350			4.9	0.12	2.08	21		24

3.8	380	4.9	0.12.20	22	25			
180° 	2.1	210		4.0	0.17	2.84	21	25
	2.5	250		4.3	0.20	3.26	21	24
	2.8	280		4.5	0.21	3.52	21	24
	3.1	310		4.6	0.22	3.63	21	24
	3.5	350		4.8	0.24	4.01	21	24
	3.8	380		4.9	0.25	4.20	21	24
210° 	2.1	210		4.0	0.20	3.33	21	25
	2.5	250		4.3	0.22	3.63	20	23
	2.8	280		4.5	0.25	4.16	21	24
	3.1	310		4.6	0.26	4.39	21	25
	3.5	350		4.8	0.28	4.69	21	24
	3.8	380		4.9	0.30	4.92	21	24
270° 	2.1	210		4.0	0.26	4.31	22	25
	2.5	250		4.3	0.28	4.69	20	23
	2.8	280		4.5	0.32	5.30	21	24
	3.1	310		4.6	0.33	5.56	21	24
	3.5	350		4.8	0.35	5.83	20	23
	3.8	380		4.9	0.37	6.09	20	23
360° 	2.1	210		4.0	0.35	5.75	22	25
	2.5	250		4.3	0.39	6.43	21	24
	2.8	280		4.5	0.42	7.08	21	24
	3.1	310		4.6	0.45	7.57	21	25
	3.5	350		4.8	0.48	8.06	21	24
	3.8	380		4.9	0.51	8.55	21	25

????? ?????? ?????? = ????? ?????? ?????? ?????? MP Rotator ?? 2.8 ????? 280 ??????????.
 ????? ?????? ??? ??? ?????? ?????? ?? ????? ??????? ?????? ?????? MP Rotator
 ?? Pro-Spray PRS40? ????? ?????? ?????? ?????? ?????? ?????? 2.8 ????? 280 ??????????.

MP-815				دور طاقلا فصن			
				و طبصلل لباقي سوق			
				دامرل او رمحمل ينبل			
				دامرل او ختافل قررال			
				رل او ينوتيرل**			
صن	قو	ل	سوق	ليغشت	وليك	م	
ال	ال	ال	ال	ال	ال	ال	
				bar	ال		
90° 	2.1	210				4.3	
	2.5	250				4.5	
	2.8	280				4.6	
	3.1	310				4.8	
	3.5	350				4.9	
180° 	3.8	380				4.9	
	2.1	210				4.0	
	2.5	250				4.3	
	2.8	280				4.5	
	3.1	310				4.6	
210° 	3.5	350				4.8	
	3.8	380				4.9	
	2.1	210				4.0	
	2.5	250				4.3	
	2.8	280				4.5	
270° 	3.1	310				4.6	
	3.5	350				4.8	
	3.8	380				4.9	
	2.1	210				4.0	
	2.5	250				4.3	
360° 	2.8	280				4.5	
	3.1	310				4.6	
	3.5	350				4.8	
	3.8	380				4.9	
	2.1	210				4.0	

ب 2.8 وه MP راودل شاشرلل لثمأل طغضل = **يوق**
 MP Rota راودل شاشرلل م ادختساب ةل وه سب كلذ
 ب 2.8 دن ع طغض مي طن ت م تي ذلا

MP-820

Radius: 16' to 24'
Adjustable Arc & Full-Circle
Black and gray: 90° to 210°
Green and gray: 210° to 270°
Red and gray: 360°

Arc	Pressure		Radius	Flow	Precip in/hr	
	PSI		ft	GPM	■	▲
90° 	30		20	0.85	0.82	0.94
	35		21	0.93	0.81	0.94
	40		22	0.97	0.77	0.89
	45		23	1.06	0.77	0.89
	50		24	1.11	0.74	0.85
180° 	55		24	1.16	0.77	0.89
	30		20	1.72	0.83	0.96
	35		21	1.82	0.79	0.91
	40		22	2.01	0.80	0.92
	45		22	2.06	0.82	0.95
210° 	50		23	2.21	0.80	0.93
	55		24	2.36	0.79	0.91
	30		20	1.94	0.80	0.92
	35		21	2.10	0.78	0.91
	40		22	2.36	0.81	0.93
270° 	45		22	2.39	0.81	0.94
	50		23	2.52	0.79	0.91
	55		24	2.66	0.76	0.88
	30		20	2.53	0.81	0.94
	35		21	2.74	0.80	0.92
360° 	40		22	3.00	0.80	0.92
	45		22	3.12	0.83	0.96
	50		23	3.30	0.80	0.93
	55		24	3.48	0.78	0.90
	30		20	3.40	0.82	0.94
	35		21	3.68	0.80	0.93
	40		22	3.97	0.79	0.91
	45		22	4.08	0.81	0.94
	50		23	4.30	0.78	0.90
	55		24	4.53	0.76	0.87

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 40 PSI.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/ar/irrigation-product/nwzl-mp800-llrshash-aldwar-mp-rotator/mp-820-210020326>