

Pro Adjustable Nozzles

For reliable coverage in any landscape setting, choose Pro Adjustable Nozzles.

أساسيات التثبيت

- Adjustable from 0° to 360° for maximum design flexibility
- Easy-grip top for simple adjustment
- Strong edges for a defined pattern with better wind resistance
- Large water droplets minimise misting with better uniformity
- Even distribution results in better coverage
- Colour-coded for easy field identification

Operating Specifications

- Recommended operating pressure: 2.1 bar; 210 kPa
- Pair with Pro-Spray™ PR530 pop-up for pressure regulation to 2.1 bar; 210 kPa
- Warranty period: 2 years



		NOZZLE 4A LT. GREEN •						NOZZLE 6A LT. BLUE •					
		1,2 m radius Adjustable from 0° to 360 Trajectory 0°						1,8 m radius Adjustable from 0° to 360 Trajectory 0°					
Arc	Pressure	Radius	Flow		Precip mm/hr		Radius	Flow		Precip mm/hr			
	bar	kPa	m	m³/hr	l/min	■ ▲	m	m³/hr	l/min	■ ▲			
45° 	1,0	100	0,9	0,02	0,31	187 216	1,5	0,03	0,54	117	136		
	1,5	150	1,0	0,02	0,39	178 206	1,6	0,04	0,60	108	124		
	2,1	210	1,2	0,03	0,48	167 193	1,8	0,04	0,65	98	114		
	2,5	250	1,3	0,03	0,56	158 183	1,9	0,04	0,70	92	106		
	3,0	300	1,4	0,04	0,64	149 172	2,1	0,05	0,75	86	99		
90° 	1,0	100	0,9	0,04	0,72	213 246	1,5	0,06	1,08	116	134		
	1,5	150	1,0	0,05	0,76	182 210	1,6	0,07	1,21	109	126		
	2,1	210	1,2	0,05	0,83	139 160	1,8	0,08	1,35	102	118		
	2,5	250	1,3	0,05	0,91	129 149	1,9	0,09	1,47	97	112		
	3,0	300	1,4	0,06	0,95	116 134	2,1	0,10	1,61	92	106		
120° 	1,0	100	0,9	0,06	0,97	221 255	1,5	0,08	1,26	102	118		
	1,5	150	1,0	0,07	1,10	188 217	1,6	0,09	1,43	97	112		
	2,1	210	1,2	0,07	1,25	162 187	1,8	0,10	1,61	91	105		
	2,5	250	1,3	0,08	1,36	146 168	1,9	0,11	1,76	87	100		
	3,0	300	1,4	0,09	1,49	131 151	2,1	0,12	1,93	82	95		
180° 	1,0	100	0,9	0,07	1,18	178 206	1,5	0,10	1,70	92	106		
	1,5	150	1,0	0,08	1,38	157 181	1,6	0,12	1,96	88	102		
	2,1	210	1,2	0,10	1,60	139 160	1,8	0,13	2,24	84	97		
	2,5	250	1,3	0,11	1,78	127 146	1,9	0,15	2,47	81	94		
	3,0	300	1,4	0,12	1,98	115 133	2,1	0,16	2,72	78	90		
240° 	1,0	100	0,9	0,12	1,94	220 254	1,5	0,15	2,44	99	114		
	1,5	150	1,0	0,13	2,24	192 221	1,6	0,17	2,83	96	111		
	2,1	210	1,2	0,16	2,59	168 194	1,8	0,20	3,28	92	107		
	2,5	250	1,3	0,17	2,86	153 177	1,9	0,22	3,63	89	103		
	3,0	300	1,4	0,19	3,17	139 160	2,1	0,24	4,03	86	99		
270° 	1,0	100	0,9	0,13	2,09	211 244	1,5	0,18	3,08	111	128		
	1,5	150	1,0	0,14	2,40	183 211	1,6	0,21	3,52	106	122		
	2,1	210	1,2	0,16	2,75	159 183	1,8	0,24	4,02	101	116		
	2,5	250	1,3	0,18	3,02	144 166	1,9	0,27	4,42	97	112		
	3,0	300	1,4	0,20	3,33	130 150	2,1	0,29	4,87	92	107		
360° 	1,0	100	0,9	0,14	2,26	171 197	1,5	0,21	3,57	96	111		
	1,5	150	1,0	0,16	2,60	148 171	1,6	0,24	4,07	92	106		
	2,1	210	1,2	0,18	2,98	129 149	1,8	0,28	4,62	87	100		
	2,5	250	1,3	0,20	3,29	117 135	1,9	0,30	5,06	83	96		
	3,0	300	1,4	0,22	3,63	106 122	2,1	0,33	5,56	79	92		

		NOZZLE 8A BROWN •						NOZZLE 10A RED •					
		2,4 m radius Adjustable from 0° to 360 Trajectory 0°						3,0 m radius Adjustable from 0° to 360 Trajectory 15°					
Arc	Pressure	Radius	Flow		Precip mm/hr		Radius	Flow		Precip mm/hr			
	bar kPa	m	m³/hr	l/min	■	▲	m	m³/hr	l/min	■	▲		
45° 	1,0	100	2,0	0,04	0,62	77	89	2,6	0,04	0,68	49	56	
	1,5	150	2,2	0,04	0,72	72	83	2,8	0,05	0,80	49	57	
	2,1	210	2,4	0,05	0,83	67	77	3,0	0,06	0,94	49	56	
	2,5	250	2,6	0,05	0,91	63	73	3,2	0,06	1,06	48	56	
	3,0	300	2,9	0,06	1,01	59	68	3,5	0,07	1,18	47	54	
90° 	1,0	100	2,0	0,07	1,24	77	89	2,6	0,08	1,35	49	56	
	1,5	150	2,2	0,09	1,44	72	83	2,8	0,10	1,61	49	57	
	2,1	210	2,4	0,10	1,65	67	77	3,0	0,11	1,89	49	56	
	2,5	250	2,6	0,11	1,82	63	73	3,2	0,13	2,11	48	56	
	3,0	300	2,9	0,12	2,02	59	68	3,5	0,14	2,37	47	54	
120° 	1,0	100	2,0	0,10	1,66	77	89	2,6	0,11	1,80	49	56	
	1,5	150	2,2	0,11	1,92	72	83	2,8	0,13	2,14	49	57	
	2,1	210	2,4	0,13	2,20	67	77	3,0	0,15	2,52	49	56	
	2,5	250	2,6	0,15	2,43	63	73	3,2	0,17	2,82	48	56	
	3,0	300	2,9	0,16	2,69	59	68	3,5	0,19	3,16	47	54	
180° 	1,0	100	2,0	0,15	2,49	77	89	2,6	0,16	2,71	49	56	
	1,5	150	2,2	0,17	2,87	72	83	2,8	0,19	3,21	49	57	
	2,1	210	2,4	0,20	3,30	67	77	3,0	0,23	3,78	49	56	
	2,5	250	2,6	0,22	3,65	63	73	3,2	0,25	4,23	48	56	
	3,0	300	2,9	0,24	4,03	59	68	3,5	0,28	4,73	47	54	
240° 	1,0	100	2,0	0,20	3,32	77	89	2,6	0,22	3,61	49	56	
	1,5	150	2,2	0,23	3,83	72	83	2,8	0,26	4,28	49	57	
	2,1	210	2,4	0,26	4,40	67	77	3,0	0,30	5,03	49	56	
	2,5	250	2,6	0,29	4,86	63	73	3,2	0,34	5,64	48	56	
	3,0	300	2,9	0,32	5,38	59	68	3,5	0,38	6,31	47	54	
270° 	1,0	100	2,0	0,22	3,73	77	89	2,6	0,24	4,06	49	56	
	1,5	150	2,2	0,26	4,31	72	83	2,8	0,29	4,82	49	57	
	2,1	210	2,4	0,30	4,95	67	77	3,0	0,34	5,66	49	56	
	2,5	250	2,6	0,33	5,47	63	73	3,2	0,38	6,34	48	56	
	3,0	300	2,9	0,36	6,05	59	68	3,5	0,43	7,10	47	54	
360° 	1,0	100	2,0	0,30	4,97	77	89	2,6	0,32	5,41	49	56	
	1,5	150	2,2	0,34	5,75	72	83	2,8	0,39	6,43	49	57	
	2,1	210	2,4	0,40	6,61	67	77	3,0	0,45	7,55	49	56	
	2,5	250	2,6	0,44	7,29	63	73	3,2	0,51	8,45	48	56	
	3,0	300	2,9	0,48	8,07	59	68	3,5	0,57	9,47	47	54	

		NOZZLE 12A GREEN •						NOZZLE 15A BLACK •						NOZZLE 17A GREY •					
		3,7 m radius Adjustable from 0° to 360 Trajectory 28°						4,6 m radius Adjustable from 0° to 360 Trajectory 28°						5,2 m radius Adjustable from 0° to 360 Trajectory 28°					
Arc	Pressure	Radius	Flow		Precip mm/hr		Radius	Flow		Precip mm/hr		Radius	Flow		Precip mm/hr				
	bar kPa	m	m³/hr	l/min			m	m³/hr	l/min			m	m³/hr	l/min					
45°	1,0 100	3,2	0,04	0,73	34	40	4,0	0,08	1,27	38	43	4,6	0,10	1,68	38	43			
	1,5 150	3,4	0,06	0,97	40	46	4,3	0,09	1,51	39	45	4,9	0,12	1,94	38	44			
	2,1 210	3,7	0,07	1,23	44	51	4,6	0,11	1,79	40	46	5,2	0,13	2,23	39	45			
	2,5 250	3,9	0,09	1,44	46	54	4,9	0,12	2,00	40	46	5,5	0,15	2,46	39	45			
	3,0 300	4,1	0,10	1,68	48	56	5,2	0,14	2,25	40	46	5,8	0,16	2,72	39	45			
90°	1,0 100	3,2	0,09	1,46	34	40	4,0	0,15	2,53	38	43	4,6	0,20	3,36	38	43			
	1,5 150	3,4	0,12	1,93	40	46	4,3	0,18	3,03	39	45	4,9	0,23	3,88	38	44			
	2,1 210	3,7	0,15	2,46	44	51	4,6	0,21	3,57	40	46	5,2	0,27	4,45	39	45			
	2,5 250	3,9	0,17	2,88	46	54	4,9	0,24	4,01	40	46	5,5	0,30	4,92	39	45			
	3,0 300	4,1	0,20	3,36	48	56	5,2	0,27	4,50	40	46	5,8	0,33	5,44	39	45			
120°	1,0 100	3,2	0,12	1,94	34	40	4,0	0,20	3,38	38	43	4,6	0,27	4,48	38	43			
	1,5 150	3,4	0,15	2,58	40	46	4,3	0,24	4,03	39	45	4,9	0,31	5,17	38	44			
	2,1 210	3,7	0,20	3,28	44	51	4,6	0,29	4,76	40	46	5,2	0,36	5,94	39	45			
	2,5 250	3,9	0,23	3,84	46	54	4,9	0,32	5,34	40	46	5,5	0,39	6,56	39	45			
	3,0 300	4,1	0,27	4,48	48	56	5,2	0,36	6,00	40	46	5,8	0,43	7,25	39	45			
180°	1,0 100	3,2	0,17	2,91	34	40	4,0	0,30	5,07	38	43	4,6	0,40	6,71	38	43			
	1,5 150	3,4	0,23	3,86	40	46	4,3	0,36	6,05	39	45	4,9	0,47	7,75	38	44			
	2,1 210	3,7	0,30	4,92	44	51	4,6	0,43	7,14	40	46	5,2	0,53	8,91	39	45			
	2,5 250	3,9	0,35	5,76	46	54	4,9	0,48	8,02	40	46	5,5	0,59	9,83	39	45			
	3,0 300	4,1	0,40	6,71	48	56	5,2	0,54	9,00	40	46	5,8	0,65	10,87	39	45			
240°	1,0 100	3,2	0,23	3,88	34	40	4,0	0,41	6,76	38	43	4,6	0,54	8,95	38	43			
	1,5 150	3,4	0,31	5,15	40	46	4,3	0,48	8,07	39	45	4,9	0,62	10,34	38	44			
	2,1 210	3,7	0,39	6,56	44	51	4,6	0,57	9,52	40	46	5,2	0,71	11,88	39	45			
	2,5 250	3,9	0,46	7,68	46	54	4,9	0,64	10,69	40	46	5,5	0,79	13,11	39	45			
	3,0 300	4,1	0,54	8,95	48	56	5,2	0,72	12,00	40	46	5,8	0,87	14,50	39	45			
270°	1,0 100	3,2	0,26	4,37	34	40	4,0	0,46	7,60	38	43	4,6	0,60	10,07	38	43			
	1,5 150	3,4	0,35	5,80	40	46	4,3	0,54	9,08	39	45	4,9	0,70	11,63	38	44			
	2,1 210	3,7	0,44	7,38	44	51	4,6	0,64	10,71	40	46	5,2	0,80	13,36	39	45			
	2,5 250	3,9	0,52	8,65	46	54	4,9	0,72	12,03	40	46	5,5	0,89	14,75	39	45			
	3,0 300	4,1	0,60	10,07	48	56	5,2	0,81	13,50	40	46	5,8	0,98	16,31	39	45			
360°	1,0 100	3,2	0,35	5,83	34	40	4,0	0,61	10,13	38	43	4,6	0,81	13,43	38	43			
	1,5 150	3,4	0,46	7,73	40	46	4,3	0,73	12,10	39	45	4,9	0,93	15,51	38	44			
	2,1 210	3,7	0,59	9,84	44	51	4,6	0,86	14,28	40	46	5,2	1,07	17,82	39	45			
	2,5 250	3,9	0,69	11,53	46	54	4,9	0,96	16,03	40	46	5,5	1,18	19,67	39	45			
	3,0 300	4,1	0,81	13,43	48	56	5,2	1,08	18,00	40	46	5,8	1,30	21,75	39	45			

Bold = Recommended pressure

Note: The Pro-Spray PRS30's built-in pressure regulator controls output to a maximum of 2,1 bar; 210 kPa. Adjusting the radius reduction screw may be required to achieve catalogue radius and flow.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.