

G-835

The Ultimate TTS Solution for Short and mid-range golf applications



- Adjustable, shorter-radius model (50° to 360°)
- Proprietary Filter Sentry™ Mechanism cleans the filter with every opening and closing cycle

MODEL SPECIFICATIONS

- Full-Circle / Part-Circle (50° to 360°)

MODEL VARIATIONS

- C** = Check-O-Matic checks up to 25' in elevation change and the top connections
- D** = Decoder Valve-In-Head with all "E" specifications below.
- DD** = 2-Station Decoder Valve-In-Head with all "E" specifications below
- E** = Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 190mA (350mA inrush) solenoid with captive plunger and internal downstream bleed.



OPERATING SPECIFICATIONS

- Discharge rate: 1.9 to 12.8 GPM
- Radius: 18' to 50'
- Pressure range: 40 to 65 PSI
- Pressure rating: 150 PSI



G835

Overall Height	11-3/4"
Pop-up Height	3"
Flange Diameter	7-1/4"
Inlet Size	1-1/2" Female ACME

G835 / G35B NOZZLE PERFORMANCE DATA*					
Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM		
2  Yellow	40	18	1.9	0.56	0.65
	50	20	2.1	0.51	0.58
	60	22	2.4	0.48	0.55
	65	23	2.6	0.47	0.55
3  Yellow	40	23	3.0	0.55	0.63
	50	25	3.2	0.49	0.57
	60	27	3.5	0.46	0.53
	65	28	3.6	0.44	0.51
4  Yellow	40	25	3.9	0.60	0.69
	50	28	4.1	0.50	0.58
	60	30	4.4	0.47	0.54
	65	31	4.6	0.46	0.53
5  Yellow	40	29	4.7	0.54	0.62
	50	32	5.0	0.47	0.54
	60	33	5.3	0.47	0.54
	65	35	5.4	0.42	0.49
6  Yellow	40	32	6.0	0.56	0.65
	50	35	6.3	0.50	0.57
	60	37	6.6	0.46	0.54
	65	39	6.8	0.43	0.50
8  Yellow	40	36	7.8	0.58	0.67
	50	39	8.0	0.51	0.58
	60	42	8.3	0.45	0.52
	65	43	8.5	0.44	0.51
10  Yellow	40	39	9.7	0.61	0.71
	50	43	10.1	0.53	0.61
	60	45	10.3	0.49	0.57
	65	47	10.5	0.46	0.53
12  Yellow	40	44	12.0	0.60	0.69
	50	47	12.2	0.53	0.61
	60	48	12.5	0.52	0.60
	65	50	12.8	0.49	0.57
Note: *Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.					

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/node/26196>
 020326