

MP **MP800**

MP [] MP800 []

--	--	--	--

- 20 
-  MP800 
- 
- 
- 
-  MP 

--	--	--	--

-  25%
-  2.8 bar  280 kPa
-  2.1 bar, 210 kPa
- 
-  3 

--	--

- Pro-Spray® PRS40 2.8 bar/280 kPa
- Pro-Spray PRS30 2.1 bar/210 kPa



MP ROTATOR ???? - ??*

MP800SR

???1.8 ? 3.5 ?
 ????
 ?????90° ? 210°
 ?????360°

				mm					mm		
						mm					
	bar	kPa		m	m³/hr	l/min	mm	mm	m	m³/hr	l/min
	2.1	200		2.6	0.04	0.61	22	25	1.8	0.03	0.49
	2.5	250		2.9	0.04	0.72	21	24	2.1	0.03	0.55
	2.8	280		3.1	0.05	0.87	21	24	2.4	0.04	0.61
	3.0	300		3.4	0.06	0.95	20	23	2.4	0.04	0.68
	3.5	350		3.5	0.06	1.02	20	23	2.7	0.04	0.72
	3.8	380		3.5	0.06	1.06	20	23	3.0	0.05	0.76
	2.1	200		2.6	0.07	1.21	22	25	1.8	0.06	0.98
	2.5	250		2.8	0.08	1.40	21	24	2.1	0.07	1.10
	2.8	280		3.0	0.10	1.59	21	24	2.4	0.07	1.21
	3.0	300		3.3	0.10	1.74	19	22	2.4	0.08	1.36
	3.5	350		3.4	0.11	1.82	19	22	2.7	0.09	1.44
	3.8	380		3.5	0.11	1.89	18	21	3.0	0.09	1.51
	2.1	200		2.6	0.08	1.40	22	25	1.8	0.07	1.15
	2.5	250		2.8	0.10	1.67	22	25	2.1	0.08	1.28
	2.8	280		3.0	0.11	1.85	21	24	2.4	0.08	1.41
	3.0	300		3.2	0.12	2.01	20	23	2.4	0.10	1.59
	3.5	350		3.4	0.13	2.12	19	22	2.7	0.10	1.68
	3.8	380		3.5	0.13	2.20	18	21	3.0	0.11	1.77
	2.1	200		2.6	0.14	2.38	22	25	1.8	0.11	1.78
	2.5	250		2.8	0.16	2.65	20	23	2.1	0.12	1.97
	2.8	280		3.0	0.18	2.95	20	23	2.4	0.13	2.12
	3.0	300		3.1	0.19	3.22	20	23	2.4	0.13	2.23
	3.5	350		3.3	0.20	3.33	19	21	2.7	0.14	2.38
	3.8	380		3.5	0.22	3.71	18	21	3.0	0.16	2.65

MP Rotator 2.8 bar 280 kPa Hunter PRS40 MP Rotator 2.8 bar 280 kPa

MP815

		barkPa	m m3/hr/min						
90°	2.1	210	4.3	0.10	1.59	21	24		
	2.5	250	4.5	0.10	1.74	21	24		
	2.8	280	4.6	0.11	1.85	21	24		
	3.1	310	4.8	0.12	1.97	21	24		
	3.5	350	4.9	0.12	2.08	21	24		
	3.8	380	4.9	0.13	2.20	22	25		
180°	2.1	210	4.0	0.17	2.84	21	25		
	2.5	250	4.3	0.20	3.26	21	24		
	2.8	280	4.5	0.21	3.52	21	24		
	3.1	310	4.6	0.22	3.63	21	24		
	3.5	350	4.8	0.24	4.01	21	24		
	3.8	380	4.9	0.25	4.20	21	24		
210°	2.1	210	4.0	0.20	3.33	21	25		
	2.5	250	4.3	0.22	3.63	20	23		
	2.8	280	4.5	0.25	4.16	21	24		
	3.1	310	4.6	0.26	4.39	21	25		
	3.5	350	4.8	0.28	4.69	21	24		
	3.8	380	4.9	0.30	4.92	21	24		
270°	2.1	210	4.0	0.26	4.31	22	25		
	2.5	250	4.3	0.28	4.69	20	23		
	2.8	280	4.5	0.32	5.30	21	24		
	3.1	310	4.6	0.33	5.56	21	24		
	3.5	350	4.8	0.35	5.83	20	23		
	3.8	380	4.9	0.37	6.09	20	23		
360°	2.1	210	4.0	0.35	5.75	22	25		
	2.5	250	4.3	0.39	6.43	21	24		
	2.8	280	4.5	0.42	7.08	21	24		
	3.1	310	4.6	0.45	7.57	21	25		
	3.5	350	4.8	0.48	8.06	21	24		
	3.8	380	4.9	0.51	8.55	21	25		

MP-815

2.5 m 4.9 m

90° 210°

90° 210°

210° 270°

360°

MP	MP			MP	MP		MP/MP	
	bar	kPa		m	m3/hr	MP	MP	MP
90° 	2.1	210		4.3	0.10	1.59	21	24
	2.5	250		4.5	0.10	1.74	21	24
	2.8	280		4.6	0.11	1.85	21	24
	3.1	310		4.8	0.12	1.97	21	24
	3.5	350		4.9	0.12	2.08	21	24
	3.8	380		4.9	0.13	2.20	22	25
180° 	2.1	210		4.0	0.17	2.84	21	25
	2.5	250		4.3	0.20	3.26	21	24
	2.8	280		4.5	0.21	3.52	21	24
	3.1	310		4.6	0.22	3.63	21	24
	3.5	350		4.8	0.24	4.01	21	24
	3.8	380		4.9	0.25	4.20	21	24
210° 	2.1	210		4.0	0.20	3.33	21	25
	2.5	250		4.3	0.22	3.63	20	23
	2.8	280		4.5	0.25	4.16	21	24
	3.1	310		4.6	0.26	4.39	21	25
	3.5	350		4.8	0.28	4.69	21	24
	3.8	380		4.9	0.30	4.92	21	24
270° 	2.1	210		4.0	0.26	4.31	22	25
	2.5	250		4.3	0.28	4.69	20	23
	2.8	280		4.5	0.32	5.30	21	24
	3.1	310		4.6	0.33	5.56	21	24
	3.5	350		4.8	0.35	5.83	20	23
	3.8	380		4.9	0.37	6.09	20	23
360° 	2.1	210		4.0	0.35	5.75	22	25
	2.5	250		4.3	0.39	6.43	21	24
	2.8	280		4.5	0.42	7.08	21	24
	3.1	310		4.6	0.45	7.57	21	25
	3.5	350		4.8	0.48	8.06	21	24
	3.8	380		4.9	0.51	8.55	21	25

MP 2.8 bar280 kPa Pro-Spray PRS40 MP 2.8 bar280 kPa

MP-820

7.3
90°210°
210°270°
360°

MP	MP			MP	MP	MP/MP
	bar	kPa		m	m3/hr	MP/MP
90° 	2.1	210		6.1	0.19	3.20 21 24
	2.5	250		6.4	0.21	3.51 21 24
	2.8	280		6.7	0.22	3.65 20 23
	3.0	300		7.0	0.24	4.01 20 23
	3.5	350		7.3	0.25	4.19 19 22
	3.8	380		7.3	0.26	4.37 20 23
180° 	2.1	210		6.1	0.39	6.50 21 24
	2.5	250		6.4	0.41	6.86 20 23
	2.8	280		6.7	0.46	7.58 20 23
	3.0	300		6.7	0.47	7.79 21 24
	3.5	350		7.0	0.50	8.36 20 24
	3.8	380		7.3	0.54	8.92 20 23
210° 	2.1	210		6.1	0.44	7.34 20 23
	2.5	250		6.4	0.48	7.92 20 23
	2.8	280		6.7	0.54	8.93 20 24
	3.0	300		6.7	0.54	9.02 21 24
	3.5	350		7.0	0.57	9.54 20 23
	3.8	380		7.3	0.60	10.06 19 22
270° 	2.1	210		6.1	0.58	9.58 21 24
	2.5	250		6.4	0.62	10.36 20 23
	2.8	280		6.7	0.68	11.35 20 23
	3.0	300		6.7	0.71	11.81 21 24
	3.5	350		7.0	0.75	12.49 20 24
	3.8	380		7.3	0.79	13.16 20 23
360° 	2.1	210		6.1	0.77	12.85 21 24
	2.5	250		6.4	0.84	13.92 20 24
	2.8	280		6.7	0.90	14.99 20 23
	3.0	300		6.7	0.93	15.41 21 24
	3.5	350		7.0	0.98	16.27 20 23
	3.8	380		7.3	1.03	17.13 19 22

MP 2.8 bar280 kPa Pro-Spray PRS40 MP 2.8 bar280 kPa

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/mp-rotator/mp-xuanzhuanshexianpentour-mp800-penzui>
020326