



MP-815-360

1/2" NPT
1/2" MP 1/2" NPT
1/2" MP 1/2" NPT® MP800 1/2"
SKU: MP815360
1/2" MP 1/2" NPT 20 1/2" / 1/2" NPT 2.5 1/2" 4.9 1/2" 360° 1/2"

Operating Specifications

Arc: 360°

Shipping Information

UPC-A: 0611698461105
1/2" / 200
1/2" 1/2" 00
1/2" 1/2" 00
1/2" 1/2" 00
1/2" 1/2"

Additional Information

1/2" 360°
1/2" Approx 0.8 in/hr
1/2" 8' - 16'

MP ROTATOR ???? - ??*

MP800SR

???1.8 ? 3.5 ?
????
???????90° ? 210°
???????360°

						mm/h					
	bar	kPa		m	m ³ /hr	l/min	■	▲	m	m ³ /hr	l/min
90° 	2.1	200		2.6	0.04	0.61	22	25	1.8	0.03	0.49
	2.5	250		2.9	0.04	0.72	21	24	2.1	0.03	0.55
	2.8	280		3.1	0.05	0.87	21	24	2.4	0.04	0.61
	3.0	300		3.4	0.06	0.95	20	23	2.4	0.04	0.68
	3.5	350		3.5	0.06	1.02	20	23	2.7	0.04	0.72
	3.8	380		3.5	0.06	1.06	20	23	3.0	0.05	0.76
180° 	2.1	200		2.6	0.07	1.21	22	25	1.8	0.06	0.98
	2.5	250		2.8	0.08	1.40	21	24	2.1	0.07	1.10
	2.8	280		3.0	0.10	1.59	21	24	2.4	0.07	1.21
	3.0	300		3.3	0.10	1.74	19	22	2.4	0.08	1.36
	3.5	350		3.4	0.11	1.82	19	22	2.7	0.09	1.44
	3.8	380		3.5	0.11	1.89	18	21	3.0	0.09	1.51
210° 	2.1	200		2.6	0.08	1.40	22	25	1.8	0.07	1.15
	2.5	250		2.8	0.10	1.67	22	25	2.1	0.08	1.28
	2.8	280		3.0	0.11	1.85	21	24	2.4	0.08	1.41
	3.0	300		3.2	0.12	2.01	20	23	2.4	0.10	1.59
	3.5	350		3.4	0.13	2.12	19	22	2.7	0.10	1.68
	3.8	380		3.5	0.13	2.20	18	21	3.0	0.11	1.77
360° 	2.1	200		2.6	0.14	2.38	22	25	1.8	0.11	1.78
	2.5	250		2.8	0.16	2.65	20	23	2.1	0.12	1.97
	2.8	280		3.0	0.18	2.95	20	23	2.4	0.13	2.12
	3.0	300		3.1	0.19	3.22	20	23	2.4	0.13	2.23
	3.5	350		3.3	0.20	3.33	19	21	2.7	0.14	2.38
	3.8	380		3.5	0.22	3.71	18	21	3.0	0.16	2.65

MP Rotator 2.8 bar280 kPa Hunter PR540 MP Rotator 2.8 bar280 kPa

*

MP815

???2.5 ? 4.9 m
????????
???????90° ? 210°
???????210° ? 270°
???????360°

	bar	kPa		m	m ³ /hr	l/min	■	▲
90° 	2.1	210		4.3	0.10	1.59	21	24
	2.5	250		4.5	0.10	1.74	21	24
	2.8	280		4.6	0.11	1.85	21	24
	3.1	310		4.8	0.12	1.97	21	24
	3.5	350		4.9	0.12	2.08	21	24
	3.8	380		4.9	0.13	2.20	22	25

180° 	2.1	210		4.0	0.17	2.84	21	25
	2.5	250		4.3	0.20	3.26	21	24
	2.8	280		4.5	0.21	3.52	21	24
	3.1	310		4.6	0.22	3.63	21	24
	3.5	350		4.8	0.24	4.01	21	24
210° 	3.8	380		4.9	0.25	4.20	21	24
	2.1	210		4.0	0.20	3.33	21	25
	2.5	250		4.3	0.22	3.63	20	23
	2.8	280		4.5	0.25	4.16	21	24
	3.1	310		4.6	0.26	4.39	21	25
270° 	3.5	350		4.8	0.28	4.69	21	24
	3.8	380		4.9	0.30	4.92	21	24
	2.1	210		4.0	0.26	4.31	22	25
	2.5	250		4.3	0.28	4.69	20	23
	2.8	280		4.5	0.32	5.30	21	24
360° 	3.1	310		4.6	0.33	5.56	21	24
	3.5	350		4.8	0.35	5.83	20	23
	3.8	380		4.9	0.37	6.09	20	23
	2.1	210		4.0	0.35	5.75	22	25
	2.5	250		4.3	0.39	6.43	21	24
	2.8	280		4.5	0.42	7.08	21	24
	3.1	310		4.6	0.45	7.57	21	25
	3.5	350		4.8	0.48	8.06	21	24
	3.8	380		4.9	0.51	8.55	21	25

?? = MP Rotator ?????? 2.8 ??280 ???????????? Pro-Spray PRS40 ? MP Rotator ????????????? 2.8 ??280 ???

MP-815									
									
2.5 4.9 m									
									
90°210°									
210°270°									
360°									
°	bar	kPa	m	m3/hr	°	■	▲		
90° 	2.1	210		4.3	0.10	1.59	21	24	
	2.5	250		4.5	0.10	1.74	21	24	
	2.8	280		4.6	0.11	1.85	21	24	
	3.1	310		4.8	0.12	1.97	21	24	
	3.5	350		4.9	0.12	2.08	21	24	
180° 	3.8	380		4.9	0.13	2.20	22	25	
	2.1	210		4.0	0.17	2.84	21	25	
	2.5	250		4.3	0.20	3.26	21	24	
	2.8	280		4.5	0.21	3.52	21	24	
	3.1	310		4.6	0.22	3.63	21	24	
210° 	3.5	350		4.8	0.24	4.01	21	24	
	3.8	380		4.9	0.25	4.20	21	24	
	2.1	210		4.0	0.20	3.33	21	25	
	2.5	250		4.3	0.22	3.63	20	23	
	2.8	280		4.5	0.25	4.16	21	24	
270° 	3.1	310		4.6	0.26	4.39	21	25	
	3.5	350		4.8	0.28	4.69	21	24	
	3.8	380		4.9	0.30	4.92	21	24	
	2.1	210		4.0	0.26	4.31	22	25	
	2.5	250		4.3	0.28	4.69	20	23	
360° 	2.8	280		4.5	0.32	5.30	21	24	
	3.1	310		4.6	0.33	5.56	21	24	
	3.5	350		4.8	0.35	5.83	20	23	
	3.8	380		4.9	0.37	6.09	20	23	
	2.1	210		4.0	0.35	5.75	22	25	
	2.5	250		4.3	0.39	6.43	21	24	
	2.8	280		4.5	0.42	7.08	21	24	
	3.1	310		4.6	0.45	7.57	21	25	
	3.5	350		4.8	0.48	8.06	21	24	
	3.8	380		4.9	0.51	8.55	21	25	

MP 2.8 bar280 kPa Pro-Spray PRS40 MP

MP-820

4.8 7.3
210°
270°
360°

	bar	kPa	m	m3/hr	l/h	■	▲
90° 	2.1	210	6.1	0.19	3.20	21	24
	2.5	250	6.4	0.21	3.51	21	24
	2.8	280	6.7	0.22	3.65	20	23
	3.0	300	7.0	0.24	4.01	20	23
	3.5	350	7.3	0.25	4.19	19	22
180° 	3.8	380	7.3	0.26	4.37	20	23
	2.1	210	6.1	0.39	6.50	21	24
	2.5	250	6.4	0.41	6.86	20	23
	2.8	280	6.7	0.46	7.58	20	23
	3.0	300	6.7	0.47	7.79	21	24
210° 	3.5	350	7.0	0.50	8.36	20	24
	3.8	380	7.3	0.54	8.92	20	23
	2.1	210	6.1	0.44	7.34	20	23
	2.5	250	6.4	0.48	7.92	20	23
	2.8	280	6.7	0.54	8.93	20	24
270° 	3.0	300	6.7	0.54	9.02	21	24
	3.5	350	7.0	0.57	9.54	20	23
	3.8	380	7.3	0.60	10.06	19	22
	2.1	210	6.1	0.58	9.58	21	24
	2.5	250	6.4	0.62	10.36	20	23
360° 	2.8	280	6.7	0.68	11.35	20	23
	3.0	300	6.7	0.71	11.81	21	24
	3.5	350	7.0	0.75	12.49	20	24
	3.8	380	7.3	0.79	13.16	20	23
	2.1	210	6.1	0.77	12.85	21	24
	2.5	250	6.4	0.84	13.92	20	24
	2.8	280	6.7	0.90	14.99	20	23
	3.0	300	6.7	0.93	15.41	21	24
	3.5	350	7.0	0.98	16.27	20	23
	3.8	380	7.3	1.03	17.13	19	22

MP 2.8 bar280 kPa Pro-Spray PRS40 MP 2.8 bar280 kPa

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/mp-xuanzhuanshexianpentoutm-mp800-penzui/mp-815-360>
020326