



I-20-04-SS-NCV

1.5" x 1/2"

1.5" x 1/2"

1.5" x 1/2"

SKU: I2004SSNCV

1.5" x 1/2" 1.5" x 1/2" 50° 360° 1/4"

Dimensions

1.5" x 1/2" 80.98 mm


1.5" x 1/2" 1.5" x 1/2"

1.5" x 1/2" 1.5" x 1/2"

1.5" x 1/2" 44.45 mm

1.5" x 1/2" 44.45 mm

1.5" x 1/2" 1/4"



Operating Specifications

Arc: 50° to 360°

Operating Pressure: 4.1 - 7.0 bar 410 - 700 kPa

Precipitation Rate: 10 mm/hr

Radius: 4.9 - 14.0 m

Flow: 0.07 - 2.22 m³/hr 1.2 to 36.0 l/min

Shipping Information

UPC-A: 0611698158173

1.5" x 1/2"

1.5" x 1/2"


1.5" x 1/2"


1.5" x 1/2"


1.5" x 1/2"

PGP Ultra / I-20:????							
??	??		??	??		?????MMI/HR?	
	bar	kPa	m	m³/hr	l/min	■	▲
10 ● ???	1.7	170	10.7	1.48	24.6	26	30
	2.0	200	11.9	1.60	26.7	23	26
	2.5	250	12.5	1.80	30.0	23	27
	3.0	300	12.8	2.01	33.5	25	28
	3.5	350	13.1	2.18	36.3	25	29
	4.0	400	13.7	2.34	39.0	25	29
	4.5	450	14.0	2.49	41.5	25	29
13 ● ???	1.7	170	11.0	1.91	31.9	32	37
	2.0	200	12.2	2.08	34.6	28	32
	2.5	250	12.8	2.34	38.9	29	33
	3.0	300	13.1	2.61	43.4	30	35
	3.5	350	13.4	2.83	47.1	31	36
	4.0	400	13.7	3.03	50.5	32	37
	4.5	450	14.0	3.23	53.8	33	38
6.0 LA ● ???	1.7	170	9.1	0.86	14.3	21	24
	2.0	200	9.4	0.94	15.6	21	24
	2.5	250	10.1	1.07	17.8	21	24
	3.0	300	10.7	1.20	20.0	21	24
	3.5	350	11.3	1.31	21.9	21	24
	4.0	400	11.6	1.42	23.6	21	24
	4.5	450	11.9	1.52	25.3	21	25
8.0 LA ● ???	1.7	170	10.1	1.17	19.5	23	27
	2.0	200	10.7	1.28	21.3	22	26
	2.5	250	11.3	1.44	24.0	23	26
	3.0	300	11.6	1.61	26.9	24	28
	3.5	350	11.9	1.76	29.3	25	29
	4.0	400	12.5	1.89	31.5	24	28
	4.5	450	12.5	2.01	33.6	26	30
????????????????180????????????360???????????							

PGP Ultra / I-20 ????????							
■■■■■■■							
??	??		??	??		?????MM/HR?	
	bar	kPa	m	m³/hr	l/min	■	▲
.50 SR ● ??	1.7	170	4.9	0.07	1.2	6	7
	2.0	200	5.2	0.08	1.3	6	7
	2.5	250	5.2	0.09	1.5	7	8
	3.0	300	5.2	0.10	1.7	8	9
	3.5	350	5.5	0.12	1.9	8	9
	4.0	400	5.5	0.13	2.1	8	10
	4.5	450	5.5	0.14	2.3	9	10
1.0 SR ● ??	1.7	170	4.9	0.16	2.7	14	16
	2.0	200	5.2	0.17	2.9	13	15
	2.5	250	5.2	0.19	3.2	14	17
	3.0	300	5.2	0.21	3.6	16	18
	3.5	350	5.5	0.23	3.8	15	18
	4.0	400	5.5	0.25	4.1	16	19
2.0 SR ● ??	4.5	450	5.5	0.26	4.3	17	20
	1.7	170	4.9	0.28	4.7	24	27
	2.0	200	5.2	0.31	5.2	23	27
	2.5	250	5.2	0.36	6.0	27	31
	3.0	300	5.2	0.41	6.9	31	35
	3.5	350	5.5	0.45	7.6	30	35
	4.0	400	5.5	0.49	8.2	33	38
.75 SR ● ??	4.5	450	5.5	0.53	8.9	35	41
	1.7	170	6.7	0.12	2.0	5	6
	2.0	200	7.0	0.13	2.2	5	6
	2.5	250	7.0	0.15	2.4	6	7
	3.0	300	7.3	0.16	2.7	6	7
	3.5	350	7.6	0.17	2.9	6	7
	4.0	400	7.6	0.19	3.1	6	7
1.5 SR ● ??	4.5	450	7.6	0.20	3.3	7	8
	1.7	170	6.7	0.23	3.8	10	12
	2.0	200	7.0	0.25	4.1	10	12
	2.5	250	7.0	0.28	4.6	11	13
	3.0	300	7.3	0.31	5.2	12	13
	3.5	350	7.6	0.34	5.6	12	13
	4.0	400	7.6	0.36	6.0	12	14
3.0 SR ● ??	4.5	450	7.6	0.39	6.4	13	15
	1.7	170	6.7	0.53	8.9	24	27
	2.0	200	7.0	0.56	9.3	23	26
	2.5	250	7.0	0.60	10.0	24	28
	3.0	300	7.3	0.64	10.7	24	28
	3.5	350	7.6	0.67	11.2	23	27
	4.0	400	7.6	0.70	11.7	24	28
	4.5	450	7.6	0.73	12.1	25	29
?:????????????180????????360????????2.							

PGP ULTRA / I-20 MPR-25							
	??		??	??		?????MM/HR?	
	bar	kPa	m	m ³ /hr	l/min		
	1.7	170	7.0	0.17	3.0		
	2.4	240	7.3	0.20	3.6		
	3.1	310	7.6	0.23	3.6		
	3.8	380	7.6	0.25	4.2		
	4.5	450	7.6	0.27	4.8		
	1.7	170	7.0	0.23	3.6		
	2.4	240	7.3	0.27	4.8		
	3.1	310	7.6	0.31	5.4		
	3.8	380	7.6	0.35	6.0		
	4.5	450	7.6	0.38	6.6		
	1.7	170	7.0	0.33	5.4		
	2.4	240	7.3	0.39	6.6		
	3.1	310	7.6	0.45	7.2		
	3.8	380	7.6	0.50	8.4		
	4.5	450	7.6	0.55	9.0		
	1.7	170	7.0	0.63	10.8		
	2.4	240	7.3	0.76	12.6		
	3.1	310	7.6	0.87	14.4		
	3.8	380	7.6	0.97	16.2		
	4.5	450	7.6	1.05	17.4		

PGP ULTRA / I-20 MPR-30							
	??		??	??		?????MM/HR?	
	bar	kPa	m	m ³ /hr	l/min		
	1.7	170	8.8	0.23	3.6		
	2.4	240	9.1	0.28	4.8		
	3.1	310	9.1	0.32	5.4		
	3.8	380	9.1	0.35	6.0		
	4.5	450	9.1	0.38	6.6		
	1.7	170	8.8	0.30	4.8		
	2.4	240	9.1	0.37	6.0		
	3.1	310	9.1	0.42	7.2		
	3.8	380	9.1	0.47	7.8		
	4.5	450	9.1	0.51	8.4		
	1.7	170	8.8	0.49	8.4		
	2.4	240	9.1	0.59	9.6		
	3.1	310	9.1	0.67	11.4		
	3.8	380	9.1	0.75	12.6		
	4.5	450	9.1	0.82	13.8		
	1.7	170	8.8	0.96	16.2		
	2.4	240	9.1	1.15	19.2		
	3.1	310	9.1	1.31	21.6		
	3.8	380	9.1	1.45	24.0		
	4.5	450	9.1	1.57	26.4		

PGP ULTRA / I-20 MPR-35							
	??		??	??		?????MM/HR?	
	bar	kPa	m	m ³ /hr	l/min		
	1.7	170	9.8	0.32	5.4		
	2.4	240	10.4	0.38	6.6		
	3.1	310	10.7	0.44	7.2		
	3.8	380	10.7	0.48	7.8		
	4.5	450	10.7	0.52	9.0		
	1.7	170	9.8	0.40	6.6		
	2.4	240	10.4	0.49	8.4		
	3.1	310	10.7	0.56	9.6		
	3.8	380	10.7	0.62	10.2		
	4.5	450	10.7	0.68	11.4		
	1.7	170	9.8	0.62	10.2		
	2.4	240	10.4	0.76	12.6		
	3.1	310	10.7	0.87	14.4		
	3.8	380	10.7	0.96	16.2		
	4.5	450	10.7	1.05	17.4		
	1.7	170	9.8	1.22	20.4		
	2.4	240	10.4	1.50	25.2		
	3.1	310	10.7	1.72	28.8		
	3.8	380	10.7	1.91	31.8		
	4.5	450	10.7	2.09	34.8		

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/i-20/i-20-04-ss-ncv>
020326