



I-20-06-SS-R-PRB

000000

[illegible]

PGP Ultra & I-20 PRB

SKU: I2006SSRPRB

☐ 1:20
 ☐ 1:15
 ☐ 1:10
 ☐ 1:8
 ☐ 1:6
 ☐ 1:5
 ☐ 1:4
 ☐ 1:3
 ☐ 1:2
 ☐ 1:1
 ☐ 2:1
 ☐ 3:1
 ☐ 4:1
 ☐ 5:1
 ☐ 6:1
 ☐ 8:1
 ☐ 10:1
 ☐ 15:1
 ☐ 20:1
 ☐ 30:1
 ☐ 40:1
 ☐ 50:1
 ☐ 60:1
 ☐ 70:1
 ☐ 80:1
 ☐ 90:1
 ☐ 100:1
 ☐ 120:1
 ☐ 150:1
 ☐ 200:1
 ☐ 250:1
 ☐ 300:1
 ☐ 360:1
 ☐ 450:1
 ☐ 540:1
 ☐ 630:1
 ☐ 720:1
 ☐ 810:1
 ☐ 900:1
 ☐ 1080:1
 ☐ 1260:1
 ☐ 1440:1
 ☐ 1620:1
 ☐ 1800:1
 ☐ 2000:1
 ☐ 2250:1
 ☐ 2500:1
 ☐ 2700:1
 ☐ 3000:1
 ☐ 3240:1
 ☐ 3600:1
 ☐ 4000:1
 ☐ 4500:1
 ☐ 5000:1
 ☐ 5400:1
 ☐ 6000:1
 ☐ 6480:1
 ☐ 7200:1
 ☐ 8000:1
 ☐ 9000:1
 ☐ 10000:1
 ☐ 11250:1
 ☐ 12600:1
 ☐ 14400:1
 ☐ 16200:1
 ☐ 18000:1
 ☐ 20000:1
 ☐ 22500:1
 ☐ 25000:1
 ☐ 27000:1
 ☐ 30000:1
 ☐ 32400:1
 ☐ 36000:1
 ☐ 40000:1
 ☐ 45000:1
 ☐ 50000:1
 ☐ 54000:1
 ☐ 60000:1
 ☐ 64800:1
 ☐ 72000:1
 ☐ 80000:1
 ☐ 90000:1
 ☐ 100000:1
 ☐ 112500:1
 ☐ 126000:1
 ☐ 144000:1
 ☐ 162000:1
 ☐ 180000:1
 ☐ 200000:1
 ☐ 225000:1
 ☐ 250000:1
 ☐ 270000:1
 ☐ 300000:1
 ☐ 324000:1
 ☐ 360000:1
 ☐ 400000:1
 ☐ 450000:1
 ☐ 500000:1
 ☐ 540000:1
 ☐ 600000:1
 ☐ 648000:1
 ☐ 720000:1
 ☐ 800000:1
 ☐ 900000:1
 ☐ 1000000:1
 ☐ 1125000:1
 ☐ 1260000:1
 ☐ 1440000:1
 ☐ 1620000:1
 ☐ 1800000:1
 ☐ 2000000:1
 ☐ 2250000:1
 ☐ 2500000:1
 ☐ 2700000:1
 ☐ 3000000:1
 ☐ 3240000:1
 ☐ 3600000:1
 ☐ 4000000:1
 ☐ 4500000:1
 ☐ 5000000:1
 ☐ 5400000:1
 ☐ 6000000:1
 ☐ 6480000:1
 ☐ 7200000:1
 ☐ 8000000:1
 ☐ 9000000:1
 ☐ 10000000:1
 ☐ 11250000:1
 ☐ 12600000:1
 ☐ 14400000:1
 ☐ 16200000:1
 ☐ 18000000:1
 ☐ 20000000:1
 ☐ 22500000:1
 ☐ 25000000:1
 ☐ 27000000:1
 ☐ 30000000:1
 ☐ 32400000:1
 ☐ 36000000:1
 ☐ 40000000:1
 ☐ 45000000:1
 ☐ 50000000:1
 ☐ 54000000:1
 ☐ 60000000:1
 ☐ 64800000:1
 ☐ 72000000:1
 ☐ 80000000:1
 ☐ 90000000:1
 ☐ 100000000:1
 ☐ 112500000:1
 ☐ 126000000:1
 ☐ 144000000:1
 ☐ 162000000:1
 ☐ 180000000:1
 ☐ 200000000:1
 ☐ 225000000:1
 ☐ 250000000:1
 ☐ 270000000:1
 ☐ 300000000:1
 ☐ 324000000:1
 ☐ 360000000:1
 ☐ 400000000:1
 ☐ 450000000:1
 ☐ 500000000:1
 ☐ 540000000:1
 ☐ 600000000:1
 ☐ 648000000:1
 ☐ 720000000:1
 ☐ 800000000:1
 ☐ 900000000:1
 ☐ 1000000000:1
 ☐ 1125000000:1
 ☐ 1260000000:1
 ☐ 1440000000:1
 ☐ 1620000000:1
 ☐ 1800000000:1
 ☐ 2000000000:1
 ☐ 2250000000:1
 ☐ 2500000000:1
 ☐ 2700000000:1
 ☐ 3000000000:1
 ☐ 3240000000:1
 ☐ 3600000000:1
 ☐ 4000000000:1
 ☐ 4500000000:1
 ☐ 5000000000:1
 ☐ 5400000000:1
 ☐ 6000000000:1
 ☐ 6480000000:1
 ☐ 7200000000:1
 ☐ 8000000000:1
 ☐ 9000000000:1
 ☐ 10000000000:1
 ☐ 11250000000:1
 ☐ 12600000000:1
 ☐ 14400000000:1
 ☐ 16200000000:1
 ☐ 18000000000:1
 ☐ 20000000000:1
 ☐ 22500000000:1
 ☐ 25000000000:1
 ☐ 27000000000:1
 ☐ 30000000000:1
 ☐ 32400000000:1
 ☐ 36000000000:1
 ☐ 40000000000:1
 ☐ 45000000000:1
 ☐ 50000000000:1
 ☐ 54000000000:1
 ☐ 60000000000:1
 ☐ 64800000000:1
 ☐ 72000000000:1
 ☐ 80000000000:1
 ☐ 90000000000:1
 ☐ 100000000000:1
 ☐ 112500000000:1
 ☐ 126000000000:1
 ☐ 144000000000:1
 ☐ 162000000000:1
 ☐ 180000000000:1
 ☐ 200000000000:1
 ☐ 225000000000:1
 ☐ 250000000000:1
 ☐ 270000000000:1
 ☐ 300000000000:1
 ☐ 324000000000:1
 ☐ 360000000000:1
 ☐ 400000000000:1
 ☐ 450000000000:1
 <

Dimensions

269.88


□25:cm

6":

44.45

44:45

3/4



Operating Specifications

Arc: 50° to 360°

Operating Pressure: 4.1 - 7.0 bar □ 410 - 700 kPa

Precipitation Rate: 10 /

Radius: 4.9 $\leq$ 14.0 $\leq$

Flow: 0.07 - 2.22 m³/hr □ 1.2 to 36.0 l/min

Shipping Information

UPC-A: 0611698060230

1720

11260

1030

20

PGP Ultra / I-20 / PRB							
N							
						mm/h	
	bar	kPa	m		l/min		
2.0 LA	1.7	170	7.3	0.33	5.6	12	14
	2.0	200	7.6	0.36	6.0	12	14
	2.5	250	7.9	0.40	6.7	13	15
	3.0	300	8.2	0.45	7.4	13	15
	3.5	350	8.5	0.48	8.0	13	15
	4.0	400	8.8	0.52	8.6	13	15
	4.5	450	9.1	0.55	9.1	13	15
2.5 LA	1.7	170	7.9	0.44	7.3	14	16
	2.0	200	8.2	0.47	7.9	14	16
	2.5	250	8.8	0.53	8.8	14	16
	3.0	300	9.4	0.59	9.8	13	15
	3.5	350	10.1	0.64	10.6	13	15
	4.0	400	10.4	0.68	11.3	13	15
	4.5	450	10.7	0.72	12.0	13	15
3.5 LA	1.7	170	8.5	0.58	9.7	16	18
	2.0	200	8.8	0.62	10.3	16	18
	2.5	250	9.1	0.68	11.4	16	19
	3.0	300	10.1	0.75	12.5	15	17
	3.5	350	10.7	0.80	13.3	14	16
	4.0	400	11.0	0.85	14.1	14	16
	4.5	450	11.3	0.89	14.8	14	16
4.5 LA	1.7	170	8.2	0.71	11.8	21	24
	2.0	200	8.8	0.76	12.7	19	23
	2.5	250	9.1	0.84	14.1	20	23
	3.0	300	10.1	0.93	15.5	18	21
	3.5	350	10.7	1.00	16.6	18	20
	4.0	400	11.0	1.06	17.6	18	20
	4.5	450	11.3	1.12	18.6	18	20
180°360°2							

PGP ULTRA / I-20 / PRB MPR-25							
						mm/h	
	bar	kPa	m	m ³ /hr	l/min		
90°	1.7	170	7.0	0.17	3.0	13.7	15.8
	2.4	240	7.3	0.20	3.6	14.9	17.3
	3.1	310	7.6	0.23	3.6	15.6	18.1
	3.8	380	7.6	0.25	4.2	17.4	20.1
	4.5	450	7.6	0.27	4.8	18.9	21.9
120°	1.7	170	7.0	0.23	3.6	13.9	16.0
	2.4	240	7.3	0.27	4.8	15.4	17.8
	3.1	310	7.6	0.31	5.4	16.2	18.7
	3.8	380	7.6	0.35	6.0	18.0	20.7
	4.5	450	7.6	0.38	6.6	19.6	22.6
180°	1.7	170	7.0	0.33	5.4	13.3	15.4
	2.4	240	7.3	0.39	6.6	14.7	17.0
	3.1	310	7.6	0.45	7.2	15.5	17.9
	3.8	380	7.6	0.50	8.4	17.3	20.0
	4.5	450	7.6	0.55	9.0	18.9	21.8
360°	1.7	170	7.0	0.63	10.8	12.8	14.8
	2.4	240	7.3	0.76	12.6	14.2	16.4
	3.1	310	7.6	0.87	14.4	14.9	17.3
	3.8	380	7.6	0.97	16.2	16.6	19.2
	4.5	450	7.6	1.05	17.4	18.1	20.9

PGP ULTRA / I-20 / PRB MPR-30							
						mm/h	
	bar	kPa	m	m ³ /hr	l/min		
90°	1.7	170	8.8	0.23	3.6	12.0	13.8
	2.4	240	9.1	0.28	4.8	13.4	15.4
	3.1	310	9.1	0.32	5.4	15.2	17.6
	3.8	380	9.1	0.35	6.0	17.0	19.6
	4.5	450	9.1	0.38	6.6	18.4	21.2
120°	1.7	170	8.8	0.30	4.8	11.7	13.5
	2.4	240	9.1	0.37	6.0	13.2	15.2
	3.1	310	9.1	0.42	7.2	15.1	17.4
	3.8	380	9.1	0.47	7.8	16.8	19.4
	4.5	450	9.1	0.51	8.4	18.3	21.1
180°	1.7	170	8.8	0.49	8.4	12.5	14.4
	2.4	240	9.1	0.59	9.6	14.1	16.2
	3.1	310	9.1	0.67	11.4	16.1	18.6
	3.8	380	9.1	0.75	12.6	17.9	20.7
	4.5	450	9.1	0.82	13.8	19.6	22.6
360°	1.7	170	8.8	0.96	16.2	12.3	14.2
	2.4	240	9.1	1.15	19.2	13.8	15.9
	3.1	310	9.1	1.31	21.6	15.7	18.1
	3.8	380	9.1	1.45	24.0	17.4	20.0
	4.5	450	9.1	1.57	26.4	18.8	21.7

PGP ULTRA / I-20 / PRB MPR-35							
						mm/h	
	bar	kPa	m	m ³ /hr	l/min		
90°	1.7	170	9.8	0.32	5.4	13.4	15.4
	2.4	240	10.4	0.38	6.6	14.1	16.3
	3.1	310	10.7	0.44	7.2	15.3	17.7
	3.8	380	10.7	0.48	7.8	17.0	19.6
	4.5	450	10.7	0.52	9.0	18.4	21.3
120°	1.7	170	9.8	0.40	6.6	12.7	14.6
	2.4	240	10.4	0.49	8.4	13.6	15.8
	3.1	310	10.7	0.56	9.6	14.7	17.0
	3.8	380	10.7	0.62	10.2	16.4	18.9
	4.5	450	10.7	0.68	11.4	17.9	20.7
180°	1.7	170	9.8	0.62	10.2	13.1	15.2
	2.4	240	10.4	0.76	12.6	14.1	16.3
	3.1	310	10.7	0.87	14.4	15.2	17.6
	3.8	380	10.7	0.96	16.2	16.9	19.5
	4.5	450	10.7	1.05	17.4	18.4	21.3
360°	1.7	170	9.8	1.22	20.4	12.8	14.8
	2.4	240	10.4	1.50	25.2	14.0	16.2
	3.1	310	10.7	1.72	28.8	15.1	17.5
	3.8	380	10.7	1.91	31.8	16.8	19.4
	4.5	450	10.7	2.09	34.8	18.3	21.2

