



## I-20-12-R

1.5" x 1.5"

1.5" x 1.5" x 1.5"

1.5" x 2.0"

**SKU:** I2012R

1.5" x 2.0" x 1.5" x 30" x 1.5" x 1.5" x 50° x 360° x 1/4" x 1.5" x 1.5" x 1.5"

### Dimensions

1.5" x 31.80"

1.5" x 2 cm

1.5" x 2"

1.5" x 4.45"

1.5" x 4.45"

1.5" x 1/4"



### Operating Specifications

**Arc:** 50° to 360°

**Operating Pressure:** 4.1 - 7.0 bar / 410 - 700 kPa

**Precipitation Rate:** 10 mm/hr

**Radius:** 4.9" - 14.0"

**Flow:** 0.07 - 2.22 m<sup>3</sup>/hr / 1.2 to 36.0 l/min

### Shipping Information

**UPC-A:** 0611698158685

1.5" x 2"


1.5" x 6.0"


1.5" x 6.8"


1.5" x 1.2"





| PGP ULTRA / I-20 MPR-25                                                           |     |     |     |                    |       |             |      |
|-----------------------------------------------------------------------------------|-----|-----|-----|--------------------|-------|-------------|------|
|                                                                                   | ??  |     | ??  | ??                 |       | ?????MM/HR? |      |
|                                                                                   | bar | kPa | m   | m <sup>3</sup> /hr | l/min |             |      |
|  | 1.7 | 170 | 7.0 | 0.17               | 3.0   | 13.7        | 15.8 |
|                                                                                   | 2.4 | 240 | 7.3 | 0.20               | 3.6   | 14.9        | 17.3 |
|                                                                                   | 3.1 | 310 | 7.6 | 0.23               | 3.6   | 15.6        | 18.1 |
|                                                                                   | 3.8 | 380 | 7.6 | 0.25               | 4.2   | 17.4        | 20.1 |
|                                                                                   | 4.5 | 450 | 7.6 | 0.27               | 4.8   | 18.9        | 21.9 |
|  | 1.7 | 170 | 7.0 | 0.23               | 3.6   | 13.9        | 16.0 |
|                                                                                   | 2.4 | 240 | 7.3 | 0.27               | 4.8   | 15.4        | 17.8 |
|                                                                                   | 3.1 | 310 | 7.6 | 0.31               | 5.4   | 16.2        | 18.7 |
|                                                                                   | 3.8 | 380 | 7.6 | 0.35               | 6.0   | 18.0        | 20.7 |
|                                                                                   | 4.5 | 450 | 7.6 | 0.38               | 6.6   | 19.6        | 22.6 |
|  | 1.7 | 170 | 7.0 | 0.33               | 5.4   | 13.3        | 15.4 |
|                                                                                   | 2.4 | 240 | 7.3 | 0.39               | 6.6   | 14.7        | 17.0 |
|                                                                                   | 3.1 | 310 | 7.6 | 0.45               | 7.2   | 15.5        | 17.9 |
|                                                                                   | 3.8 | 380 | 7.6 | 0.50               | 8.4   | 17.3        | 20.0 |
|                                                                                   | 4.5 | 450 | 7.6 | 0.55               | 9.0   | 18.9        | 21.8 |
|  | 1.7 | 170 | 7.0 | 0.63               | 10.8  | 12.8        | 14.8 |
|                                                                                   | 2.4 | 240 | 7.3 | 0.76               | 12.6  | 14.2        | 16.4 |
|                                                                                   | 3.1 | 310 | 7.6 | 0.87               | 14.4  | 14.9        | 17.3 |
|                                                                                   | 3.8 | 380 | 7.6 | 0.97               | 16.2  | 16.6        | 19.2 |
|                                                                                   | 4.5 | 450 | 7.6 | 1.05               | 17.4  | 18.1        | 20.9 |

| PGP ULTRA / I-20 MPR-30                                                           |     |     |     |                    |       |             |      |
|-----------------------------------------------------------------------------------|-----|-----|-----|--------------------|-------|-------------|------|
|                                                                                   | ??  |     | ??  | ??                 |       | ?????MM/HR? |      |
|                                                                                   | bar | kPa | m   | m <sup>3</sup> /hr | l/min |             |      |
|  | 1.7 | 170 | 8.8 | 0.23               | 3.6   | 12.0        | 13.8 |
|                                                                                   | 2.4 | 240 | 9.1 | 0.28               | 4.8   | 13.4        | 15.4 |
|                                                                                   | 3.1 | 310 | 9.1 | 0.32               | 5.4   | 15.2        | 17.6 |
|                                                                                   | 3.8 | 380 | 9.1 | 0.35               | 6.0   | 17.0        | 19.6 |
|                                                                                   | 4.5 | 450 | 9.1 | 0.38               | 6.6   | 18.4        | 21.2 |
|  | 1.7 | 170 | 8.8 | 0.30               | 4.8   | 11.7        | 13.5 |
|                                                                                   | 2.4 | 240 | 9.1 | 0.37               | 6.0   | 13.2        | 15.2 |
|                                                                                   | 3.1 | 310 | 9.1 | 0.42               | 7.2   | 15.1        | 17.4 |
|                                                                                   | 3.8 | 380 | 9.1 | 0.47               | 7.8   | 16.8        | 19.4 |
|                                                                                   | 4.5 | 450 | 9.1 | 0.51               | 8.4   | 18.3        | 21.1 |
|  | 1.7 | 170 | 8.8 | 0.49               | 8.4   | 12.5        | 14.4 |
|                                                                                   | 2.4 | 240 | 9.1 | 0.59               | 9.6   | 14.1        | 16.2 |
|                                                                                   | 3.1 | 310 | 9.1 | 0.67               | 11.4  | 16.1        | 18.6 |
|                                                                                   | 3.8 | 380 | 9.1 | 0.75               | 12.6  | 17.9        | 20.7 |
|                                                                                   | 4.5 | 450 | 9.1 | 0.82               | 13.8  | 19.6        | 22.6 |
|  | 1.7 | 170 | 8.8 | 0.96               | 16.2  | 12.3        | 14.2 |
|                                                                                   | 2.4 | 240 | 9.1 | 1.15               | 19.2  | 13.8        | 15.9 |
|                                                                                   | 3.1 | 310 | 9.1 | 1.31               | 21.6  | 15.7        | 18.1 |
|                                                                                   | 3.8 | 380 | 9.1 | 1.45               | 24.0  | 17.4        | 20.0 |
|                                                                                   | 4.5 | 450 | 9.1 | 1.57               | 26.4  | 18.8        | 21.7 |

| PGP ULTRA / I-20 MPR-35                                                             |     |     |      |                    |       |             |      |
|-------------------------------------------------------------------------------------|-----|-----|------|--------------------|-------|-------------|------|
|                                                                                     | ??  |     | ??   | ??                 |       | ?????MM/HR? |      |
|                                                                                     | bar | kPa | m    | m <sup>3</sup> /hr | l/min |             |      |
|  | 1.7 | 170 | 9.8  | 0.32               | 5.4   | 13.4        | 15.4 |
|                                                                                     | 2.4 | 240 | 10.4 | 0.38               | 6.6   | 14.1        | 16.3 |
|                                                                                     | 3.1 | 310 | 10.7 | 0.44               | 7.2   | 15.3        | 17.7 |
|                                                                                     | 3.8 | 380 | 10.7 | 0.48               | 7.8   | 17.0        | 19.6 |
|                                                                                     | 4.5 | 450 | 10.7 | 0.52               | 9.0   | 18.4        | 21.3 |
|  | 1.7 | 170 | 9.8  | 0.40               | 6.6   | 12.7        | 14.6 |
|                                                                                     | 2.4 | 240 | 10.4 | 0.49               | 8.4   | 13.6        | 15.8 |
|                                                                                     | 3.1 | 310 | 10.7 | 0.56               | 9.6   | 14.7        | 17.0 |
|                                                                                     | 3.8 | 380 | 10.7 | 0.62               | 10.2  | 16.4        | 18.9 |
|                                                                                     | 4.5 | 450 | 10.7 | 0.68               | 11.4  | 17.9        | 20.7 |
|  | 1.7 | 170 | 9.8  | 0.62               | 10.2  | 13.1        | 15.2 |
|                                                                                     | 2.4 | 240 | 10.4 | 0.76               | 12.6  | 14.1        | 16.3 |
|                                                                                     | 3.1 | 310 | 10.7 | 0.87               | 14.4  | 15.2        | 17.6 |
|                                                                                     | 3.8 | 380 | 10.7 | 0.96               | 16.2  | 16.9        | 19.5 |
|                                                                                     | 4.5 | 450 | 10.7 | 1.05               | 17.4  | 18.4        | 21.3 |
|  | 1.7 | 170 | 9.8  | 1.22               | 20.4  | 12.8        | 14.8 |
|                                                                                     | 2.4 | 240 | 10.4 | 1.50               | 25.2  | 14.0        | 16.2 |
|                                                                                     | 3.1 | 310 | 10.7 | 1.72               | 28.8  | 15.1        | 17.5 |
|                                                                                     | 3.8 | 380 | 10.7 | 1.91               | 31.8  | 16.8        | 19.4 |
|                                                                                     | 4.5 | 450 | 10.7 | 2.09               | 34.8  | 18.3        | 21.2 |

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/i-20/i-20-12-r020326>