




PGP-04-CV-R

PGP Ultra  
SKU: PGP04CVR  
PGP Ultra 10 50° 360° 3/4

Dimensions

90.50  
4  
44.45  
44.45  
3/4



Operating Specifications

Arc: 50° to 360°  
Operating Pressure: 4.1 - 7.0 bar 410 - 700 kPa  
Precipitation Rate: 10 mm/hr  
Radius: 4.9 - 14.0 m  
Flow: 0.07 - 2.22 m3/hr 1.2 to 36.0 l/min


Shipping Information


UPC-A: 0611698157466  
120  
1800  
1140  
20




| PGP Ultra / I-20:????                         |     |     |      |       |       |             |    |
|-----------------------------------------------|-----|-----|------|-------|-------|-------------|----|
| ??                                            | ??  |     | ??   | ??    |       | ?????MM/HR? |    |
|                                               | bar | kPa | m    | m³/hr | l/min | ■           | ▲  |
| 10<br>●<br>???                                | 1.7 | 170 | 10.7 | 1.48  | 24.6  | 26          | 30 |
|                                               | 2.0 | 200 | 11.9 | 1.60  | 26.7  | 23          | 26 |
|                                               | 2.5 | 250 | 12.5 | 1.80  | 30.0  | 23          | 27 |
|                                               | 3.0 | 300 | 12.8 | 2.01  | 33.5  | 25          | 28 |
|                                               | 3.5 | 350 | 13.1 | 2.18  | 36.3  | 25          | 29 |
|                                               | 4.0 | 400 | 13.7 | 2.34  | 39.0  | 25          | 29 |
|                                               | 4.5 | 450 | 14.0 | 2.49  | 41.5  | 25          | 29 |
| 13<br>●<br>???                                | 1.7 | 170 | 11.0 | 1.91  | 31.9  | 32          | 37 |
|                                               | 2.0 | 200 | 12.2 | 2.08  | 34.6  | 28          | 32 |
|                                               | 2.5 | 250 | 12.8 | 2.34  | 38.9  | 29          | 33 |
|                                               | 3.0 | 300 | 13.1 | 2.61  | 43.4  | 30          | 35 |
|                                               | 3.5 | 350 | 13.4 | 2.83  | 47.1  | 31          | 36 |
|                                               | 4.0 | 400 | 13.7 | 3.03  | 50.5  | 32          | 37 |
|                                               | 4.5 | 450 | 14.0 | 3.23  | 53.8  | 33          | 38 |
| 6.0 LA<br>●<br>???                            | 1.7 | 170 | 9.1  | 0.86  | 14.3  | 21          | 24 |
|                                               | 2.0 | 200 | 9.4  | 0.94  | 15.6  | 21          | 24 |
|                                               | 2.5 | 250 | 10.1 | 1.07  | 17.8  | 21          | 24 |
|                                               | 3.0 | 300 | 10.7 | 1.20  | 20.0  | 21          | 24 |
|                                               | 3.5 | 350 | 11.3 | 1.31  | 21.9  | 21          | 24 |
|                                               | 4.0 | 400 | 11.6 | 1.42  | 23.6  | 21          | 24 |
|                                               | 4.5 | 450 | 11.9 | 1.52  | 25.3  | 21          | 25 |
| 8.0 LA<br>●<br>???                            | 1.7 | 170 | 10.1 | 1.17  | 19.5  | 23          | 27 |
|                                               | 2.0 | 200 | 10.7 | 1.28  | 21.3  | 22          | 26 |
|                                               | 2.5 | 250 | 11.3 | 1.44  | 24.0  | 23          | 26 |
|                                               | 3.0 | 300 | 11.6 | 1.61  | 26.9  | 24          | 28 |
|                                               | 3.5 | 350 | 11.9 | 1.76  | 29.3  | 25          | 29 |
|                                               | 4.0 | 400 | 12.5 | 1.89  | 31.5  | 24          | 28 |
|                                               | 4.5 | 450 | 12.5 | 2.01  | 33.6  | 26          | 30 |
| ????????????????180????????????360??????????? |     |     |      |       |       |             |    |

| PGP Ultra / I-20 ????????                     |     |     |     |       |       |             |    |
|-----------------------------------------------|-----|-----|-----|-------|-------|-------------|----|
| ■■■■■■■                                       |     |     |     |       |       |             |    |
| ??                                            | ??  |     | ??  | ??    |       | ?????MM/HR? |    |
|                                               | bar | kPa | m   | m³/hr | l/min | ■           | ▲  |
| .50 SR<br>●<br>??                             | 1.7 | 170 | 4.9 | 0.07  | 1.2   | 6           | 7  |
|                                               | 2.0 | 200 | 5.2 | 0.08  | 1.3   | 6           | 7  |
|                                               | 2.5 | 250 | 5.2 | 0.09  | 1.5   | 7           | 8  |
|                                               | 3.0 | 300 | 5.2 | 0.10  | 1.7   | 8           | 9  |
|                                               | 3.5 | 350 | 5.5 | 0.12  | 1.9   | 8           | 9  |
|                                               | 4.0 | 400 | 5.5 | 0.13  | 2.1   | 8           | 10 |
|                                               | 4.5 | 450 | 5.5 | 0.14  | 2.3   | 9           | 10 |
| 1.0 SR<br>●<br>??                             | 1.7 | 170 | 4.9 | 0.16  | 2.7   | 14          | 16 |
|                                               | 2.0 | 200 | 5.2 | 0.17  | 2.9   | 13          | 15 |
|                                               | 2.5 | 250 | 5.2 | 0.19  | 3.2   | 14          | 17 |
|                                               | 3.0 | 300 | 5.2 | 0.21  | 3.6   | 16          | 18 |
|                                               | 3.5 | 350 | 5.5 | 0.23  | 3.8   | 15          | 18 |
|                                               | 4.0 | 400 | 5.5 | 0.25  | 4.1   | 16          | 19 |
| 2.0 SR<br>●<br>??                             | 4.5 | 450 | 5.5 | 0.26  | 4.3   | 17          | 20 |
|                                               | 1.7 | 170 | 4.9 | 0.28  | 4.7   | 24          | 27 |
|                                               | 2.0 | 200 | 5.2 | 0.31  | 5.2   | 23          | 27 |
|                                               | 2.5 | 250 | 5.2 | 0.36  | 6.0   | 27          | 31 |
|                                               | 3.0 | 300 | 5.2 | 0.41  | 6.9   | 31          | 35 |
|                                               | 3.5 | 350 | 5.5 | 0.45  | 7.6   | 30          | 35 |
|                                               | 4.0 | 400 | 5.5 | 0.49  | 8.2   | 33          | 38 |
| .75 SR<br>●<br>??                             | 4.5 | 450 | 5.5 | 0.53  | 8.9   | 35          | 41 |
|                                               | 1.7 | 170 | 6.7 | 0.12  | 2.0   | 5           | 6  |
|                                               | 2.0 | 200 | 7.0 | 0.13  | 2.2   | 5           | 6  |
|                                               | 2.5 | 250 | 7.0 | 0.15  | 2.4   | 6           | 7  |
|                                               | 3.0 | 300 | 7.3 | 0.16  | 2.7   | 6           | 7  |
|                                               | 3.5 | 350 | 7.6 | 0.17  | 2.9   | 6           | 7  |
|                                               | 4.0 | 400 | 7.6 | 0.19  | 3.1   | 6           | 7  |
| 1.5 SR<br>●<br>??                             | 4.5 | 450 | 7.6 | 0.20  | 3.3   | 7           | 8  |
|                                               | 1.7 | 170 | 6.7 | 0.23  | 3.8   | 10          | 12 |
|                                               | 2.0 | 200 | 7.0 | 0.25  | 4.1   | 10          | 12 |
|                                               | 2.5 | 250 | 7.0 | 0.28  | 4.6   | 11          | 13 |
|                                               | 3.0 | 300 | 7.3 | 0.31  | 5.2   | 12          | 13 |
|                                               | 3.5 | 350 | 7.6 | 0.34  | 5.6   | 12          | 13 |
|                                               | 4.0 | 400 | 7.6 | 0.36  | 6.0   | 12          | 14 |
| 3.0 SR<br>●<br>??                             | 4.5 | 450 | 7.6 | 0.39  | 6.4   | 13          | 15 |
|                                               | 1.7 | 170 | 6.7 | 0.53  | 8.9   | 24          | 27 |
|                                               | 2.0 | 200 | 7.0 | 0.56  | 9.3   | 23          | 26 |
|                                               | 2.5 | 250 | 7.0 | 0.60  | 10.0  | 24          | 28 |
|                                               | 3.0 | 300 | 7.3 | 0.64  | 10.7  | 24          | 28 |
|                                               | 3.5 | 350 | 7.6 | 0.67  | 11.2  | 23          | 27 |
|                                               | 4.0 | 400 | 7.6 | 0.70  | 11.7  | 24          | 28 |
|                                               | 4.5 | 450 | 7.6 | 0.73  | 12.1  | 25          | 29 |
| ????????????????180????????????360?????????2. |     |     |     |       |       |             |    |

| PGP ULTRA / I-20 MPR-25                                                           |     |     |     |                    |       |             |  |
|-----------------------------------------------------------------------------------|-----|-----|-----|--------------------|-------|-------------|--|
|                                                                                   | ??  |     | ??  | ??                 |       | ?????MM/HR? |  |
|                                                                                   | bar | kPa | m   | m <sup>3</sup> /hr | l/min |             |  |
|  | 1.7 | 170 | 7.0 | 0.17               | 3.0   |             |  |
|                                                                                   | 2.4 | 240 | 7.3 | 0.20               | 3.6   |             |  |
|                                                                                   | 3.1 | 310 | 7.6 | 0.23               | 3.6   |             |  |
|                                                                                   | 3.8 | 380 | 7.6 | 0.25               | 4.2   |             |  |
|                                                                                   | 4.5 | 450 | 7.6 | 0.27               | 4.8   |             |  |
|  | 1.7 | 170 | 7.0 | 0.23               | 3.6   |             |  |
|                                                                                   | 2.4 | 240 | 7.3 | 0.27               | 4.8   |             |  |
|                                                                                   | 3.1 | 310 | 7.6 | 0.31               | 5.4   |             |  |
|                                                                                   | 3.8 | 380 | 7.6 | 0.35               | 6.0   |             |  |
|                                                                                   | 4.5 | 450 | 7.6 | 0.38               | 6.6   |             |  |
|  | 1.7 | 170 | 7.0 | 0.33               | 5.4   |             |  |
|                                                                                   | 2.4 | 240 | 7.3 | 0.39               | 6.6   |             |  |
|                                                                                   | 3.1 | 310 | 7.6 | 0.45               | 7.2   |             |  |
|                                                                                   | 3.8 | 380 | 7.6 | 0.50               | 8.4   |             |  |
|                                                                                   | 4.5 | 450 | 7.6 | 0.55               | 9.0   |             |  |
|  | 1.7 | 170 | 7.0 | 0.63               | 10.8  |             |  |
|                                                                                   | 2.4 | 240 | 7.3 | 0.76               | 12.6  |             |  |
|                                                                                   | 3.1 | 310 | 7.6 | 0.87               | 14.4  |             |  |
|                                                                                   | 3.8 | 380 | 7.6 | 0.97               | 16.2  |             |  |
|                                                                                   | 4.5 | 450 | 7.6 | 1.05               | 17.4  |             |  |

| PGP ULTRA / I-20 MPR-30                                                           |     |     |     |                    |       |             |  |
|-----------------------------------------------------------------------------------|-----|-----|-----|--------------------|-------|-------------|--|
|                                                                                   | ??  |     | ??  | ??                 |       | ?????MM/HR? |  |
|                                                                                   | bar | kPa | m   | m <sup>3</sup> /hr | l/min |             |  |
|  | 1.7 | 170 | 8.8 | 0.23               | 3.6   |             |  |
|                                                                                   | 2.4 | 240 | 9.1 | 0.28               | 4.8   |             |  |
|                                                                                   | 3.1 | 310 | 9.1 | 0.32               | 5.4   |             |  |
|                                                                                   | 3.8 | 380 | 9.1 | 0.35               | 6.0   |             |  |
|                                                                                   | 4.5 | 450 | 9.1 | 0.38               | 6.6   |             |  |
|  | 1.7 | 170 | 8.8 | 0.30               | 4.8   |             |  |
|                                                                                   | 2.4 | 240 | 9.1 | 0.37               | 6.0   |             |  |
|                                                                                   | 3.1 | 310 | 9.1 | 0.42               | 7.2   |             |  |
|                                                                                   | 3.8 | 380 | 9.1 | 0.47               | 7.8   |             |  |
|                                                                                   | 4.5 | 450 | 9.1 | 0.51               | 8.4   |             |  |
|  | 1.7 | 170 | 8.8 | 0.49               | 8.4   |             |  |
|                                                                                   | 2.4 | 240 | 9.1 | 0.59               | 9.6   |             |  |
|                                                                                   | 3.1 | 310 | 9.1 | 0.67               | 11.4  |             |  |
|                                                                                   | 3.8 | 380 | 9.1 | 0.75               | 12.6  |             |  |
|                                                                                   | 4.5 | 450 | 9.1 | 0.82               | 13.8  |             |  |
|  | 1.7 | 170 | 8.8 | 0.96               | 16.2  |             |  |
|                                                                                   | 2.4 | 240 | 9.1 | 1.15               | 19.2  |             |  |
|                                                                                   | 3.1 | 310 | 9.1 | 1.31               | 21.6  |             |  |
|                                                                                   | 3.8 | 380 | 9.1 | 1.45               | 24.0  |             |  |
|                                                                                   | 4.5 | 450 | 9.1 | 1.57               | 26.4  |             |  |

| PGP ULTRA / I-20 MPR-35                                                             |     |     |      |                    |       |             |  |
|-------------------------------------------------------------------------------------|-----|-----|------|--------------------|-------|-------------|--|
|                                                                                     | ??  |     | ??   | ??                 |       | ?????MM/HR? |  |
|                                                                                     | bar | kPa | m    | m <sup>3</sup> /hr | l/min |             |  |
|  | 1.7 | 170 | 9.8  | 0.32               | 5.4   |             |  |
|                                                                                     | 2.4 | 240 | 10.4 | 0.38               | 6.6   |             |  |
|                                                                                     | 3.1 | 310 | 10.7 | 0.44               | 7.2   |             |  |
|                                                                                     | 3.8 | 380 | 10.7 | 0.48               | 7.8   |             |  |
|                                                                                     | 4.5 | 450 | 10.7 | 0.52               | 9.0   |             |  |
|  | 1.7 | 170 | 9.8  | 0.40               | 6.6   |             |  |
|                                                                                     | 2.4 | 240 | 10.4 | 0.49               | 8.4   |             |  |
|                                                                                     | 3.1 | 310 | 10.7 | 0.56               | 9.6   |             |  |
|                                                                                     | 3.8 | 380 | 10.7 | 0.62               | 10.2  |             |  |
|                                                                                     | 4.5 | 450 | 10.7 | 0.68               | 11.4  |             |  |
|  | 1.7 | 170 | 9.8  | 0.62               | 10.2  |             |  |
|                                                                                     | 2.4 | 240 | 10.4 | 0.76               | 12.6  |             |  |
|                                                                                     | 3.1 | 310 | 10.7 | 0.87               | 14.4  |             |  |
|                                                                                     | 3.8 | 380 | 10.7 | 0.96               | 16.2  |             |  |
|                                                                                     | 4.5 | 450 | 10.7 | 1.05               | 17.4  |             |  |
|  | 1.7 | 170 | 9.8  | 1.22               | 20.4  |             |  |
|                                                                                     | 2.4 | 240 | 10.4 | 1.50               | 25.2  |             |  |
|                                                                                     | 3.1 | 310 | 10.7 | 1.72               | 28.8  |             |  |
|                                                                                     | 3.8 | 380 | 10.7 | 1.91               | 31.8  |             |  |
|                                                                                     | 4.5 | 450 | 10.7 | 2.09               | 34.8  |             |  |

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/pgp-ultra/pgp-04-cv-r>  
020326