



# PCB-20-R

000000

[illegible]

**SKU:** PCB20R

7.6 l/min<sup>1/2</sup> ID

## Shipping Information

**UPC-A:** 0611698159651

25/250

48000

4000

250

| PCN / PCB                                                                         |                                                                                   |          |                    |       |     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------|--------------------|-------|-----|
|                                                                                   |                                                                                   |          |                    |       |     |
|                                                                                   |                                                                                   |          | m <sup>3</sup> /hr | l/min | m   |
|  |  | MSBN-25Q | 0.06               | 0.9   | 0.3 |
|                                                                                   |  | MSBN-50Q | 0.11               | 1.9   | 0.5 |
|  |  | MSBN-50H | 0.11               | 1.9   | 0.3 |
|                                                                                   |  | MSBN-10H | 0.23               | 3.8   | 0.5 |
|  |  | MSBN-10F | 0.23               | 3.8   | 0.3 |
|                                                                                   |  | MSBN-20F | 0.45               | 7.6   | 0.5 |
| 0.6 - 1.2 m<br>1.0 - 4.8 bar(100 -480 kPa)                                        |                                                                                   |          |                    |       |     |

| PCN / PCB                                                                         |    |                    |       |  |
|-----------------------------------------------------------------------------------|----|--------------------|-------|--|
|                                                                                   |    |                    |       |  |
|                                                                                   |    | m <sup>3</sup> /hr | l/min |  |
|  | 25 | 0.06               | 0.09  |  |
|                                                                                   | 50 | 0.11               | 1.90  |  |
|                                                                                   | 10 | 0.23               | 3.80  |  |
|                                                                                   | 20 | 0.45               | 7.60  |  |
| 0.3 - 0.9 m1.0 - 4.8 bar(100 -480 kPa)                                            |    |                    |       |  |

| AFB                                                                               |     |                    |        |  |
|-----------------------------------------------------------------------------------|-----|--------------------|--------|--|
|                                                                                   |     |                    |        |  |
|                                                                                   |     | m <sup>3</sup> /hr | l/min  |  |
|  | AFB | < 0.45             | < 0.76 |  |

| 5-CST-B                                                                            |     |     |     |                    |       |
|------------------------------------------------------------------------------------|-----|-----|-----|--------------------|-------|
|                                                                                    |     |     |     |                    |       |
|                                                                                    | bar | kPa | m   | m <sup>3</sup> /hr | l/min |
|  | 1.0 | 100 | 1.5 | 0.07               | 1.1   |
|                                                                                    | 1.5 | 150 | 1.5 | 0.07               | 1.2   |
|                                                                                    | 2.0 | 200 | 1.5 | 0.09               | 1.4   |
|                                                                                    | 2.1 | 210 | 1.5 | 0.09               | 1.5   |
|                                                                                    | 2.5 | 250 | 1.5 | 0.10               | 1.6   |

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/yongquanpentouheyongquanpenzui/pcb-20-r020326>