



5Q

1.5" 90°  
1.5" 90°  
1.5" 90°  
SKU: 5Q  
1.5" 90°

Shipping Information

UPC-A: 0611698155479  
25/250  
52000  
40000  
250

Additional Information

90°  
Approx 1.6 in/hr  
5'







1.5 m  
1/4, 1/2, 3/4  
0°

|      |   |     |     |     |       |       | mm/hr |    |
|------|---|-----|-----|-----|-------|-------|-------|----|
|      |   | bar | kPa | m   | m³/hr | l/min |       |    |
| 90°  | Q | 1.0 | 100 | 1.1 | 0.02  | 0.30  | 60    | 69 |
|      |   | 1.5 | 150 | 1.3 | 0.02  | 0.38  | 54    | 62 |
|      |   | 2.0 | 200 | 1.5 | 0.03  | 0.45  | 48    | 55 |
|      |   | 2.1 | 210 | 1.5 | 0.03  | 0.46  | 49    | 57 |
|      |   | 2.5 | 250 | 1.7 | 0.03  | 0.51  | 42    | 49 |
| 120° | T | 1.0 | 100 |     |       |       |       |    |
|      |   | 1.5 | 150 |     |       |       |       |    |
|      |   | 2.0 | 200 |     |       | 4A    |       |    |
|      |   | 2.1 | 210 |     |       |       |       |    |
|      |   | 2.5 | 250 |     |       |       |       |    |
| 180° | H | 1.0 | 100 | 1.1 | 0.40  | 0.60  | 60    | 69 |
|      |   | 1.5 | 150 | 1.3 | 0.05  | 0.76  | 54    | 62 |
|      |   | 2.0 | 200 | 1.5 | 0.05  | 0.90  | 48    | 53 |
|      |   | 2.1 | 210 | 1.5 | 0.06  | 0.92  | 49    | 57 |
|      |   | 2.5 | 250 | 1.7 | 0.06  | 1.02  | 42    | 49 |
| 360° | F | 1.0 | 100 | 1.1 | 0.07  | 1.2   | 60    | 69 |
|      |   | 1.5 | 150 | 1.3 | 0.09  | 1.52  | 54    | 62 |
|      |   | 2.0 | 200 | 1.5 | 0.11  | 1.79  | 48    | 55 |
|      |   | 2.1 | 210 | 1.5 | 0.11  | 1.85  | 49    | 57 |
|      |   | 2.5 | 250 | 1.7 | 0.12  | 2.04  | 42    | 49 |

8



2.4 m  
1/4, 1/2, 3/4  
0°

|      |   |     |     |     |       |       | mm/hr |    |
|------|---|-----|-----|-----|-------|-------|-------|----|
|      |   | bar | kPa | m   | m³/hr | l/min |       |    |
| 90°  | Q | 1.0 | 100 | 1.7 | 0.04  | 0.62  | 51    | 59 |
|      |   | 1.5 | 150 | 2.1 | 0.05  | 0.84  | 46    | 53 |
|      |   | 2.0 | 200 | 2.4 | 0.06  | 1.00  | 42    | 48 |
|      |   | 2.1 | 210 | 2.4 | 0.06  | 1.03  | 43    | 49 |
|      |   | 2.5 | 250 | 2.7 | 0.07  | 1.13  | 37    | 43 |
| 120° | T | 1.0 | 100 | 1.7 | 0.05  | 0.83  | 51    | 59 |
|      |   | 1.5 | 150 | 2.1 | 0.07  | 1.12  | 46    | 53 |
|      |   | 2.0 | 200 | 2.4 | 0.08  | 1.33  | 42    | 48 |
|      |   | 2.1 | 210 | 2.4 | 0.08  | 1.37  | 43    | 49 |
|      |   | 2.5 | 250 | 2.7 | 0.09  | 1.51  | 37    | 33 |
| 180° | H | 1.0 | 100 | 1.7 | 0.08  | 1.33  | 55    | 64 |
|      |   | 1.5 | 150 | 2.1 | 0.10  | 1.69  | 46    | 53 |
|      |   | 2.0 | 200 | 2.4 | 0.12  | 1.99  | 42    | 48 |
|      |   | 2.1 | 210 | 2.4 | 0.12  | 2.05  | 43    | 49 |
|      |   | 2.5 | 250 | 2.7 | 0.14  | 2.27  | 37    | 43 |
| 360° | F | 1.0 | 100 | 1.7 | 0.16  | 2.67  | 55    | 64 |
|      |   | 1.5 | 150 | 2.1 | 0.20  | 3.37  | 46    | 53 |
|      |   | 2.0 | 200 | 2.4 | 0.24  | 3.99  | 42    | 48 |
|      |   | 2.1 | 210 | 2.4 | 0.25  | 4.10  | 43    | 49 |
|      |   | 2.5 | 250 | 2.7 | 0.27  | 4.54  | 37    | 43 |

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/pro-gudingjiaodupenzui/5q020326>