



1.5 m
1/4, 1/2, 3/4
0°

							mm/hr	
		bar	kPa	m	m³/hr	l/min		
90°	Q	1.0	100	1.1	0.02	0.30	60	69
		1.5	150	1.3	0.02	0.38	54	62
		2.0	200	1.5	0.03	0.45	48	55
		2.1	210	1.5	0.03	0.46	49	57
		2.5	250	1.7	0.03	0.51	42	49
120°	T	1.0	100					
		1.5	150					
		2.0	200			4A		
		2.1	210					
		2.5	250					
180°	H	1.0	100	1.1	0.40	0.60	60	69
		1.5	150	1.3	0.05	0.76	54	62
		2.0	200	1.5	0.05	0.90	48	53
		2.1	210	1.5	0.06	0.92	49	57
		2.5	250	1.7	0.06	1.02	42	49
360°	F	1.0	100	1.1	0.07	1.2	60	69
		1.5	150	1.3	0.09	1.52	54	62
		2.0	200	1.5	0.11	1.79	48	55
		2.1	210	1.5	0.11	1.85	49	57
		2.5	250	1.7	0.12	2.04	42	49

8



2.4 m
1/4, 1/2, 3/4
0°

							mm/hr	
		bar	kPa	m	m³/hr	l/min		
90°	Q	1.0	100	1.7	0.04	0.62	51	59
		1.5	150	2.1	0.05	0.84	46	53
		2.0	200	2.4	0.06	1.00	42	48
		2.1	210	2.4	0.06	1.03	43	49
		2.5	250	2.7	0.07	1.13	37	43
120°	T	1.0	100	1.7	0.05	0.83	51	59
		1.5	150	2.1	0.07	1.12	46	53
		2.0	200	2.4	0.08	1.33	42	48
		2.1	210	2.4	0.08	1.37	43	49
		2.5	250	2.7	0.09	1.51	37	33
180°	H	1.0	100	1.7	0.08	1.33	55	64
		1.5	150	2.1	0.10	1.69	46	53
		2.0	200	2.4	0.12	1.99	42	48
		2.1	210	2.4	0.12	2.05	43	49
		2.5	250	2.7	0.14	2.27	37	43
360°	F	1.0	100	1.7	0.16	2.67	55	64
		1.5	150	2.1	0.20	3.37	46	53
		2.0	200	2.4	0.24	3.99	42	48
		2.1	210	2.4	0.25	4.10	43	49
		2.5	250	2.7	0.27	4.54	37	43

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/pro-gudingjiaodupenzui/12q020326>