

10A-HE



000000

Prüfung

SKU: 10AHE

3.0 0° 360°

Shipping Information

UPC-A: 0611698945391

4000

4000

□250

Additional Information

3.0 m

8A-HE



2.4

0° 360°

20°

	bar	kPa	m				mm/h
	1.0	100	2.0	0.05	0.87	52	60
90°	1.5	150	2.2	0.06	1.02	51	59
	2.1	210	2.4	0.06	1.06	44	51
	2.5	250	2.6	0.07	1.21	43	50
	3.0	300	2.8	0.08	1.32	41	47
	1.0	100	2.0	0.10	1.65	49	57
180°	1.5	150	2.2	0.11	1.85	46	53
	2.1	210	2.4	0.12	2.08	43	50
	2.5	250	2.6	0.14	2.37	42	48
	3.0	300	2.8	0.15	2.57	39	45
	1.0	100	2.0	0.15	2.47	49	57
270°	1.5	150	2.2	0.17	2.78	46	53
	2.1	210	2.4	0.19	3.11	43	50
	2.5	250	2.6	0.21	3.55	42	48
	3.0	300	2.8	0.23	3.86	39	45
	1.0	100	2.0	0.20	3.29	49	57
360°	1.5	150	2.2	0.22	3.71	46	53
	2.1	210	2.4	0.25	4.15	43	50
	2.5	250	2.6	0.28	4.73	42	50
	3.0	300	2.8	0.31	5.50	39	45

10A-HE



3.0

0° 360°

25°

	bar	kPa	m				mm/h
	1.0	100	2.7	0.08	1.36	45	52
90°	1.5	150	2.8	0.09	1.55	48	55
	2.1	210	3.0	0.10	1.67	44	51
	2.5	250	3.1	0.11	1.82	45	52
	3.0	300	3.2	0.12	1.93	45	52
	1.0	100	2.7	0.16	2.65	44	50
180°	1.5	150	2.8	0.18	2.94	45	52
	2.1	210	3.0	0.19	3.24	43	50
	2.5	250	3.1	0.21	3.52	44	51
	3.0	300	3.2	0.23	3.79	44	51
	1.0	100	2.7	0.24	3.97	44	50
270°	1.5	150	2.8	0.26	4.41	45	52
	2.1	210	3.0	0.29	4.85	43	50
	2.5	250	3.1	0.32	5.28	44	51
	3.0	300	3.2	0.34	5.68	44	51
	1.0	100	2.7	0.32	5.30	44	50
360°	1.5	150	2.8	0.35	5.88	45	52
	2.1	210	3.0	0.39	6.47	43	50
	2.5	250	3.1	0.42	7.04	44	51

3.0

300

3.2

0.45

7.57

44

51

12A-HE



3.7

0° 360°

25°

mm/h

bar

kPa

m

/



90°



1.0

1.5

2.1

2.5

3.0

1.0

1.5

2.1

2.5

3.0

1.0

1.5

2.1

2.5

3.0

1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

100

150

210

250

300

100

150

210

250

300

3.3

3.5

3.7

3.8

3.9

3.3

3.5

3.7

3.8

3.9

3.3

3.5

3.7

3.8

3.9

3.3

3.5

3.7

3.8

3.9

0.12

0.13

0.14

0.16

0.17

0.23

0.125

0.30

0.33

0.35

0.38

0.42

0.45

0.50

0.47

0.51

0.55

0.60

0.66

2.01

2.23

2.38

2.65

2.84

3.88

4.24

5.03

5.53

5.82

6.36

6.93

7.55

8.29

7.76

8.48

9.24

10.07

11.05

44

44

42

44

45

43

42

42

42

42

43

42

40

42

44

43

42

40

42

44

51

51

48

51

51

49

48

47

48

50

49

48

47

48

50

49

48

47

48

50

15-HE



4.6

0° 360°

25°

mm/h

bar

kPa

m

/



90°



1.0

1.5

2.1

2.5

3.0

1.0

1.5

2.1

2.5

3.0

1.0

1.5

2.1

2.5

3.0

1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

100

150

210

250

300

100

150

210

250

300

4.2

4.4

4.6

4.7

4.8

4.2

4.4

4.6

4.7

4.8

4.2

4.4

4.6

4.7

4.8

4.2

4.4

4.6

4.7

4.8

0.18

0.20

0.22

0.24

0.26

0.35

0.38

0.42

0.47

0.50

0.52

0.57

0.64

0.70

0.75

0.69

0.77

0.85

0.93

1.01

2.95

3.33

3.63

4.05

4.28

5.78

6.38

7.08

7.76

8.39

8.67

9.58

10.62

11.64

12.59

11.56

12.77

14.16

15.52

16.78

40

41

41

44

45

39

40

40

42

44

39

40

40

42

42

39

40

40

42

44

46

48

48

51

51

45

46

46

49

50

45

46

46

49

50

45

46

46

49

50

17-HE



4.6

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/pro-gaoxiaopenzui/10a-he020326>