



15A-HE

1/2" NPT

1/2" NPT

1/2" NPT 1/2" NPT

SKU: 15AHE

1/2" NPT 4.6" 0° 360°

Shipping Information

UPC-A: 0611698945414

40000

40000

250

Additional Information

15'

8A-HE



2.4

0° 360°

20°

	bar	kPa	m				mm/h
	1.0	100	2.0	0.05	0.87	52	60
90°	1.5	150	2.2	0.06	1.02	51	59
	2.1	210	2.4	0.06	1.06	44	51
	2.5	250	2.6	0.07	1.21	43	50
	3.0	300	2.8	0.08	1.32	41	47
	1.0	100	2.0	0.10	1.65	49	57
180°	1.5	150	2.2	0.11	1.85	46	53
	2.1	210	2.4	0.12	2.08	43	50
	2.5	250	2.6	0.14	2.37	42	48
	3.0	300	2.8	0.15	2.57	39	45
	1.0	100	2.0	0.15	2.47	49	57
270°	1.5	150	2.2	0.17	2.78	46	53
	2.1	210	2.4	0.19	3.11	43	50
	2.5	250	2.6	0.21	3.55	42	48
	3.0	300	2.8	0.23	3.86	39	45
	1.0	100	2.0	0.20	3.29	49	57
360°	1.5	150	2.2	0.22	3.71	46	53
	2.1	210	2.4	0.25	4.15	43	50
	2.5	250	2.6	0.28	4.73	42	50
	3.0	300	2.8	0.31	5.50	39	45

10A-HE



3.0

0° 360°

25°

	bar	kPa	m				mm/h
	1.0	100	2.7	0.08	1.36	45	52
90°	1.5	150	2.8	0.09	1.55	48	55
	2.1	210	3.0	0.10	1.67	44	51
	2.5	250	3.1	0.11	1.82	45	52
	3.0	300	3.2	0.12	1.93	45	52
	1.0	100	2.7	0.16	2.65	44	50
180°	1.5	150	2.8	0.18	2.94	45	52
	2.1	210	3.0	0.19	3.24	43	50
	2.5	250	3.1	0.21	3.52	44	51
	3.0	300	3.2	0.23	3.79	44	51
	1.0	100	2.7	0.24	3.97	44	50
270°	1.5	150	2.8	0.26	4.41	45	52
	2.1	210	3.0	0.29	4.85	43	50
	2.5	250	3.1	0.32	5.28	44	51
	3.0	300	3.2	0.34	5.68	44	51
	1.0	100	2.7	0.32	5.30	44	50
360°	1.5	150	2.8	0.35	5.88	45	52
	2.1	210	3.0	0.39	6.47	43	50
	2.5	250	3.1	0.42	7.04	44	51

3.0

300

3.2

0.45

7.57

44

51

12A-HE



3.7

0° 360°

25°

mm/h

bar

kPa

m

/



90°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

3.3

3.5

3.7

3.8

3.9

0.12

0.13

0.14

0.16

0.17

2.01

2.23

2.38

2.65

2.84

44

44

42

44

45

51

51

48

51

51

180°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

3.3

3.5

3.7

3.8

3.9

0.23

0.125

0.28

0.30

0.33

3.88

4.24

4.62

5.03

5.53

43

42

40

42

42

49

48

47

48

50

270°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

3.3

3.5

3.7

3.8

3.9

0.35

0.38

0.42

0.45

0.50

5.82

6.36

6.93

7.55

8.29

43

42

40

42

44

49

48

47

48

50

360°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

3.3

3.5

3.7

3.8

3.9

0.47

0.51

0.55

0.60

0.66

7.76

8.48

9.24

10.07

11.05

43

42

40

42

44

49

48

47

48

50

15-HE



4.6

0° 360°

25°

mm/h

bar

kPa

m

/



90°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

4.2

4.4

4.6

4.7

4.8

0.18

0.20

0.22

0.24

0.26

2.95

3.33

3.63

4.05

4.28

40

41

41

44

45

46

48

48

51

51

180°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

4.2

4.4

4.6

4.7

4.8

0.35

0.38

0.42

0.47

0.50

5.78

6.38

7.08

7.76

8.39

39

40

40

42

44

45

46

46

49

50

270°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

4.2

4.4

4.6

4.7

4.8

0.52

0.57

0.64

0.70

0.75

8.67

9.58

10.62

11.64

12.59

39

40

40

42

42

45

46

46

49

50

360°



1.0

1.5

2.1

2.5

3.0

100

150

210

250

300

4.2

4.4

4.6

4.7

4.8

0.69

0.77

0.85

0.93

1.01

11.56

12.77

14.16

15.52

16.78

39

40

40

42

44

45

46

46

49

50

17-HE



4.6

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/pro-gaoxiaopenzui/15a-he020326>