

PGV Jar-Top

概述

特点

- 安装简单
- 可拆卸设计
- 环保设计
- Hunter 独特的喷头设计
- 高效喷洒

兼容性

- Accu Sync™ 系统*
- 电源适配器 P/N 458200
- 电源线 (P/N 464322)

连接

- LS 管道连接
- DC 管道连接

尺寸

- 0.05 m^3/hr 0.7 l/min
- 1.5 bar 150 kPa
- 66°C
- 2

电源

- 24 VAC 电源
 - 350 mA 190mA 60 Hz
 - 370 mA 210mA 50 Hz



1" 25 MM PGV

流量 m^3/hr	压力 bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23
5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1" 25 MM PGV

Flow/hr	Pressure/kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/diancifa/pgv-jar-top>

020326