

MP

MP 30%

- 10
-
-
-
-
-
-
-
-

- 25%
- 2.8 bar/280 kPa
- 2.1bar,210kPa
- 3

- Pro-Spray™ PRS40 2.8 bar
- Pro-Spray™ PRS30 2.1 bar



MP1000

- 2.5 to 4.5 m
-
- 90° to 210°
- 110° to 270°
- 160°

°	mm			m	l/min		in/hr	
	bar	kPa			m³/hr	l/min	■	▲
90° 	1.7	170		-	-	-	-	-
	2.0	200		3.7	0.04	0.64	11	13
	2.5	250		4	0.04	0.72	11	13
	2.8	280		4.1	0.05	0.8	11	13
	3.0	300		4.3	0.05	0.87	11	13
	3.5	350		4.5	0.06	0.95	11	13
	3.8	380		4.5	0.06	1.02	12	14
180° 	1.7	170		-	-	-	-	-
	2.0	200		3.7	0.08	1.29	11	13
	2.5	250		4	0.09	1.44	11	13
	2.8	280		4.1	0.1	1.59	11	13
	3.0	300		4.3	0.1	1.67	11	13
	3.5	350		4.5	0.12	1.9	11	13
	3.8	380		4.5	0.12	1.93	12	13
210° 	1.7	170		-	-	-	-	-
	2.0	200		3.7	0.09	1.52	12	13
	2.5	250		4	0.1	1.71	11	13
	2.8	280		4.1	0.11	1.86	11	13
	3.0	300		4.3	0.12	1.93	11	13
	3.5	350		4.5	0.13	2.16	11	13
	3.8	380		4.5	0.14	2.24	11	13
270° 	1.7	170		-	-	-	-	-
	2.0	200		3.7	0.11	1.82	11	12
	2.5	250		4	0.12	2.01	10	12
	2.8	280		4.1	0.14	2.39	11	13
	3.0	300		4.3	0.15	2.54	11	13
	3.5	350		4.5	0.17	2.73	11	13
	3.8	380		4.5	0.17	2.84	11	13
360° 	1.7	170		-	-	-	-	-
	2.0	200		3.7	0.16	2.62	12	13
	2.5	250		4	0.18	2.92	11	13
	2.8	280		4.1	0.19	3.18	11	13
	3.0	300		4.3	0.2	3.34	11	13
	3.5	350		4.5	0.23	3.71	11	13
	3.8	380		4.5	0.23	3.83	11	13

MP2000

0 - 6.4 m

000000

90° - 210°

210° - 270°

360°

□□		□□		□□	□□		□□□□ in/hr		
		bar	kPa		m	m³/hr	l/min	■	▲
90° 	1.7	170		5.2	0.08	1.29	12	13	
	2.0	200		5.5	0.09	1.44	12	13	
	2.5	250		5.8	0.09	1.52	11	13	
	2.8	280		6.1	0.1	1.63	11	12	
	3.0	300		6.4	0.11	1.74	10	12	
	3.5	350		6.4	0.11	1.78	11	12	
	3.8	380		6.4	0.11	1.82	11	12	
180° 	1.7	170		4.9	0.14	2.27	11	13	
	2.0	200		5.2	0.15	2.43	11	13	
	2.5	250		5.5	0.16	2.69	11	12	
	2.8	280		5.8	0.18	2.92	11	12	
	3.0	300		6.1	0.2	3.22	11	12	
	3.5	350		6.4	0.21	3.45	10	12	
	3.8	380		6.4	0.22	3.6	11	12	
210° 	1.7	170		4.9	0.17	2.73	12	14	
	2.0	200		5.2	0.17	2.84	11	13	
	2.5	250		5.5	0.19	3.07	11	12	
	2.8	280		5.8	0.2	3.26	10	12	
	3.0	300		6.1	0.21	3.45	10	11	
	3.5	350		6.4	0.23	3.71	9	11	
	3.8	380		6.4	0.23	3.83	10	11	
270° 	1.7	170		4.9	0.2	3.3	11	13	
	2.0	200		5.2	0.22	3.6	11	12	
	2.5	250		5.5	0.24	3.9	10	12	
	2.8	280		5.8	0.25	4.17	10	12	
	3.0	300		6.1	0.27	4.43	10	11	
	3.5	350		6.4	0.28	4.66	9	11	
	3.8	380		6.4	0.3	4.93	10	11	
360° 	1.7	170		4.9	0.28	4.55	11	13	
	2.0	200		5.2	0.29	4.85	11	13	
	2.5	250		5.5	0.32	5.19	10	12	
	2.8	280		5.8	0.34	5.61	10	12	
	3.0	300		6.1	0.36	5.95	10	11	
	3.5	350		6.4	0.39	6.37	9	11	
	3.8	380		6.4	0.4	6.59	10	11	

MP3000

7 - 9.1 m

90° - 210°

210° - 270°

360°

°	mm			m	l/min		in/hr	
	bar	kPa			m³/hr		■	▲
90° 	1.7	170		7.6	0.16	2.69	11	13
	2.0	200		8.2	0.17	2.88	10	12
	2.5	250		8.5	0.19	3.11	10	12
	2.8	280		9.1	0.2	3.26	10	11
	3.0	300		9.1	0.21	3.41	10	12
	3.5	350		9.1	0.22	3.6	11	12
	3.8	380		9.1	0.23	3.83	11	13
180° 	1.7	170		7.6	0.33	5.46	11	13
	2.0	200		8.2	0.36	5.99	11	12
	2.5	250		8.5	0.39	6.44	11	12
	2.8	280		9.1	0.42	6.9	10	12
	3.0	300		9.1	0.44	7.31	11	12
	3.5	350		9.1	0.47	7.73	11	13
	3.8	380		9.1	0.49	8.07	12	14
210° 	1.7	170		7.6	0.39	6.37	11	13
	2.0	200		8.2	0.42	6.97	11	12
	2.5	250		8.5	0.46	7.54	11	13
	2.8	280		9.1	0.49	8.03	10	12
	3.0	300		9.1	0.52	8.53	11	12
	3.5	350		9.1	0.55	8.98	11	13
	3.8	380		9.1	0.57	9.44	12	14
270° 	1.7	170		7.6	0.5	8.3	12	13
	2.0	200		8.2	0.55	8.98	11	12
	2.5	250		8.5	0.59	9.66	11	12
	2.8	280		9.1	0.63	10.35	10	12
	3.0	300		9.1	0.66	10.95	11	12
	3.5	350		9.1	0.7	11.6	11	13
	3.8	380		9.1	0.74	12.2	12	14
360° 	1.7	170		7.6	0.66	10.92	11	13
	2.0	200		8.2	0.72	11.94	11	12
	2.5	250		8.5	0.78	12.89	11	12
	2.8	280		9.1	0.84	13.8	10	12
	3.0	300		9.1	0.89	14.63	11	12
	3.5	350		9.1	0.94	15.43	11	13
	3.8	380		9.1	0.98	16.18	12	14

MP3500

Ø 4 - 10.7 m
□□□□□□
190° - 210°

⬜	⬜		⬜	⬜		⬜ in/hr	
	bar	kPa		m	m³/hr	l/min	⬛ ▲
90° 	1.7	170		10.1	0.24	3.94	9 11
	2.0	200		10.4	0.26	4.28	10 11
	2.5	250		10.4	0.28	4.58	10 12
	2.8	280		10.7	0.29	4.84	10 12
	3.0	300		10.7	0.31	5.22	11 13
	3.5	350		10.7	0.33	5.41	11 13
	3.8	380		10.7	0.34	5.68	12 14
180° 	1.7	170		10.1	0.50	8.36	10 11
	2.0	200		10.4	0.51	8.48	9 11
	2.5	250		10.4	0.60	10.03	11 13
	2.8	280		10.7	0.65	10.83	11 13
	3.0	300		10.7	0.70	11.73	12 14
	3.5	350		10.7	0.73	12.15	13 15
	3.8	380		10.7	0.75	12.41	13 15
210° 	1.7	170		10.1	0.59	9.80	10 12
	2.0	200		10.4	0.65	10.75	10 12
	2.5	250		10.4	0.70	11.66	11 13
	2.8	280		10.7	0.75	12.45	11 13
	3.0	300		10.7	0.80	13.40	12 14
	3.5	350		10.7	0.85	14.23	13 15
	3.8	380		10.7	0.90	14.91	13 16
270° 	1.7	170					
	2.0	200					
	2.5	250					
	2.8	280				⬜	
	3.0	300					
	3.5	350					
	3.8	380					
360° 	1.7	170					
	2.0	200					
	2.5	250					
	2.8	280				⬜	
	3.0	300					
	3.5	350					
	3.8	380					

⬜⬜⬜⬜

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/mp-rotator/biaozhun-mp-xuanzhuanshexianpenzui>
020326