

MP-820-360



MP

MP® MP800

SKU: MP820360

MP 20 / 4.6 7.3 360°

Dimensions

25.40



Operating Specifications

Arc: 360°

Operating Pressure: 2.8 bar280 kPa

Precipitation Rate: 20 /

Radius: 1.8 7.3

Flow: 0.77 1.03 /12.85 17.13 /

Shipping Information

UPC-A: 196055004824

1

290

Additional Information

360°

1.5' - 24'

MP ROTATOR ???? - ??*

MP800SR

???1.8 ? 3.5 ?
????
???????90° ? 210°
???????360°

						mm/h					
	bar	kPa		m	m ³ /hr	l/min	■	▲	m	m ³ /hr	l/min
90° 	2.1	200		2.6	0.04	0.61	22	25	1.8	0.03	0.49
	2.5	250		2.9	0.04	0.72	21	24	2.1	0.03	0.55
	2.8	280		3.1	0.05	0.87	21	24	2.4	0.04	0.61
	3.0	300		3.4	0.06	0.95	20	23	2.4	0.04	0.68
	3.5	350		3.5	0.06	1.02	20	23	2.7	0.04	0.72
	3.8	380		3.5	0.06	1.06	20	23	3.0	0.05	0.76
180° 	2.1	200		2.6	0.07	1.21	22	25	1.8	0.06	0.98
	2.5	250		2.8	0.08	1.40	21	24	2.1	0.07	1.10
	2.8	280		3.0	0.10	1.59	21	24	2.4	0.07	1.21
	3.0	300		3.3	0.10	1.74	19	22	2.4	0.08	1.36
	3.5	350		3.4	0.11	1.82	19	22	2.7	0.09	1.44
	3.8	380		3.5	0.11	1.89	18	21	3.0	0.09	1.51
210° 	2.1	200		2.6	0.08	1.40	22	25	1.8	0.07	1.15
	2.5	250		2.8	0.10	1.67	22	25	2.1	0.08	1.28
	2.8	280		3.0	0.11	1.85	21	24	2.4	0.08	1.41
	3.0	300		3.2	0.12	2.01	20	23	2.4	0.10	1.59
	3.5	350		3.4	0.13	2.12	19	22	2.7	0.10	1.68
	3.8	380		3.5	0.13	2.20	18	21	3.0	0.11	1.77
360° 	2.1	200		2.6	0.14	2.38	22	25	1.8	0.11	1.78
	2.5	250		2.8	0.16	2.65	20	23	2.1	0.12	1.97
	2.8	280		3.0	0.18	2.95	20	23	2.4	0.13	2.12
	3.0	300		3.1	0.19	3.22	20	23	2.4	0.13	2.23
	3.5	350		3.3	0.20	3.33	19	21	2.7	0.14	2.38
	3.8	380		3.5	0.22	3.71	18	21	3.0	0.16	2.65

MP Rotator 2.8 bar280 kPa Hunter PR540 MP Rotator 2.8 bar280 kPa

*

MP815

???2.5 ? 4.9 m
????????
???????90° ? 210°
???????210° ? 270°
???????360°

	bar	kPa		m	m ³ /hr	l/min	■	▲
90° 	2.1	210		4.3	0.10	1.59	21	24
	2.5	250		4.5	0.10	1.74	21	24
	2.8	280		4.6	0.11	1.85	21	24
	3.1	310		4.8	0.12	1.97	21	24
	3.5	350		4.9	0.12	2.08	21	24
	3.8	380		4.9	0.13	2.20	22	25

180° 	2.1	210		4.0	0.17	2.84	21	25
	2.5	250		4.3	0.20	3.26	21	24
	2.8	280		4.5	0.21	3.52	21	24
	3.1	310		4.6	0.22	3.63	21	24
	3.5	350		4.8	0.24	4.01	21	24
210° 	3.8	380		4.9	0.25	4.20	21	24
	2.1	210		4.0	0.20	3.33	21	25
	2.5	250		4.3	0.22	3.63	20	23
	2.8	280		4.5	0.25	4.16	21	24
	3.1	310		4.6	0.26	4.39	21	25
270° 	3.5	350		4.8	0.28	4.69	21	24
	3.8	380		4.9	0.30	4.92	21	24
	2.1	210		4.0	0.26	4.31	22	25
	2.5	250		4.3	0.28	4.69	20	23
	2.8	280		4.5	0.32	5.30	21	24
360° 	3.1	310		4.6	0.33	5.56	21	24
	3.5	350		4.8	0.35	5.83	20	23
	3.8	380		4.9	0.37	6.09	20	23
	2.1	210		4.0	0.35	5.75	22	25
	2.5	250		4.3	0.39	6.43	21	24
	2.8	280		4.5	0.42	7.08	21	24
	3.1	310		4.6	0.45	7.57	21	25
	3.5	350		4.8	0.48	8.06	21	24
	3.8	380		4.9	0.51	8.55	21	25

?? = MP Rotator ?????? 2.8 ??280 ???????????? Pro-Spray PRS40 ? MP Rotator ????????????? 2.8 ??280 ???

MP-815									
									
2.5 4.9 m									
									
90°210°									
210°270°									
360°									
									
	bar	kPa		m	m3/hr	□/□	■	▲	
90° 	2.1	210		4.3	0.10	1.59	21	24	
	2.5	250		4.5	0.10	1.74	21	24	
	2.8	280		4.6	0.11	1.85	21	24	
	3.1	310		4.8	0.12	1.97	21	24	
	3.5	350		4.9	0.12	2.08	21	24	
180° 	3.8	380		4.9	0.13	2.20	22	25	
	2.1	210		4.0	0.17	2.84	21	25	
	2.5	250		4.3	0.20	3.26	21	24	
	2.8	280		4.5	0.21	3.52	21	24	
	3.1	310		4.6	0.22	3.63	21	24	
210° 	3.5	350		4.8	0.24	4.01	21	24	
	3.8	380		4.9	0.25	4.20	21	24	
	2.1	210		4.0	0.20	3.33	21	25	
	2.5	250		4.3	0.22	3.63	20	23	
	2.8	280		4.5	0.25	4.16	21	24	
270° 	3.1	310		4.6	0.26	4.39	21	25	
	3.5	350		4.8	0.28	4.69	21	24	
	3.8	380		4.9	0.30	4.92	21	24	
	2.1	210		4.0	0.26	4.31	22	25	
	2.5	250		4.3	0.28	4.69	20	23	
360° 	2.8	280		4.5	0.32	5.30	21	24	
	3.1	310		4.6	0.33	5.56	21	24	
	3.5	350		4.8	0.35	5.83	20	23	
	3.8	380		4.9	0.37	6.09	20	23	
	2.1	210		4.0	0.35	5.75	22	25	
	2.5	250		4.3	0.39	6.43	21	24	
	2.8	280		4.5	0.42	7.08	21	24	
	3.1	310		4.6	0.45	7.57	21	25	
	3.5	350		4.8	0.48	8.06	21	24	
	3.8	380		4.9	0.51	8.55	21	25	

MP 2.8 bar280 kPa Pro-Spray PRS40 MP

MP-820

4.8 7.3
210°
270°
360°

	bar	kPa	m	m3/hr	l/h	■	▲
90° 	2.1	210	6.1	0.19	3.20	21	24
	2.5	250	6.4	0.21	3.51	21	24
	2.8	280	6.7	0.22	3.65	20	23
	3.0	300	7.0	0.24	4.01	20	23
	3.5	350	7.3	0.25	4.19	19	22
180° 	3.8	380	7.3	0.26	4.37	20	23
	2.1	210	6.1	0.39	6.50	21	24
	2.5	250	6.4	0.41	6.86	20	23
	2.8	280	6.7	0.46	7.58	20	23
	3.0	300	6.7	0.47	7.79	21	24
210° 	3.5	350	7.0	0.50	8.36	20	24
	3.8	380	7.3	0.54	8.92	20	23
	2.1	210	6.1	0.44	7.34	20	23
	2.5	250	6.4	0.48	7.92	20	23
	2.8	280	6.7	0.54	8.93	20	24
270° 	3.0	300	6.7	0.54	9.02	21	24
	3.5	350	7.0	0.57	9.54	20	23
	3.8	380	7.3	0.60	10.06	19	22
	2.1	210	6.1	0.58	9.58	21	24
	2.5	250	6.4	0.62	10.36	20	23
360° 	2.8	280	6.7	0.68	11.35	20	23
	3.0	300	6.7	0.71	11.81	21	24
	3.5	350	7.0	0.75	12.49	20	24
	3.8	380	7.3	0.79	13.16	20	23
	2.1	210	6.1	0.77	12.85	21	24
	2.5	250	6.4	0.84	13.92	20	24
	2.8	280	6.7	0.90	14.99	20	23
	3.0	300	6.7	0.93	15.41	21	24
	3.5	350	7.0	0.98	16.27	20	23
	3.8	380	7.3	1.03	17.13	19	22

MP 2.8 bar280 kPa Pro-Spray PRS40 MP 2.8 bar280 kPa

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/mp-xuanzhuanshexianpentour-mp800-penzui/mp-820-360>
020326