



Pro



- 0° 360°
-
-
-
-
-
-



- 2.1 bar210 kPa
- Pro-Spray™ PRS30 2.1 bar210 kPa
- 2



			4A 4" x 1"						6A 6" x 1"					
			1.2 m						1.8 m					
			0°- 360°						0°- 360°					
			0°						0°					
°						mm/hr						mm/hr		
	bar	kPa	m	m³/hr	l/min	▲	▲	m	m³/hr	l/min	▲	▲		
45° 	1.0	100	0.9	0.02	0.31	187	216	1.5	0.03	0.54	117	136		
	1.5	150	1.0	0.02	0.39	178	206	1.6	0.04	0.60	108	124		
	2.1	210	1.2	0.03	0.48	167	193	1.8	0.04	0.65	98	114		
	2.5	250	1.3	0.03	0.56	158	183	1.9	0.04	0.70	92	106		
	3.0	300	1.4	0.04	0.64	149	172	2.1	0.05	0.75	86	99		
90° 	1.0	100	0.9	0.04	0.72	213	246	1.5	0.06	1.08	116	134		
	1.5	150	1.0	0.05	0.76	182	210	1.6	0.07	1.21	109	126		
	2.1	210	1.2	0.05	0.83	139	160	1.8	0.08	1.35	102	118		
	2.5	250	1.3	0.05	0.91	129	149	1.9	0.09	1.47	97	112		
	3.0	300	1.4	0.06	0.95	116	134	2.1	0.10	1.61	92	106		
120° 	1.0	100	0.9	0.06	0.97	221	255	1.5	0.08	1.26	102	118		
	1.5	150	1.0	0.07	1.10	188	217	1.6	0.09	1.43	97	112		
	2.1	210	1.2	0.07	1.25	162	187	1.8	0.10	1.61	91	105		
	2.5	250	1.3	0.08	1.36	146	168	1.9	0.11	1.76	87	100		
	3.0	300	1.4	0.09	1.49	131	151	2.1	0.12	1.93	82	95		
180° 	1.0	100	0.9	0.07	1.18	178	206	1.5	0.10	1.70	92	106		
	1.5	150	1.0	0.08	1.38	157	181	1.6	0.12	1.96	88	102		
	2.1	210	1.2	0.10	1.60	139	160	1.8	0.13	2.24	84	97		
	2.5	250	1.3	0.11	1.78	127	146	1.9	0.15	2.47	81	94		
	3.0	300	1.4	0.12	1.98	115	133	2.1	0.16	2.72	78	90		
240° 	1.0	100	0.9	0.12	1.94	220	254	1.5	0.15	2.44	99	114		
	1.5	150	1.0	0.13	2.24	192	221	1.6	0.17	2.83	96	111		
	2.1	210	1.2	0.16	2.59	168	194	1.8	0.20	3.28	92	107		
	2.5	250	1.3	0.17	2.86	153	177	1.9	0.22	3.63	89	103		
	3.0	300	1.4	0.19	3.17	139	160	2.1	0.24	4.03	86	99		
270° 	1.0	100	0.9	0.13	2.09	211	244	1.5	0.18	3.08	111	128		
	1.5	150	1.0	0.14	2.40	183	211	1.6	0.21	3.52	106	122		
	2.1	210	1.2	0.16	2.75	159	183	1.8	0.24	4.02	101	116		
	2.5	250	1.3	0.18	3.02	144	166	1.9	0.27	4.42	97	112		
	3.0	300	1.4	0.20	3.33	130	150	2.1	0.29	4.87	92	107		
360° 	1.0	100	0.9	0.14	2.26	171	197	1.5	0.21	3.57	96	111		
	1.5	150	1.0	0.16	2.60	148	171	1.6	0.24	4.07	92	106		
	2.1	210	1.2	0.18	2.98	129	149	1.8	0.28	4.62	87	100		
	2.5	250	1.3	0.20	3.29	117	135	1.9	0.30	5.06	83	96		
	3.0	300	1.4	0.22	3.63	106	122	2.1	0.33	5.56	79	92		

		8A 						10A 					
		2.4 m						3.0 m					
		0°- 360° 						0°- 360° 					
		0°						15°					
													
	bar	kPa	m	m³/hr	l/min			m	m³/hr	l/min			
45° 	1.0	100	2.0	0.04	0.62	77	89	2.6	0.04	0.68	49	56	
	1.5	150	2.2	0.04	0.72	72	83	2.8	0.05	0.80	49	57	
	2.1	210	2.4	0.05	0.83	67	77	3.0	0.06	0.94	49	56	
	2.5	250	2.6	0.05	0.91	63	73	3.2	0.06	1.06	48	56	
	3.0	300	2.9	0.06	1.01	59	68	3.5	0.07	1.18	47	54	
90° 	1.0	100	2.0	0.07	1.24	77	89	2.6	0.08	1.35	49	56	
	1.5	150	2.2	0.09	1.44	72	83	2.8	0.10	1.61	49	57	
	2.1	210	2.4	0.10	1.65	67	77	3.0	0.11	1.89	49	56	
	2.5	250	2.6	0.11	1.82	63	73	3.2	0.13	2.11	48	56	
	3.0	300	2.9	0.12	2.02	59	68	3.5	0.14	2.37	47	54	
120° 	1.0	100	2.0	0.10	1.66	77	89	2.6	0.11	1.80	49	56	
	1.5	150	2.2	0.11	1.92	72	83	2.8	0.13	2.14	49	57	
	2.1	210	2.4	0.13	2.20	67	77	3.0	0.15	2.52	49	56	
	2.5	250	2.6	0.15	2.43	63	73	3.2	0.17	2.82	48	56	
	3.0	300	2.9	0.16	2.69	59	68	3.5	0.19	3.16	47	54	
180° 	1.0	100	2.0	0.15	2.49	77	89	2.6	0.16	2.71	49	56	
	1.5	150	2.2	0.17	2.87	72	83	2.8	0.19	3.21	49	57	
	2.1	210	2.4	0.20	3.30	67	77	3.0	0.23	3.78	49	56	
	2.5	250	2.6	0.22	3.65	63	73	3.2	0.25	4.23	48	56	
	3.0	300	2.9	0.24	4.03	59	68	3.5	0.28	4.73	47	54	
240° 	1.0	100	2.0	0.20	3.32	77	89	2.6	0.22	3.61	49	56	
	1.5	150	2.2	0.23	3.83	72	83	2.8	0.26	4.28	49	57	
	2.1	210	2.4	0.26	4.40	67	77	3.0	0.30	5.03	49	56	
	2.5	250	2.6	0.29	4.86	63	73	3.2	0.34	5.64	48	56	
	3.0	300	2.9	0.32	5.38	59	68	3.5	0.38	6.31	47	54	
270° 	1.0	100	2.0	0.22	3.73	77	89	2.6	0.24	4.06	49	56	
	1.5	150	2.2	0.26	4.31	72	83	2.8	0.29	4.82	49	57	
	2.1	210	2.4	0.30	4.95	67	77	3.0	0.34	5.66	49	56	
	2.5	250	2.6	0.33	5.47	63	73	3.2	0.38	6.34	48	56	
	3.0	300	2.9	0.36	6.05	59	68	3.5	0.43	7.10	47	54	
360° 	1.0	100	2.0	0.30	4.97	77	89	2.6	0.32	5.41	49	56	
	1.5	150	2.2	0.34	5.75	72	83	2.8	0.39	6.43	49	57	
	2.1	210	2.4	0.40	6.61	67	77	3.0	0.45	7.55	49	56	
	2.5	250	2.6	0.44	7.29	63	73	3.2	0.51	8.45	48	56	
	3.0	300	2.9	0.48	8.07	59	68	3.5	0.57	9.47	47	54	

		12A 🔧 📏						15A 🔧 📏						17A 🔧 📏					
		📏 3.7 m 📐0°- 360°📏 📏📏 28°						📏 4.6 m 📐0°- 360°📏 📏📏 28°						📏 5.2 m 📐0°- 360°📏 📏📏 28°					
📐	📏	📏	📏	📏	📏mm/hr	📏	📏	📏	📏	📏mm/hr	📏	📏	📏	📏	📏mm/hr				
45° 🔪	1.0	100	3.2	0.04	0.73	34	40	4.0	0.08	1.27	38	43	4.6	0.10	1.68	38	43		
	1.5	150	3.4	0.06	0.97	40	46	4.3	0.09	1.51	39	45	4.9	0.12	1.94	38	44		
	2.1	210	3.7	0.07	1.23	44	51	4.6	0.11	1.79	40	46	5.2	0.13	2.23	39	45		
	2.5	250	3.9	0.09	1.44	46	54	4.9	0.12	2.00	40	46	5.5	0.15	2.46	39	45		
	3.0	300	4.1	0.10	1.68	48	56	5.2	0.14	2.25	40	46	5.8	0.16	2.72	39	45		
90° 🔪	1.0	100	3.2	0.09	1.46	34	40	4.0	0.15	2.53	38	43	4.6	0.20	3.36	38	43		
	1.5	150	3.4	0.12	1.93	40	46	4.3	0.18	3.03	39	45	4.9	0.23	3.88	38	44		
	2.1	210	3.7	0.15	2.46	44	51	4.6	0.21	3.57	40	46	5.2	0.27	4.45	39	45		
	2.5	250	3.9	0.17	2.88	46	54	4.9	0.24	4.01	40	46	5.5	0.30	4.92	39	45		
	3.0	300	4.1	0.20	3.36	48	56	5.2	0.27	4.50	40	46	5.8	0.33	5.44	39	45		
120° 🔪	1.0	100	3.2	0.12	1.94	34	40	4.0	0.20	3.38	38	43	4.6	0.27	4.48	38	43		
	1.5	150	3.4	0.15	2.58	40	46	4.3	0.24	4.03	39	45	4.9	0.31	5.17	38	44		
	2.1	210	3.7	0.20	3.28	44	51	4.6	0.29	4.76	40	46	5.2	0.36	5.94	39	45		
	2.5	250	3.9	0.23	3.84	46	54	4.9	0.32	5.34	40	46	5.5	0.39	6.56	39	45		
	3.0	300	4.1	0.27	4.48	48	56	5.2	0.36	6.00	40	46	5.8	0.43	7.25	39	45		
180° 🔪	1.0	100	3.2	0.17	2.91	34	40	4.0	0.30	5.07	38	43	4.6	0.40	6.71	38	43		
	1.5	150	3.4	0.23	3.86	40	46	4.3	0.36	6.05	39	45	4.9	0.47	7.75	38	44		
	2.1	210	3.7	0.30	4.92	44	51	4.6	0.43	7.14	40	46	5.2	0.53	8.91	39	45		
	2.5	250	3.9	0.35	5.76	46	54	4.9	0.48	8.02	40	46	5.5	0.59	9.83	39	45		
	3.0	300	4.1	0.40	6.71	48	56	5.2	0.54	9.00	40	46	5.8	0.65	10.87	39	45		
240° 🔪	1.0	100	3.2	0.23	3.88	34	40	4.0	0.41	6.76	38	43	4.6	0.54	8.95	38	43		
	1.5	150	3.4	0.31	5.15	40	46	4.3	0.48	8.07	39	45	4.9	0.62	10.34	38	44		
	2.1	210	3.7	0.39	6.56	44	51	4.6	0.57	9.52	40	46	5.2	0.71	11.88	39	45		
	2.5	250	3.9	0.46	7.68	46	54	4.9	0.64	10.69	40	46	5.5	0.79	13.11	39	45		
	3.0	300	4.1	0.54	8.95	48	56	5.2	0.72	12.00	40	46	5.8	0.87	14.50	39	45		
270° 🔪	1.0	100	3.2	0.26	4.37	34	40	4.0	0.46	7.60	38	43	4.6	0.60	10.07	38	43		
	1.5	150	3.4	0.35	5.80	40	46	4.3	0.54	9.08	39	45	4.9	0.70	11.63	38	44		
	2.1	210	3.7	0.44	7.38	44	51	4.6	0.64	10.71	40	46	5.2	0.80	13.36	39	45		
	2.5	250	3.9	0.52	8.65	46	54	4.9	0.72	12.03	40	46	5.5	0.89	14.75	39	45		
	3.0	300	4.1	0.60	10.07	48	56	5.2	0.81	13.50	40	46	5.8	0.98	16.31	39	45		
360° 🔪	1.0	100	3.2	0.35	5.83	34	40	4.0	0.61	10.13	38	43	4.6	0.81	13.43	38	43		
	1.5	150	3.4	0.46	7.73	40	46	4.3	0.73	12.10	39	45	4.9	0.93	15.51	38	44		
	2.1	210	3.7	0.59	9.84	44	51	4.6	0.86	14.28	40	46	5.2	1.07	17.82	39	45		
	2.5	250	3.9	0.69	11.53	46	54	4.9	0.96	16.03	40	46	5.5	1.18	19.67	39	45		
	3.0	300	4.1	0.81	13.43	48	56	5.2	1.08	18.00	40	46	5.8	1.30	21.75	39	45		

Pro-Spray PRS302.1 bar (210 kPa)

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://api.hunterirrigation.com/cn/irrigation-product/penzui/kediaopenzui020326