

Pro

Pro

-
-
-
-

- 2.1 bar210 kPa
- Pro-Spray™ PRS30 2.1 bar210 kPa
- 2

5

1.5 m
¼, ½,
0°



						mm/hr	
	bar	kPa	m	m³/hr	l/min	■	▲
90° Q	1.0	100	1.1	0.02	0.30	60	69
	1.5	150	1.3	0.02	0.38	54	62
	2.0	200	1.5	0.03	0.45	48	55
	2.1	210	1.5	0.03	0.46	49	57
	2.5	250	1.7	0.03	0.51	42	49
120° T	1.0	100					
	1.5	150					
	2.0	200		4A			
	2.1	210					
	2.5	250					
180° H	1.0	100	1.1	0.40	0.60	60	69
	1.5	150	1.3	0.05	0.76	54	62
	2.0	200	1.5	0.05	0.90	48	53
	2.1	210	1.5	0.06	0.92	49	57
	2.5	250	1.7	0.06	1.02	42	49
360° F	1.0	100	1.1	0.07	1.2	60	69
	1.5	150	1.3	0.09	1.52	54	62
	2.0	200	1.5	0.11	1.79	48	55
	2.1	210	1.5	0.11	1.85	49	57
	2.5	250	1.7	0.12	2.04	42	49

2.4 m

¼, ⅓, ½, 1

0°

??	??	??	??	??	??	???mm/hr	
		bar	kPa	m	m³/hr	l/min	■▲
90° 	Q	1.0	100	1.7	0.04	0.62	51 59
		1.5	150	2.1	0.05	0.84	46 53
		2.0	200	2.4	0.06	1.00	42 48
		2.1	210	2.4	0.06	1.03	43 49
		2.5	250	2.7	0.07	1.13	37 43
120° 	T	1.0	100	1.7	0.05	0.83	51 59
		1.5	150	2.1	0.07	1.12	46 53
		2.0	200	2.4	0.08	1.33	42 48
		2.1	210	2.4	0.08	1.37	43 49
		2.5	250	2.7	0.09	1.51	37 33
180° 	H	1.0	100	1.7	0.08	1.33	55 64
		1.5	150	2.1	0.10	1.69	46 53
		2.0	200	2.4	0.12	1.99	42 48
		2.1	210	2.4	0.12	2.05	43 49
		2.5	250	2.7	0.14	2.27	37 43
360° 	F	1.0	100	1.7	0.16	2.67	55 64
		1.5	150	2.1	0.20	3.37	46 53
		2.0	200	2.4	0.24	3.99	42 48
		2.1	210	2.4	0.25	4.10	43 49
		2.5	250	2.7	0.27	4.54	37 43

3.0 m

¼, ⅓, ½, 1

15°

??	??	??	??	??	??	????mm/hr	
		bar	kPa	m	m³/hr	l/min	■▲
90° 	Q	1.0	100	2.4	0.07	1.08	45 52
		1.5	150	2.7	0.08	1.33	44 50
		2.0	200	3.0	0.09	1.53	41 47
		2.1	210	3.0	0.09	1.57	42 48
		2.5	250	3.3	0.10	1.71	38 44
120° 	T	1.0	100	2.4	0.09	1.44	45 52
		1.5	150	2.7	0.11	1.77	44 50
		2.0	200	3.0	0.12	2.04	41 47
		2.1	210	3.0	0.13	2.09	42 48
		2.5	250	3.3	0.21	3.43	38 44
180° 	H	1.0	100	2.4	0.13	2.17	45 52
		1.5	150	2.7	0.16	2.65	44 50
		2.0	200	3.0	0.18	3.06	41 47
		2.1	210	3.0	0.19	3.14	42 48
		2.5	250	3.3	0.21	3.43	38 44
360° 	F	1.0	100	2.4	0.26	4.33	45 52
		1.5	150	2.7	0.32	5.31	44 50
		2.0	200	3.0	0.37	6.13	41 47
		2.1	210	3.0	0.38	6.28	42 48
		2.5	250	3.3	0.41	6.85	38 44

12

3.7 m

¼, ⅓, ½, ⅔, ¾,

28°

??	??	??	??	??	??	????mm/hr	
		bar	kPa	m	m³/hr	l/min	■▲
90° 	Q	1.0	100	3.0	0.10	1.58	42 49
		1.5	150	3.4	0.12	2.00	42 48
		2.0	200	3.7	0.14	2.37	41 48
		2.1	210	3.7	0.15	2.43	43 49
		2.5	250	4.0	0.16	2.69	40 47
120° 	T	1.0	100	3.0	0.13	2.11	42 49
		1.5	150	3.4	0.16	2.67	42 48
		2.0	200	3.7	0.19	3.16	41 48
		2.1	210	3.7	0.19	3.25	43 49
		2.5	250	4.0	0.22	3.59	40 47
180° 	H	1.0	100	3.0	0.19	3.17	42 49
		1.5	150	3.4	0.24	4.01	42 48
		2.0	200	3.7	0.28	4.73	41 48
		2.1	210	3.7	0.29	4.87	43 49
		2.5	250	4.0	0.32	5.39	40 47
360° 	F	1.0	100	3.0	0.38	6.33	42 49
		1.5	150	3.4	0.48	8.01	42 48
		2.0	200	3.7	0.57	9.47	41 48
		2.1	210	3.7	0.58	9.74	43 49
		2.5	250	4.0	0.65	10.78	40 47

4.6 m

¼, ½, ¾, 1

28°

??	??	??	??	??	??	???mm/hr	
		bar	kPa	m	m³/hr	l/min	■ ▲
90° 	Q	1.0	100	3.9	0.15	2.50	39 46
		1.5	150	4.2	0.18	3.06	42 48
		2.0	200	4.6	0.21	3.54	40 46
		2.1	210	4.6	0.22	3.62	41 47
		2.5	250	4.9	0.24	3.95	40 46
120° 	T	1.0	100	3.9	0.20	3.33	39 46
		1.5	150	4.2	0.24	4.08	42 48
		2.0	200	4.6	0.28	4.71	40 46
		2.1	210	4.6	0.29	4.83	41 47
		2.5	250	4.9	0.32	5.27	40 46
180° 	H	1.0	100	3.9	0.30	5.00	39 46
		1.5	150	4.2	0.37	6.12	42 48
		2.0	200	4.6	0.42	7.07	40 46
		2.1	210	4.6	0.43	7.25	41 47
		2.5	250	4.9	0.47	7.91	40 46
360° 	F	1.0	100	3.9	0.60	10.00	39 46
		1.5	150	4.2	0.73	12.25	42 48
		2.0	200	4.6	0.85	14.14	40 46
		2.1	210	4.6	0.87	14.49	41 47
		2.5	250	4.9	0.95	15.81	40 46

5.2 m

¼, ½

28°

??	??	??	??	??	??	??	mm/hr
		bar	kPa	m	m³/hr	l/min	■▲
90° 	Q	1.0	100	4.7	0.19	3.17	34 40
		1.5	150	4.9	0.23	3.88	39 45
		2.0	200	5.2	0.27	4.48	40 46
		2.1	210	5.2	0.28	4.59	41 47
		2.5	250	5.5	0.30	5.01	40 46
120° 	T	1.0	100				
		1.5	150				
		2.0	200			17A	
		2.1	210				
		2.5	250				
180° 	H	1.0	100	4.7	0.38	6.33	34 40
		1.5	150	4.9	0.47	7.76	39 45
		2.0	200	5.2	0.54	8.96	40 46
		2.1	210	5.2	0.55	9.18	41 47
		2.5	250	5.5	0.60	10.01	40 46
360° 	F	1.0	100				
		1.5	150				
		2.0	200			17A	
		2.1	210				
		2.5	250				

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/cn/irrigation-product/penzui/pro-gudingjiaodupenzui020326>