

1" PGV

100% Hunter

- /
-
-
-
- Hunter
-

- Accu Sync™ *
- P/N 458200
- (P/N 464322)

- LS
- DC

1" (25 mm) PGV

- 0.05 3 /hr 0.7 150 l/min
- 1.5 10 bar 150 1,000 kPa
- 66°C
- 2

1½" (40 mm) 2" (50 mm) PGV

- - PGV-151 5 27 m³/hr 75 450 l/min
 - PGV-201 5 34 m³/hr 75 570 l/min
- 1.5 10 bar 150 1000 kPa
- 66°C
- 2
- 1½" 2" PGV >

1" (25 mm) PGV

1" (25 mm) PGV Bar	
m³/hr	bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23



1" (25 mm) PGV [][][][][] Bar [][][]

5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1" (25 mm) PGV [][][][][] KPa [][][]

?? [][]/[][]	???? kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

1½" (40 mm) [] 2" (50 mm) PGV [][][]

PGV [][][][][] Bar [][][]				
?? m ³ /hr	1½" (40 mm) [][][]	1½" (40 mm) [][]	2" (50 mm) [][][]	2" (50 mm) [][]
4.5	0.2	0.2	0.1	0.1
5.5	0.2	0.2	0.1	0.1
6.5	0.2	0.2	0.1	0.1
8.0	0.2	0.2	0.1	0.1
9.0	0.2	0.2	0.1	0.1
11.0	0.3	0.2	0.1	0.1
13.5	0.3	0.3	0.1	0.1
18.0	0.4	0.4	0.2	0.1
22.5	0.6	0.5	0.3	0.2
27.0	0.8	0.8	0.4	0.3
30.5			0.6	0.5
34.0			0.7	0.6
PGV [][][][][] kPa [][][]				
?? [][]	1½" (40 mm) [][][]	1½" (40 mm) [][]	2" (50 mm) [][][]	2" (50 mm) [][]
75	20	22	4	9
95	20	21	5.5	9
115	21	21	7.5	9.5
135	22	21	9	10

PGV <div></div> kPa <div></div>				
150	25	23	12	11
200	27	24	14	12
325	47	41	26	19
400	65	59	33	24
500	96	92	43	32
625			56	45
775			74	64

- 24 VAC
 - 350 mA 190mA 60 Hz
 - 370 mA 210mA 50 Hz

1"25 MMPGV <div></div>	
<div></div> 3/hr	<div></div> bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23
5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1"25 MMPGV <div></div>	
<div></div> l/hr	<div></div> kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.