

HDL-06-12-500-CV



Marke: Grünflächenbewässerung

Produktlinie: Microbewässerung

Produktmodell: HDL

SKU: HDL0612500CV

Beschreibung: Hunter Tropfrohr, druckkompensierendes Auslaufsperrventil, 2,1 l/Std., 30 cm Abstand, 150 m

Shipping Information

UPC-A: 0611698514597

Menge / Beutel: 1

Ursprung: MONTIERT IN DEN USA

Ozean-Palette: 32

Land-Palette: 28

Master-Karton: 1

Additional Information

Flowrate: 0.6 GPH

Spulenlänge: 500'

Emitterabstand: 12"

Flowrate: 0.6 GPH

Inline-Bewässerung: Drip irrigation

Online-Bewässerung: Rohre

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	206
3.0	129	210	280
4.0	167	295	399

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	389

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/de/irrigation-product/hdl/hdl-06-12-500-cv>
020326