

# Point Source Drip Emitters

Hunter Point-Source Emitters apply water slowly and directly at the base of the plant to ensure every drop is put to efficient use. They are available in three convenient styles for maximum design flexibility and top performance in any setting.

## KEY BENEFITS

- Pressure compensating
- Color-coded by flow
- Three inlet variations: ¼" barb, 10-32 thread, ½" FPT
- Coined edges for easy grip
- Self-piercing barb
- Optional diffuser cap
- Self-flushing diaphragm
- Warranty period: 2 years

## POINT SOURCE DRIP EMITTER OPERATING SPECIFICATIONS

- Pressure Compensating 20 to 50 PSI
- Filtration required: 150 mesh



Emitter Model Chart

		Model	Inlet Types	Flow (l/hr)
	Blue	HE-050-B	Self-piercing Barb	2.0
	Black	HE-10-B	Self-piercing Barb	4.0
	Red	HE-20-B	Self-piercing Barb	8.0
	Tan	HE-40-B	Self-piercing Barb	15.0
	Orange	HE-60-B	Self-piercing Barb	23.0
	Blue	HE-050-T	$\frac{10}{32}$ Thread	2.0

	Black	HE-10-T	10/32 Thread	4.0
	Red	HE-20-T	10/32 Thread	8.0
	Tan	HE-40-T	10/32 Thread	15.0
	Orange	HE-60-T	10/32 Thread	23.0
	Blue	HEB-05	1/2" Female Thread	2.0
	Blue	HEB-05-CV	1/2" Female Thread	2.0

	Black	HEB-10	½" Female Thread	4.0
	Black	HEB-10-CV	½" Female Thread	4.0
	Red	HEB-20	½" Female Thread	8.0
	Red	HEB-20-CV	½" Female Thread	8.0
	Tan	HEB-40	½" Female Thread	15.0
	Tan	HEB-40-CV	½" Female Thread	15.0

	Orange	HEB-60	½" Female Thread	23.0
	Orange	HEB-60-CV	½" Female Thread	23.0

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/micro-irrigation/point-source-drip-emitters>  
121525