



G-990-E-53-P1

Brand: Golf Irrigation

Product Model: G-990

SKU: G990E53P1

Description: G-990E Golf Rotor, full-circle opposing nozzle configuration, electric valve-in-head design, nozzle 53 installed, 6.9 bar

Shipping Information

UPC-A: 0611698150108

Ocean Pallet: 176

Land Pallet: 144

Master Carton: 4



G990

Overall Height 34 cm
 Pop-up Height 8 cm
 Flange Diameter 19 cm
 Inlet Size 1-1/2" Female ACME

| G990 Nozzle Performance Data* | | | | | | | |
|-------------------------------|----------|-----|-------------|--------------------|-------|--------------|------|
| Nozzle | Pressure | | Radius m | Flow | | Precip mm/hr | |
| | bar | kPa | | m ³ /hr | l/min | ■ | ▲ |
| 25 ● Lt. Blue | 5.5 | 551 | 22.3 | 6.93 | 115.2 | 14.0 | 16.2 |
| | 6.2 | 620 | 22.9 | 7.36 | 122.6 | 14.1 | 16.3 |
| | 6.9 | 689 | 23.2 | 7.79 | 129.8 | 14.5 | 16.8 |
| | 7.6 | 758 | 23.8 | 8.29 | 138.2 | 14.7 | 16.9 |
| 33 ● Grey | 5.5 | 551 | 23.5 | 8.25 | 137.4 | 15.0 | 17.3 |
| | 6.2 | 620 | 23.8 | 8.72 | 145.4 | 15.4 | 17.8 |
| | 6.9 | 689 | 24.4 | 9.22 | 153.7 | 15.5 | 17.9 |
| | 7.6 | 758 | 24.7 | 9.70 | 161.6 | 15.9 | 18.4 |
| 38 ● Red | 5.5 | 551 | 24.4 | 9.22 | 153.7 | 15.5 | 17.9 |
| | 6.2 | 620 | 25.0 | 9.75 | 162.4 | 15.6 | 18.0 |
| | 6.9 | 689 | 25.3 | 10.29 | 171.4 | 16.1 | 18.6 |
| | 7.6 | 758 | 25.9 | 10.84 | 180.6 | 16.1 | 18.6 |
| 43 ● Dk. Brown | 5.5 | 551 | 25.3 | 10.49 | 174.9 | 16.4 | 18.9 |
| | 6.2 | 620 | 25.6 | 11.04 | 184.0 | 16.8 | 19.4 |
| | 6.9 | 689 | 25.9 | 11.56 | 192.7 | 17.2 | 19.9 |
| | 7.6 | 758 | 26.2 | 12.13 | 202.1 | 17.7 | 20.4 |
| 48 ● Dk. Green | 5.5 | 551 | 26.2 | 11.27 | 187.8 | 16.4 | 18.9 |
| | 6.2 | 620 | 27.1 | 11.93 | 198.7 | 16.2 | 18.7 |
| | 6.9 | 689 | 27.4 | 12.45 | 207.4 | 16.5 | 19.1 |
| | 7.6 | 758 | 27.7 | 13.02 | 216.9 | 16.9 | 19.5 |
| 53 ● Dk. Blue | 5.5 | 551 | 27.1 | 12.31 | 205.2 | 17.2 | 19.8 |
| | 6.2 | 620 | 27.4 | 12.88 | 214.6 | 17.1 | 19.8 |
| | 6.9 | 689 | 28.0 | 13.45 | 224.1 | 17.1 | 19.7 |
| | 7.6 | 758 | 28.3 | 14.02 | 233.6 | 17.4 | 20.1 |
| 63 ● Black | 5.5 | 551 | 28.0 | 14.36 | 239.2 | 17.8 | 20.5 |
| | 6.2 | 620 | 28.7 | 14.97 | 249.5 | 18.3 | 21.1 |
| | 6.9 | 689 | 29.3 | 15.76 | 265.7 | 18.4 | 21.3 |
| | 7.6 | 758 | 29.6 | 16.36 | 272.5 | 18.7 | 21.6 |
| 73 ● Orange | 5.5 | 551 | 29.9 | 17.01 | 283.5 | 19.1 | 22.0 |
| | 6.2 | 620 | 29.9 | 16.38 | 272.9 | 19.1 | 22.1 |
| | 6.9 | 689 | 30.2 | 17.04 | 283.9 | 19.1 | 22.0 |
| | 7.6 | 758 | 31.1 | 18.29 | 304.7 | 18.9 | 21.8 |
| | 8.3 | 827 | 31.4 | 18.92 | 315.3 | 19.2 | 22.2 |

Note: *Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.
 ** For low angle nozzle performance, reduce radius by 15

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/g-990/g-990-e-53-p1>
 020326