



G-995-E-63-P8

Brand: Golf Irrigation

Product Model: G-995

SKU: G995E63P8

Description: G-995E Golf Rotor, full-/part-circle opposing nozzle configuration, electric valve-in-head design, nozzle 63 installed, 5.5 bar

Shipping Information

UPC-A: 0611698150344

Ocean Pallet: 176

Land Pallet: 144

Master Carton: 4



G995

Overall Height 34 cm
 Pop-up Height 8 cm
 Flange Diameter 19 cm
 Inlet Size 1-1/2" Female ACME

G995 Nozzle Performance Data*							
Nozzle	Pressure		Radius	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
25 ● Lt. Blue	5.5	550	20.1	6.70	111.7	16.6	19.1
	6.2	620	20.4	7.16	119.2	17.2	19.8
	6.9	690	20.7	7.54	125.7	17.6	20.3
	7.6	760	21.0	8.09	134.8	18.3	21.1
	8.3	830	21.0	8.52	142.0	19.3	22.2
33 ● Grey	5.5	550	20.7	8.22	137.0	19.1	22.1
	6.2	620	21.0	8.68	144.6	19.6	22.7
	6.9	690	21.3	9.18	152.9	20.2	23.3
	7.6	760	21.6	9.68	161.3	20.7	23.9
	8.3	830	21.9	10.18	169.6	21.1	24.4
38 ● Red	5.5	550	21.9	9.22	153.7	19.1	22.1
	6.2	620	22.3	9.77	162.8	19.7	22.8
	6.9	690	22.9	10.31	171.9	19.7	22.8
	7.6	760	23.2	10.81	180.2	20.1	23.3
	8.3	830	23.5	11.36	189.3	20.6	23.8
43 ● Dk. Brown	5.5	550	22.6	10.47	174.5	20.6	23.8
	6.2	620	22.6	11.02	183.6	21.7	25.0
	6.9	690	22.9	11.52	191.9	22.0	25.4
	7.6	760	23.5	12.13	202.1	22.0	25.4
	8.3	830	23.8	12.65	210.8	22.4	25.8
48 ● Dk. Green	5.5	550	23.5	11.40	190.0	20.7	23.9
	6.2	620	24.1	11.95	199.1	20.6	23.8
	6.9	690	24.7	12.52	208.6	20.5	23.7
	7.6	760	25.0	13.06	217.7	20.9	24.1
	8.3	830	25.3	13.74	229.0	21.5	24.8
53 ● Dk. Blue	5.5	550	24.7	12.47	207.8	20.5	23.6
	6.2	620	25.6	12.99	216.5	19.8	22.9
	6.9	690	26.2	13.52	225.2	19.7	22.7
	7.6	760	26.5	14.11	235.1	20.1	23.2
	8.3	830	26.8	14.63	243.8	20.3	23.5
63 ● Black	5.5	550	26.2	14.15	235.8	20.6	23.8
	6.2	620	26.8	14.88	247.9	20.7	23.9
	6.9	690	27.4	15.67	261.2	20.8	24.0
	7.6	760	27.7	16.33	272.2	21.2	24.5
	8.3	830	28.0	16.97	282.8	21.6	24.9
73 ● Orange	5.5	550	27.1	16.51	275.2	22.4	25.9
	6.2	620	27.7	17.13	285.4	22.3	25.7
	6.9	690	28.3	17.74	295.6	22.1	25.5
	7.6	760	29.0	18.38	306.2	21.9	25.3
	8.3	830	29.6	19.04	317.2	21.8	25.1
Note: *Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. ** For low angle nozzle performance, reduce radius by 15%							

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/g-995/g-995-e-63-p8>
 020326