

## HDL-06-18-250-CV



**Brand:** Landscape Irrigation

**Product Line:** Micro Irrigation

**Product Model:** HDL

**SKU:** HDL0618250CV

**Description:** Hunter Dripline, pressure-compensating check valve, 2.1 l/hr, 45 cm spacing, 75 m

### Shipping Information

**UPC-A:** 0611698514610

**Qty. / Bag:** 1

**Ocean Pallet:** 44

**Land Pallet:** 36

**Master Carton:** 1

### Additional Information

**Flow Rate:** 2.1 l/hr

**Coil Length:** 75 m

**Emitter Spacing:** 45 cm

**Flow Rate:** 2.1 l/hr

**Inline Irrigation:** Drip irrigation

**Online Irrigation:** Tubing

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	128
2.0	105	147	186
3.0	129	170	200
4.0	167	206	209

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	102
2.0	96	103	107
3.0	142	200	250
4.0	184	289	289

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/hdl/hdl-06-18-250-cv>  
020326