

I-25-04-SS-R

Brand: Landscape Irrigation

Product Line: Rotors

Product Model: I-25

SKU: I2504SSR

Description: I-25 Rotor, 10 cm, adjustable from 50° to 360°, 1" (25 mm) inlet, stainless steel riser, check valve, reclaimed ID, five nozzles included



Dimensions

Height: 200.03 mm

Pop-up Height: 10 cm

Diameter: 44.45 mm

Exposed Diameter: 44.45 mm



Operating Specifications

Arc: 50° to 360°

Operating Pressure: 2.5 to 7.0 bar; 250 to 700 kPa

Precipitation Rate: 10 mm/hr

Radius: 11.9 to 21.6 m

Flow: 0.82 to 7.24 m³/hr; 13.6 to 120.2 l/min

Shipping Information

UPC-A: 0611698156469

Qty. / Bag: 12

Origin: Made in Mexico

Ocean Pallet: 1620

Land Pallet: 1440

Master Carton: 12

I-25 Nozzle Performance Data							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
4 ● Yellow	2.5	250	11.9	0.82	13.6	12	13
	3.0	300	12.2	0.91	15.2	12	14
	3.5	350	12.5	0.98	16.4	13	15
	4.0	400	12.5	1.05	17.5	13	16
	4.5	450	12.8	1.11	18.6	14	16
	5.0	500	13.1	1.18	19.6	14	16
	5.5	550	13.4	1.24	20.7	14	16
7 ● Orange*	2.5	250	13.4	1.44	24.0	16	19
	3.0	300	14.0	1.54	25.6	16	18
	3.5	350	14.3	1.61	26.9	16	18
	4.0	400	14.3	1.68	28.0	16	19
	4.5	450	14.6	1.75	29.1	16	19
	5.0	500	14.9	1.81	30.1	16	19
	5.5	550	15.2	1.87	31.1	16	19
8 ● Lt. Brown	2.5	250	14.0	1.65	27.5	17	19
	3.0	300	14.3	1.81	30.1	18	20
	3.5	350	14.9	1.94	32.3	17	20
	4.0	400	15.2	2.05	34.2	18	20
	4.5	450	15.2	2.16	36.0	19	22
	5.0	500	15.5	2.27	37.8	19	22
	5.5	550	15.8	2.38	39.6	19	22
10 ● Lt. Green*	3.0	300	15.2	2.15	35.8	18	21
	3.5	350	15.5	2.32	38.6	19	22
	4.0	400	15.8	2.48	41.3	20	23
	4.5	450	16.2	2.63	43.9	20	23
	5.0	500	16.2	2.78	46.3	21	25
	5.5	550	16.5	2.94	48.9	22	25
	6.0	600	16.8	3.07	51.1	22	25
13 ● Lt. Blue	3.0	300	15.8	2.38	39.6	19	22
	3.5	350	16.2	2.57	42.8	20	23
	4.0	400	16.5	2.75	45.7	20	23
	4.5	450	16.5	2.91	48.5	21	25
	5.0	500	16.8	3.07	51.2	22	25
	5.5	550	16.8	3.24	54.0	23	27
	6.0	600	17.1	3.39	56.4	23	27
15 ● Grey*	3.0	300	16.8	2.86	47.7	20	24
	3.5	350	17.1	3.05	50.8	21	24
	4.0	400	17.4	3.22	53.7	21	25
	4.5	450	17.4	3.38	56.3	22	26
	5.0	500	17.4	3.53	58.8	23	27
	5.5	550	17.7	3.69	61.5	24	27
	6.0	600	18.0	3.82	63.7	24	27
18 ● Red	6.2	620	18.3	3.88	64.6	23	27
	3.0	300	17.4	3.08	51.4	20	24
	3.5	350	17.7	3.31	55.2	21	24
	4.0	400	18.0	3.52	58.7	22	25
	4.5	450	18.3	3.72	62.0	22	26
	5.0	500	18.9	3.91	65.2	22	25
	5.5	550	19.2	4.11	68.5	22	26
20 ● Dk. Brown*	6.0	600	19.5	4.28	71.4	23	26
	6.2	620	19.5	4.35	72.5	23	26
	3.5	350	18.0	3.72	62.1	23	27
	4.0	400	18.6	3.97	66.2	23	27
	4.5	450	18.9	4.2	70.1	24	27
	5.0	500	19.2	4.42	73.7	24	28
	5.5	550	19.5	4.66	77.7	25	28
23 ● Dk. Green	6.0	600	19.8	4.86	81.0	25	29
	6.5	650	20.1	5.05	84.2	25	29
	6.9	690	20.4	5.21	86.8	25	29
	3.5	350	18.6	4.56	76.0	26	30
	4.0	400	19.2	4.88	81.3	26	31
	4.5	450	19.5	5.18	86.3	27	31
	5.0	500	19.8	5.47	91.1	28	32
23 ● Dk. Green	5.5	550	20.1	5.78	96.3	29	33
	6.0	600	20.1	6.04	100.6	30	34
	6.5	650	20.4	6.29	104.8	30	35

6.9	690	20.7	6.5	108.3	30	35	
25 ● Dk. Blue*	3.5	350	19.2	4.86	80.9	26	30
	4.0	400	19.8	5.23	87.1	27	31
	4.5	450	20.1	5.58	93.1	28	32
	5.0	500	20.4	5.92	98.7	28	33
	5.5	550	21.0	6.29	104.9	28	33
	6.0	600	21.0	6.6	110.0	30	34
	6.5	650	21.3	6.9	115.1	30	35
28 ● Black	6.9	690	21.6	7.15	119.2	31	35
	3.5	350	18.3	5.31	88.5	32	37
	4.0	400	19.2	5.63	93.8	31	35
	4.5	450	20.1	5.93	98.8	29	34
	5.0	500	20.7	6.21	103.5	29	33
	5.5	550	21.3	6.52	108.6	29	33
	6.0	600	21.3	6.77	112.8	30	34
6.5	650	21.6	7.01	116.9	30	35	
6.9	690	21.6	7.21	120.2	31	36	

* 5 standard nozzles included with each sprinkler.

Notes:

All precipitation rates calculated for 180 degree operation. For the precipitation rate for a 360 degree sprinkler, divide by 2.

I-25 High Speed Nozzle Performance Data							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
4 ● Yellow	2.5	250	11.0	0.81	13.6	14	16
	3.0	300	11.3	0.91	15.1	14	16
	3.5	350	11.6	0.99	16.4	15	17
	4.0	400	11.6	1.06	17.6	16	18
	4.5	450	11.6	1.13	18.8	17	19
	5.0	500	11.9	1.19	19.9	17	19
	5.5	550	11.9	1.26	21.1	18	21
7 ● Orange*	2.5	250	11.9	1.32	22.0	19	22
	3.0	300	12.2	1.46	24.3	20	23
	3.5	350	12.5	1.57	26.2	20	23
	4.0	400	12.8	1.68	27.9	20	24
	4.5	450	13.1	1.78	29.6	21	24
	5.0	500	13.4	1.87	31.1	21	24
	5.5	550	13.4	1.97	32.8	22	25
8 ● Lt. Brown	2.5	250	12.5	1.54	25.7	20	23
	3.0	300	12.8	1.72	28.6	21	24
	3.5	350	13.1	1.86	31.0	22	25
	4.0	400	13.4	2.00	33.3	22	26
	4.5	450	13.4	2.13	35.4	24	27
	5.0	500	13.7	2.25	37.5	24	28
	5.5	550	13.7	2.38	39.7	25	29
10 ● Lt. Green*	3.0	300	13.7	2.15	35.8	23	26
	3.5	350	14.0	2.32	38.6	24	27
	4.0	400	14.3	2.48	41.3	24	28
	4.5	450	14.6	2.63	43.9	25	28
	5.0	500	14.9	2.78	46.3	25	29
	5.5	550	15.2	2.94	48.9	25	29
	6.0	600	15.2	3.07	51.1	26	31
13 ● Lt. Blue	3.0	300	14.3	2.38	39.6	23	27
	3.5	350	14.6	2.57	42.8	24	28
	4.0	400	14.9	2.75	45.7	25	28
	4.5	450	15.2	2.91	48.5	25	29
	5.0	500	15.5	3.07	51.2	25	29
	5.5	550	15.5	3.24	54.0	27	31
	6.0	600	15.5	3.39	56.4	28	32
15 ● Grey*	3.0	300	14.6	2.86	47.7	27	31
	3.5	350	14.9	3.05	50.8	27	32
	4.0	400	15.2	3.22	53.7	28	32
	4.5	450	15.5	3.38	56.3	28	32
	5.0	500	16.2	3.53	58.8	27	31
	5.5	550	16.5	3.69	61.5	27	31
	6.0	600	16.5	3.82	63.7	28	33
18 ● Red	6.2	620	16.5	3.88	64.6	29	33
	3.0	300	14.9	3.08	51.4	28	32
	3.5	350	15.2	3.31	55.2	29	33
	4.0	400	15.5	3.52	58.7	29	34
	4.5	450	16.2	3.72	62.0	29	33
	5.0	500	16.8	3.91	65.2	28	32
	5.5	550	17.4	4.11	68.5	27	31
20 ● Dk. Brown*	6.0	600	17.4	4.28	71.4	28	33
	6.2	620	17.4	4.35	72.5	29	33
	3.5	350	15.5	3.72	62.1	31	36
	4.0	400	16.2	3.97	66.2	30	35
	4.5	450	16.5	4.20	70.1	31	36
	5.0	500	17.1	4.42	73.7	30	35
	5.5	550	17.7	4.66	77.7	30	34
23 ● Dk. Green	6.0	600	17.7	4.86	81.0	31	36
	6.5	650	18.0	5.05	84.2	31	36
	6.9	690	18.0	5.21	86.8	32	37
	3.5	350	16.5	4.56	76.0	34	39
	4.0	400	17.1	4.88	81.3	33	39
	4.5	450	17.4	5.18	86.3	34	40
	5.0	500	17.7	5.47	91.1	35	40
25 ● Dk. Green	5.5	550	18.3	5.78	96.3	35	40
	6.0	600	18.3	6.04	100.6	36	42
	6.5	650	18.6	6.29	104.8	36	42
	6.9	690	18.6	6.50	108.3	38	43
	3.5	350	17.1	4.86	80.9	33	38
25 ● Dk. Green	4.0	400	17.7	5.23	87.1	33	39
	4.5	450	18.3	5.58	93.1	33	39

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/i-25/i-25-04-ss-r020326>