



## I-90-36V-B

**Brand:** Landscape Irrigation

**Product Line:** Rotors

**Product Model:** I-90

**SKU:** I9036VB

**Description:** I-90 Rotor, 8 cm, full-circle, 1½" (40 mm) BSP inlet, check valve, opposing nozzles, with eight nozzles included (25–73)

### Dimensions

**Height:** 279.40 mm

**Pop-up Height:** 7.5 cm

**Diameter:** 88.90 mm

**Exposed Diameter:** 88.90 mm



### Operating Specifications

**Arc:** 0° to 360°

**Operating Pressure:** 5.5 to 8.0 bar; 550 to 800 kPa

**Precipitation Rate:** 19 mm/hr

**Radius:** 22.3 to 31.4 m

**Flow:** 6.93 to 18.92 m<sup>3</sup>/hr; 115.5 to 315.3 l/min

### Shipping Information

**UPC-A:** 0611698126479

**Ocean Pallet:** 336

**Land Pallet:** 240

**Master Carton:** 6

I-90-ADV Nozzle Performance Data							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
25 Lt. Blue	5.5	550	20.1	6.70	111.7	33.1	38.2
	6.0	600	20.4	7.16	119.2	34.3	39.6
	7.0	700	20.7	7.54	125.7	35.1	40.5
	7.5	750	21.0	8.09	134.8	36.6	42.2
33 Grey	5.5	550	20.7	8.22	137.0	38.3	44.2
	6.0	600	21.0	8.68	144.6	39.2	45.3
	7.0	700	21.3	9.18	152.9	40.3	46.6
	7.5	750	21.6	9.68	161.3	41.3	47.7
38 Red	5.5	550	21.9	9.22	153.7	38.3	44.2
	6.0	600	22.3	9.77	162.8	39.5	45.6
	7.0	700	22.9	10.31	171.9	39.5	45.6
	7.5	750	23.2	10.81	180.2	40.3	46.5
43 Dk. Brown	5.5	550	22.6	10.47	174.5	41.2	47.5
	6.0	600	22.6	11.02	183.6	43.3	50.0
	7.0	700	22.9	11.52	191.9	44.1	50.9
	7.5	750	23.5	12.13	202.1	44.0	50.9
48 Dk. Green	5.5	550	23.5	11.40	190.0	41.4	47.8
	6.0	600	24.1	11.95	199.1	41.2	47.6
	7.0	700	24.7	12.52	208.6	41.1	47.4
53 Dk. Blue*	5.5	550	24.7	12.47	207.8	40.9	47.2
	6.0	600	25.6	12.99	216.5	39.6	45.8
	7.0	700	26.2	13.52	225.2	39.3	45.4
63 Black	5.5	550	26.5	14.11	235.1	40.1	46.3
	6.0	600	26.8	14.63	243.8	40.7	47.0
	7.0	700	27.4	15.67	261.2	41.7	48.1
	8.0	800	28.0	16.97	282.8	43.2	49.8
73 Orange	5.5	550	26.2	14.15	235.8	41.2	47.6
	6.0	600	26.8	14.88	247.9	41.4	47.8
	7.0	700	27.4	15.67	261.2	41.7	48.1
	8.0	800	28.0	16.97	282.8	43.2	49.8
73 Orange	5.5	550	27.1	16.51	275.2	44.9	51.8
	6.0	600	27.7	17.13	285.4	44.5	51.4
	7.0	700	28.3	17.74	295.6	44.2	51.0
	8.0	800	29.6	19.04	317.2	43.5	50.3

\* Factory-installed nozzle

**Notes:**  
Precipitation rates for ADV models are calculated for 180-degree operation. All triangular rates are equilateral. For low angle nozzle performance, reduce radius by 15%. Complies to ASAE standard.

I-90-36V Nozzle Performance Data							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
25 Lt. Blue	5.5	550	22.3	6.93	115.5	14.0	16.2
	6.0	600	22.9	7.36	122.6	14.1	16.3
	7.0	700	23.2	7.79	129.8	14.5	16.8
	7.5	750	23.8	8.29	138.2	14.7	16.9
33 Grey	5.5	550	23.5	8.25	137.4	15.0	17.3
	6.0	600	23.8	8.72	145.4	15.4	17.8
	7.0	700	24.4	9.22	153.7	15.5	17.9
	7.5	750	24.7	9.70	161.6	15.9	18.4
38 Red	5.5	550	24.4	9.22	153.7	15.5	17.9
	6.0	600	25.0	9.75	162.4	15.6	18.0
	7.0	700	25.3	10.29	171.5	16.1	18.6
	7.5	750	25.9	10.84	180.6	16.1	18.6
43 Dk. Brown	5.5	550	25.3	10.49	174.9	16.4	18.9
	6.0	600	25.6	11.04	184.0	16.8	19.4
	7.0	700	25.9	11.56	192.7	17.2	19.9
	7.5	750	26.2	12.13	202.1	17.7	20.4
48 Dk. Green	5.5	550	26.2	11.27	187.8	16.4	18.9
	6.0	600	27.1	11.93	198.7	16.2	18.7
	7.0	700	27.4	12.45	207.4	16.5	19.1
	7.5	750	27.7	13.02	216.9	16.9	19.5
53 Dk. Blue*	5.5	550	27.1	12.31	205.2	16.7	19.3
	6.0	600	27.4	12.88	214.6	17.1	19.8
	7.0	700	28.0	13.45	224.1	17.1	19.7
	7.5	750	28.3	14.02	233.6	17.4	20.1
63 Black	8.0	800	28.7	14.58	243.0	17.8	20.5
	5.5	550	28.0	14.36	239.2	18.3	21.1
	6.0	600	28.7	14.97	249.5	18.2	21.1
	7.0	700	29.3	15.76	262.7	18.4	21.3
73 Orange	7.5	750	29.6	16.36	272.5	18.7	21.6
	8.0	800	29.9	17.01	283.5	19.1	22.0
	5.5	550	29.3	16.38	272.9	19.1	22.1
	6.0	600	29.9	17.04	283.9	19.1	22.0
73 Orange	7.0	700	30.2	17.67	294.5	19.4	22.4
	7.5	750	31.1	18.29	304.7	18.9	21.8
	8.0	800	31.4	18.92	315.3	19.2	22.2

\* Factory installed nozzle.

**Notes:**  
Precipitation rates for 36V models are calculated for 360-degree operation. All triangular rates are equilateral. For low angle nozzle performance, reduce radius by 15%. Complies to ASAE standard.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/i-90/i-90-36v-b020326>