



PSU-04-8A

Brand: Landscape Irrigation

Product Line: Spray Bodies

Product Model: PS Ultra

SKU: PSU048A

Description: PS Ultra Sprinkler Body, 10 cm slim pop-up with preinstalled nozzle, 2.5 m radius, adjustable arc (0° to 360°), ½" inlet, and large inlet filter screen

Dimensions

Height: 184.15 mm

Pop-up Height: 10 cm

Diameter: 31.75 mm

Exposed Diameter: 31.75 mm



Shipping Information

UPC-A: 0611698379066

Qty. / Bag: 100

Ocean Pallet: 9000

Land Pallet: 7200








Master Carton: 100

Additional Information

Radius: 2.5 m

PRO ADJUSTABLE NOZZLE PERFORMANCE DATA

4A & 6A

		Nozzle 4 ● Lt. Green 1.2 m radius Adjustable from 0° to 360 Trajectory 0°						Nozzle 6 ● Lt. Blue 1.8 m radius Adjustable from 0° to 360 Trajectory 0°					
Arc	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		
	bar	kPa		m ³ /hr	l/min	■	▲		m ³ /hr	l/min	■	▲	
45° 	1.0	100	0.9	0.02	0.31	187	216	1.5	0.03	0.54	117	136	
	1.5	150	1.0	0.02	0.39	178	206	1.6	0.04	0.60	108	124	
	2.1	210	1.2	0.03	0.48	167	193	1.8	0.04	0.65	98	114	
	2.5	250	1.3	0.03	0.56	158	183	1.9	0.04	0.70	92	106	
	3.0	300	1.4	0.04	0.64	149	172	2.1	0.05	0.75	86	99	
90° 	1.0	100	0.9	0.04	0.72	213	246	1.5	0.06	1.08	116	134	
	1.5	150	1.0	0.05	0.76	182	210	1.6	0.07	1.21	109	126	
	2.1	210	1.2	0.05	0.83	139	160	1.8	0.08	1.35	102	118	
	2.5	250	1.3	0.05	0.91	129	149	1.9	0.09	1.47	97	112	
	3.0	300	1.4	0.06	0.95	116	134	2.1	0.10	1.61	92	106	
120° 	1.0	100	0.9	0.06	0.97	221	255	1.5	0.08	1.26	102	118	
	1.5	150	1.0	0.07	1.10	188	217	1.6	0.09	1.43	97	112	
	2.1	210	1.2	0.07	1.25	162	187	1.8	0.10	1.61	91	105	
	2.5	250	1.3	0.08	1.36	146	168	1.9	0.11	1.76	87	100	
	3.0	300	1.4	0.09	1.49	131	151	2.1	0.12	1.93	82	95	
180° 	1.0	100	0.9	0.07	1.18	178	206	1.5	0.10	1.70	92	106	
	1.5	150	1.0	0.08	1.38	157	181	1.6	0.12	1.96	88	102	
	2.1	210	1.2	0.10	1.60	139	160	1.8	0.13	2.24	84	97	
	2.5	250	1.3	0.11	1.78	127	146	1.9	0.15	2.47	81	94	
	3.0	300	1.4	0.12	1.98	115	133	2.1	0.16	2.72	78	90	
240° 	1.0	100	0.9	0.12	1.94	220	254	1.5	0.15	2.44	99	114	
	1.5	150	1.0	0.13	2.24	192	221	1.6	0.17	2.83	96	111	
	2.1	210	1.2	0.16	2.59	168	194	1.8	0.20	3.28	92	107	
	2.5	250	1.3	0.17	2.86	153	177	1.9	0.22	3.63	89	103	
	3.0	300	1.4	0.19	3.17	139	160	2.1	0.24	4.03	86	99	
270° 	1.0	100	0.9	0.13	2.09	211	244	1.5	0.18	3.08	111	128	
	1.5	150	1.0	0.14	2.40	183	211	1.6	0.21	3.52	106	122	
	2.1	210	1.2	0.16	2.75	159	183	1.8	0.24	4.02	101	116	
	2.5	250	1.3	0.18	3.02	144	166	1.9	0.27	4.42	97	112	
	3.0	300	1.4	0.20	3.33	130	150	2.1	0.29	4.87	92	107	
360° 	1.0	100	0.9	0.14	2.26	171	197	1.5	0.21	3.57	96	111	
	1.5	150	1.0	0.16	2.60	148	171	1.6	0.24	4.07	92	106	
	2.1	210	1.2	0.18	2.98	129	149	1.8	0.28	4.62	87	100	
	2.5	250	1.3	0.20	3.29	117	135	1.9	0.30	5.06	83	96	
	3.0	300	1.4	0.22	3.63	106	122	2.1	0.33	5.56	79	92	

8A & 10A

		Nozzle ● Brown 2.4 m radius Adjustable from 0° to 360° Trajectory 15°						Nozzle ●A Red 3.0 m radius Adjustable from 0° to 360° Trajectory 15°					
Arc	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		
	bar	kPa		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲	
45°	1.0	100	2.0	0.04	0.62	77	89	2.6	0.04	0.68	49	56	
	1.5	150	2.2	0.04	0.72	72	83	2.8	0.05	0.80	49	57	
	2.1	210	2.4	0.05	0.83	67	77	3.0	0.06	0.94	49	56	
	2.5	250	2.6	0.05	0.91	63	73	3.2	0.06	1.06	48	56	
	3.0	300	2.9	0.06	1.01	59	68	3.5	0.07	1.18	47	54	
90°	1.0	100	2.0	0.07	1.24	77	89	2.6	0.08	1.35	49	56	
	1.5	150	2.2	0.09	1.44	72	83	2.8	0.10	1.61	49	57	
	2.1	210	2.4	0.10	1.65	67	77	3.0	0.11	1.89	49	56	
	2.5	250	2.6	0.11	1.82	63	73	3.2	0.13	2.11	48	56	
	3.0	300	2.9	0.12	2.02	59	68	3.5	0.14	2.37	47	54	
120°	1.0	100	2.0	0.10	1.66	77	89	2.6	0.11	1.80	49	56	
	1.5	150	2.2	0.11	1.92	72	83	2.8	0.13	2.14	49	57	
	2.1	210	2.4	0.13	2.20	67	77	3.0	0.15	2.52	49	56	
	2.5	250	2.6	0.15	2.43	63	73	3.2	0.17	2.82	48	56	
	3.0	300	2.9	0.16	2.69	59	68	3.5	0.19	3.16	47	54	
180°	1.0	100	2.0	0.15	2.49	77	89	2.6	0.16	2.71	49	56	
	1.5	150	2.2	0.17	2.87	72	83	2.8	0.19	3.21	49	57	
	2.1	210	2.4	0.20	3.30	67	77	3.0	0.23	3.78	49	56	
	2.5	250	2.6	0.22	3.65	63	73	3.2	0.25	4.23	48	56	
	3.0	300	2.9	0.24	4.03	59	68	3.5	0.28	4.73	47	54	
240°	1.0	100	2.0	0.20	3.32	77	89	2.6	0.22	3.61	49	56	
	1.5	150	2.2	0.23	3.83	72	83	2.8	0.26	4.28	49	57	
	2.1	210	2.4	0.26	4.40	67	77	3.0	0.30	5.03	49	56	
	2.5	250	2.6	0.29	4.86	63	73	3.2	0.34	5.64	48	56	
	3.0	300	2.9	0.32	5.38	59	68	3.5	0.38	6.31	47	54	
270°	1.0	100	2.0	0.22	3.73	77	89	2.6	0.24	4.06	49	56	
	1.5	150	2.2	0.26	4.31	72	83	2.8	0.29	4.82	49	57	
	2.1	210	2.4	0.30	4.95	67	77	3.0	0.34	5.66	49	56	
	2.5	250	2.6	0.33	5.47	63	73	3.2	0.38	6.34	48	56	
	3.0	300	2.9	0.36	6.05	59	68	3.5	0.43	7.10	47	54	
360°	1.0	100	2.0	0.30	4.97	77	89	2.6	0.32	5.41	49	56	
	1.5	150	2.2	0.34	5.75	72	83	2.8	0.39	6.43	49	57	
	2.1	210	2.4	0.40	6.61	67	77	3.0	0.45	7.55	49	56	
	2.5	250	2.6	0.44	7.29	63	73	3.2	0.51	8.45	48	56	
	3.0	300	2.9	0.48	8.07	59	68	3.5	0.57	9.47	47	54	

Strip Pattern Nozzles Performance Data				
Nozzle Blue				
Arc	Pressure		Width x Length	
	bar	kPa	m	mm
SS-530	1.0	100	1.2 x 8.5	
	1.5	150	1.5 x 9.0	
	2.0	200	1.5 x 9.0	
Side Strip	2.1	210	1.5 x 9.0	
	2.5	250	1.5 x 9.0	

Notes = Recommended pressure

12A, 15A & 17A

		Nozzle ●A Green 3.7 m radius Adjustable from 0° to 360° Trajectory 28°						Nozzle ●A Black 4.6 m radius Adjustable from 0° to 360° Trajectory 28°						Nozzle ●A Grey 5.2 m radius Adjustable from 0° to 360° Trajectory 28°					
Arc	Pressure		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr		Radius m	Flow		Precip mm/hr			
	bar	kPa		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲		m³/hr	l/min	■	▲		
45°	1.0	100	3.2	0.04	0.73	34	40	4.0	0.08	1.27	38	43	4.6	0.10	1.68	38	43		
	1.5	150	3.4	0.06	0.97	40	46	4.3	0.09	1.51	39	45	4.9	0.12	1.94	38	44		
	2.1	210	3.7	0.07	1.23	44	51	4.6	0.11	1.79	40	46	5.2	0.13	2.23	39	45		
	2.5	250	3.9	0.09	1.44	46	54	4.9	0.12	2.00	40	46	5.5	0.15	2.46	39	45		
	3.0	300	4.1	0.10	1.68	48	56	5.2	0.14	2.25	40	46	5.8	0.16	2.72	39	45		
90°	1.0	100	3.2	0.09	1.46	34	40	4.0	0.15	2.53	38	43	4.6	0.20	3.36	38	43		
	1.5	150	3.4	0.12	1.93	40	46	4.3	0.18	3.03	39	45	4.9	0.23	3.88	38	44		
	2.1	210	3.7	0.15	2.46	44	51	4.6	0.21	3.57	40	46	5.2	0.27	4.45	39	45		
	2.5	250	3.9	0.17	2.88	46	54	4.9	0.24	4.01	40	46	5.5	0.30	4.92	39	45		
	3.0	300	4.1	0.20	3.36	48	56	5.2	0.27	4.50	40	46	5.8	0.33	5.44	39	45		
120°	1.0	100	3.2	0.12	1.94	34	40	4.0	0.20	3.38	38	43	4.6	0.27	4.48	38	43		

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/ps-ultra/psu-04-8a020326>