



5Q

Brand: Landscape Irrigation

Product Line: Nozzles

Product Model: Pro Fixed Nozzles

SKU: 5Q

Description: Pro Fixed Nozzle, 1.5 m radius, 90°, fixed arc, female thread

Shipping Information

UPC-A: 0611698155479

Qty. / Bag: 25/250

Ocean Pallet: 52000

Land Pallet: 40000

Master Carton: 250

Additional Information

Arc: 90°





Precipitation Rate: Approx 40 mm/hr

Radius: 1.5 m

PRO-SPRAY FIXED ARC NOZZLES PERFORMANCE DATA





Nozzle 8 Blue

Radius: 1.5 m
Fixed ¼, ½, Full
Trajectory 0°

Arc	Position	Pressure		Radius m	Flow		Precip mm/hr		
		bar	kPa		m ³ /hr	l/min	■	▲	
90° 	Q	1.0	100	1.1	0.02	0.30	60	69	
		1.5	150	1.3	0.02	0.38	54	62	
		2.0	200	1.5	0.03	0.45	48	55	
		2.1	210	1.5	0.03	0.46	49	57	
		2.5	250	1.7	0.03	0.51	42	49	
120° 	T	1.0	100						
		1.5	150						
		2.0	200						
		2.1	210						
Use Hunter 4A Nozzle									
180° 	H	1.0	100	1.1	0.40	0.60	60	69	
		1.5	150	1.3	0.05	0.76	54	62	
		2.0	200	1.5	0.05	0.90	48	53	
		2.1	210	1.5	0.06	0.92	49	57	
360° 	F	2.5	250	1.7	0.06	1.02	42	49	
		1.0	100	1.1	0.07	1.2	60	69	
		1.5	150	1.3	0.09	1.52	54	62	
		2.0	200	1.5	0.11	1.79	48	55	
		2.1	210	1.5	0.11	1.85	49	57	
		2.5	250	1.7	0.12	2.04	42	49	

Nozzle 8 Brown





Radius: 2.4 m
Fixed ¼, ½, Full
Trajectory 15°

Arc	Position	Pressure		Radius m	Flow		Precip mm/hr	
		bar	kPa		m ³ /hr	l/min	■	▲
90° 	Q	1.0	100	1.7	0.04	0.62	51	59
		1.5	150	2.1	0.05	0.84	46	53
		2.0	200	2.4	0.06	1.00	42	48
		2.1	210	2.4	0.06	1.03	43	49
		2.5	250	2.7	0.07	1.13	37	43
120° 	T	1.0	100	1.7	0.05	0.83	51	59
		1.5	150	2.1	0.07	1.12	46	53
		2.0	200	2.4	0.08	1.33	42	48
		2.1	210	2.4	0.08	1.37	43	49
180° 	H	2.5	250	2.7	0.09	1.51	37	33
		1.0	100	1.7	0.08	1.33	55	64
		1.5	150	2.1	0.10	1.69	46	53
		2.0	200	2.4	0.12	1.99	42	48
		2.1	210	2.4	0.12	2.05	43	49
360° 	F	2.5	250	2.7	0.14	2.27	37	43
		1.0	100	1.7	0.16	2.67	55	64
		1.5	150	2.1	0.20	3.37	46	53
		2.0	200	2.4	0.24	3.99	42	48
		2.1	210	2.4	0.25	4.10	43	49
		2.5	250	2.7	0.27	4.54	37	43

Nozzle 10 Red





Radius: 3.0 m
Fixed ¼, ½, Full
Trajectory 15°

Arc	Position	Pressure		Radius m	Flow		Precip mm/hr	
		bar	kPa		m ³ /hr	l/min	■	▲

Arc	Position	Pressure	Radius	Flow	Precip mm/hr			
		bar	kPa	m ³ /hr	l/min			
90° 	Q	1.0	100	2.4	0.07	1.08	45	52
		1.5	150	2.7	0.08	1.33	44	50
		2.0	200	3.0	0.09	1.53	41	47
		2.1	210	3.0	0.09	1.57	42	48
		2.5	250	3.3	0.10	1.71	38	44
120° 	T	1.0	100	2.4	0.09	1.44	45	52
		1.5	150	2.7	0.11	1.77	44	50
		2.0	200	3.0	0.12	2.04	41	47
		2.1	210	3.0	0.13	2.09	42	48
		2.5	250	3.3	0.21	3.43	38	44
180° 	H	1.0	100	2.4	0.13	2.17	45	52
		1.5	150	2.7	0.16	2.65	44	50
		2.0	200	3.0	0.18	3.06	41	47
		2.1	210	3.0	0.19	3.14	42	48
		2.5	250	3.3	0.21	3.43	38	44
360° 	F	1.0	100	2.4	0.26	4.33	45	52
		1.5	150	2.7	0.32	5.31	44	50
		2.0	200	3.0	0.37	6.13	41	47
		2.1	210	3.0	0.38	6.28	42	48
		2.5	250	3.3	0.41	6.85	38	44





Nozzle ● Green

Radius: 3.7 m
Fixed ¼, ½, ¾, Full
Trajectory 28°

Arc	Position	Pressure	Radius	Flow	Precip mm/hr			
		bar	kPa	m	m ³ /hr	l/min	■	▲
90° 	Q	1.0	100	3.0	0.10	1.58	42	49
		1.5	150	3.4	0.12	2.00	42	48
		2.0	200	3.7	0.14	2.37	41	48
		2.1	210	3.7	0.15	2.43	43	49
		2.5	250	4.0	0.16	2.69	40	47
120° 	T	1.0	100	3.0	0.13	2.11	42	49
		1.5	150	3.4	0.16	2.67	42	48
		2.0	200	3.7	0.19	3.16	41	48
		2.1	210	3.7	0.19	3.25	43	49
		2.5	250	4.0	0.22	3.59	40	47
180° 	H	1.0	100	3.0	0.19	3.17	42	49
		1.5	150	3.4	0.24	4.01	42	48
		2.0	200	3.7	0.28	4.73	41	48
		2.1	210	3.7	0.29	4.87	43	49
		2.5	250	4.0	0.32	5.39	40	47
360° 	F	1.0	100	3.0	0.38	6.33	42	49
		1.5	150	3.4	0.48	8.01	42	48
		2.0	200	3.7	0.57	9.47	41	48
		2.1	210	3.7	0.58	9.74	43	49
		2.5	250	4.0	0.65	10.78	40	47

Nozzle ● Black

Radius: 4.6 m
Fixed ¼, ½, ¾, Full
Trajectory 28°

Arc	Position	Pressure	Radius	Flow	Precip mm/hr			
		bar	kPa	m	m ³ /hr	l/min	■	▲
90° 	Q	1.0	100	3.9	0.15	2.50	39	46
		1.5	150	4.2	0.18	3.06	42	48
		2.0	200	4.6	0.21	3.54	40	46
		2.1	210	4.6	0.22	3.62	41	47
		2.5	250	4.9	0.24	3.95	40	46
120° 	T	1.0	100	3.9	0.20	3.33	39	46
		1.5	150	4.2	0.24	4.08	42	48
		2.0	200	4.6	0.28	4.71	40	46
		2.1	210	4.6	0.29	4.83	41	47
		2.5	250	4.9	0.32	5.27	40	46
180° 	H	1.0	100	3.9	0.30	5.00	39	46
		1.5	150	4.2	0.37	6.12	42	48
		2.0	200	4.6	0.42	7.07	40	46
		2.1	210	4.6	0.43	7.25	41	47
		2.5	250	4.9	0.47	7.91	40	46
360° 	F	1.0	100	3.9	0.60	10.00	39	46
		1.5	150	4.2	0.73	12.25	42	48
		2.0	200	4.6	0.85	14.14	40	46
		2.1	210	4.6	0.87	14.49	41	47
		2.5	250	4.9	0.95	15.81	40	46

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/pro-fixed-nozzles/5q020326>