

PGV Jar-Top

These versatile and robust valves offer simple serviceability.

KEY BENEFITS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Jar-top models provide easy access without tools
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximises efficiency and prolongs the life of the system

User-Installed Options

- Accu Sync™ pressure regulation at the valve*
- DC-latching solenoid for battery-powered controllers (P/N 458200)
- Solenoid conduit cover (P/N 464322)

Factory-Installed Options

- LS: Valve without solenoid
- DC: DC-latching solenoid for battery-powered controllers

Operating Specifications

- Flow: 0.05 to 9 m³ /hr; 0.7 to 150 l/min
- Recommended pressure range: 1.5 to 10 bar; 150 to 1,000 kPa
- Temperature rating: 66°C
- Warranty period: 2 years

Solenoid Specifications

- 24 VAC solenoid
 - 350 mA inrush, 190 mA holding, 60 Hz
 - 370 mA inrush, 210 mA holding, 50 Hz



1" (25 MM) PGV VALVE

Flow m ³ /hr	Pressure Loss bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23
5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1" (25 MM) PGV VALVE

Flow l/min	Pressure Loss kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/valves/pgv-jar-top>
020326