

MP-820-360



Product Line: MP Rotator Nozzles


Product Model: MP Rotator® MP800 Nozzle

SKU: MP820360

Description: MP Rotator Nozzle, 20 mm/hr precipitation rate, 4.6 m to 7.3 m radius, 360° arc, female thread, grey and red

Dimensions

Diameter: 25.40 mm



Operating Specifications

Arc: 360°

Operating Pressure: 2.8 bar; 280 kPa

Precipitation Rate: 20 mm/hr

Radius: 1.8 to 7.3 m

Flow: 0.77 to 1.03 m³/hr; 12.85 to 17.13 l/min

Shipping Information

UPC-A: 196055004824

Origin: MADEINUSA

Master Carton: 200

Additional Information

Arc: 360°

Radius: 4.6 m – 7.3 m

MP ROTATOR PERFORMANCE DATA - Metric*

MP-800SR

Radius: 1.8 to 3.5 m
Adjustable Arc
Orange and Grey: 90° to 210°
Lime Green and Grey: 360°

Arc	Pressure		Min Radius			Max Radius			Precip mm/hr	
			Radius		Flow	Radius		Flow		
	bar	kPa	m	m ³ /hr	l/min	m	m ³ /hr	l/min	■	▲
90° 	2.1	210	1.8	0.03	0.49	2.6	0.04	0.61	22	25
	2.5	250	2.1	0.03	0.55	2.9	0.04	0.72	21	24
	2.8	280	2.4	0.04	0.61	3.1	0.05	0.87	21	24
	3.0	300	2.4	0.04	0.68	3.4	0.06	0.95	20	23
	3.5	350	2.7	0.04	0.72	3.5	0.06	1.02	20	23
180° 	3.8	380	3.0	0.05	0.76	3.5	0.06	1.06	20	23
	2.1	210	1.8	0.06	0.98	2.6	0.07	1.21	22	25
	2.5	250	2.1	0.07	1.10	2.8	0.08	1.40	21	24
	2.8	280	2.4	0.07	1.21	3.0	0.10	1.59	21	24
	3.0	300	2.4	0.08	1.36	3.3	0.10	1.74	19	22
210° 	3.5	350	2.7	0.09	1.44	3.4	0.11	1.82	19	22
	3.8	380	3.0	0.09	1.51	3.5	0.11	1.89	18	21
	2.1	210	1.8	0.07	1.15	2.6	0.08	1.40	22	25
	2.5	250	2.1	0.08	1.28	2.8	0.10	1.67	22	25
	2.8	280	2.4	0.08	1.41	3.0	0.11	1.85	21	24
360° 	3.0	300	2.4	0.10	1.59	3.2	0.12	2.01	20	23
	3.5	350	2.7	0.10	1.68	3.4	0.13	2.12	19	22
	3.8	380	3.0	0.11	1.77	3.5	0.13	2.20	18	21
	2.1	210	1.8	0.11	1.78	2.6	0.14	2.38	22	25
	2.5	250	2.1	0.12	1.97	2.8	0.16	2.65	20	23
	2.8	280	2.4	0.13	2.12	3.0	0.18	2.95	20	23
	3.0	300	2.4	0.13	2.23	3.1	0.19	3.22	20	23
	3.5	350	2.7	0.14	2.38	3.3	0.20	3.33	19	21
	3.8	380	3.0	0.16	2.65	3.5	0.22	3.71	18	21

Bold = Optimal pressure for the MP Rotator is 2.8 bar; 280 kPa. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 2.8 bar; 280 kPa.

* Flow and precipitation rates may change as a result of reducing radius.

Radius: 2.5 to 4.9 m
Adjustable Arc & Full-Circle
Maroon and Grey: 90° to 210°
Lt. Blue and Grey: 210° to 270°
Olive and Grey: 360°

Arc	Pressure		Radius	Flow		Precip in/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
90° 	2.1	210	4.3	0.10	1.59	21	24
	2.5	250	4.5	0.10	1.74	21	24
	2.8	280	4.6	0.11	1.85	21	24
	3.1	310	4.8	0.12	1.97	21	24
	3.5	350	4.9	0.12	2.08	21	24
180° 	3.8	380	4.9	0.13	2.20	22	25
	2.1	210	4.0	0.17	2.84	21	25
	2.5	250	4.3	0.20	3.26	21	24
	2.8	280	4.5	0.21	3.52	21	24
	3.1	310	4.6	0.22	3.63	21	24
210° 	3.5	350	4.8	0.24	4.01	21	24
	3.8	380	4.9	0.25	4.20	21	24
	2.1	210	4.0	0.20	3.33	21	25
	2.5	250	4.3	0.22	3.63	20	23
	2.8	280	4.5	0.25	4.16	21	24
270° 	3.1	310	4.6	0.26	4.39	21	25
	3.5	350	4.8	0.28	4.69	21	24
	3.8	380	4.9	0.30	4.92	21	24
	2.1	210	4.0	0.26	4.31	22	25
	2.5	250	4.3	0.28	4.69	20	23
360° 	2.8	280	4.5	0.32	5.30	21	24
	3.1	310	4.6	0.33	5.56	21	24
	3.5	350	4.8	0.35	5.83	20	23
	3.8	380	4.9	0.37	6.09	20	23
	2.1	210	4.0	0.35	5.75	22	25
	2.5	250	4.3	0.39	6.43	21	24
	2.8	280	4.5	0.42	7.08	21	24
	3.1	310	4.6	0.45	7.57	21	25
	3.5	350	4.8	0.48	8.06	21	24
	3.8	380	4.9	0.51	8.55	21	25

Bold = Optimal pressure for the MP Rotator is 2.8 bar; 280 kPa. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 2.8 bar; 280 kPa.

Radius: 1.8 m to 7.3 m
Adjustable Arc & Full-Circle
Black and grey: 90° to 210°
Green and grey: 210° to 270°
Red and grey: 360°

Arc	Pressure				Radius		Flow		Precip in/hr	
	bar	kPa			m	m3/hr	l/min			
	2.1	210			6.1	0.19	3.20	21	24	
	2.5	250			6.4	0.21	3.51	21	24	
	2.8	280			6.7	0.22	3.65	20	23	
	3.0	300			7.0	0.24	4.01	20	23	
	3.5	350			7.3	0.25	4.19	19	22	
	3.8	380			7.3	0.26	4.37	20	23	
	2.1	210			6.1	0.39	6.50	21	24	
	2.5	250			6.4	0.41	6.86	20	23	
	2.8	280			6.7	0.46	7.58	20	23	
	3.0	300			6.7	0.47	7.79	21	24	
	3.5	350			7.0	0.50	8.36	20	24	
	3.8	380			7.3	0.54	8.92	20	23	
	2.1	210			6.1	0.44	7.34	20	23	
	2.5	250			6.4	0.48	7.92	20	23	
	2.8	280			6.7	0.54	8.93	20	24	
	3.0	300			6.7	0.54	9.02	21	24	
	3.5	350			7.0	0.57	9.54	20	23	
	3.8	380			7.3	0.60	10.06	19	22	
	2.1	210			6.1	0.58	9.58	21	24	
	2.5	250			6.4	0.62	10.36	20	23	
	2.8	280			6.7	0.68	11.35	20	23	
	3.0	300			6.7	0.71	11.81	21	24	
	3.5	350			7.0	0.75	12.49	20	24	
	3.8	380			7.3	0.79	13.16	20	23	
	2.1	210			6.1	0.77	12.85	21	24	
	2.5	250			6.4	0.84	13.92	20	24	
	2.8	280			6.7	0.90	14.99	20	23	
	3.0	300			6.7	0.93	15.41	21	24	
	3.5	350			7.0	0.98	16.27	20	23	
	3.8	380			7.3	1.03	17.13	19	22	

Bold = Optimal pressure for the MP Rotator is 2.8 bar; 280 kPa. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 2.8 bar; 280 kPa.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/mp-rotatorrr-mp800-nozzle/mp-820-360>
020326