

# Eco-Wrap

Irrigate more efficiently than blank dripline with fleece-wrapped dripline.

## KEY BENEFITS

- Perfect for narrow areas that are difficult to irrigate with standard methods
- Anti-siphon feature and fleece wrap protect against debris and root intrusion
- Saves 20–40% more water than standard products due to superior capillary movement of water to the entire root zone, promoting healthier root growth
- Non-draining, pressure-compensating emitters open/close simultaneously, maximising efficiency
- Check height of 1.5 m minimises system drainage and runoff

## Operating Specifications

- Operating range: 1.0 to 3.5 bar; 100 to 350 kPa
- Minimum filtration: 120 mesh; 125 microns
- Air relief recommended for sloping conditions greater than 1.5 m
- Recommended installation depth: turf (10-16 cm); other (10-30 cm)
- Compatible with Eco-Mat
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)

## Product Specifications

- Flow rate: 2.1 l/hr
- Emitter spacing: 30 cm
- Tubing dimensions: 0.660" x 0.560" (outside/inside diameter)
- Roll length: 16 mm = 100 m; 17 mm = 90 m
- Accepts 16 mm barb or LOC fittings



## ECO-WRAP TECHNICAL SPECIFICATIONS

	<b>16mm</b>	<b>17mm</b>
<b>Flow</b>	2.2 l hr; 0.13 m <sup>3</sup> /hr	2.2 l hr; 0.13 m <sup>3</sup> /hr
<b>Roll Length</b>	100 m	76 m
<b>Operating Pressure</b>	1.0 to 3.5 bar; 100 to 350 kPa	1.0 to 3.5 bar; 100 to 350 kPa
<b>Minimum Filtration</b>	120 mesh	120 mesh
<b>Emitter Spacing</b>	30 cm	30 cm

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.