

# Landscape Dripline (LDL)

Bring optimal precision and performance to landscape applications with pressure-compensating Landscape Dripline.

## KEY BENEFITS

- Pressure-compensating emitters ensure consistent flow and uniform coverage
- Colour-coded stripe provides easy identification of flow
- UV resistance facilitates product longevity
- Full-size outlet pool and raised wall inhibit debris and roots from entering the emitter
- Check valves keep the line charged up to 2 m and prevent low-point drainage
- Proprietary emitter design with multiple inlet filters and a wide, turbulent labyrinth provides superior grit tolerance
- Use with barbed 16 mm PLD or PLD-LOC Fittings
- Continuous self-flushing emitter
- 



## OPERATING SPECIFICATIONS

- Operating range: 1.0 to 4.2 bar; 100 to 420 kPa
- Minimum filtration: 120 mesh (125 microns)
- Warranty period: 5 years

## PRODUCT SPECIFICATIONS

- Available flow rates: 2.4, 3.8 l/hr
- Available emitter spacing: 30 cm, 45 cm
- Tubing dimensions: 15.8 mm x 13.8 mm (outside/inside diameter)
- Wall thickness: 1.0 mm
- Available lengths: 400 m

### LDL-PC: 2.4 l/hr

Pressure		Emitter Spacing (cm)	
(bar)	(kPa)	30	45
1.0	100	71	96
2.0	200	104	142
3.0	300	124	170
4.0	400	140	190

### LDL-PC: 3.8 l/hr

Pressure		Emitter Spacing (cm)	
(bar)	(kPa)	30	45
1.0	100	52	72
2.0	200	77	106
3.0	300	92	126
4.0	400	103	144

**Notes**  
Run lengths based on maintaining consistent flows.

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/landscape-dripline-ldl121625>