

# Landscape Dripline (LDL)

Bring optimal precision and performance to landscape applications with pressure-compensating Landscape Dripline.

## KEY BENEFITS

- Pressure-compensating emitters ensure consistent flow and uniform coverage
- Colour-coded stripe provides easy identification of flow
- UV resistance facilitates product longevity
- Full-size outlet pool and raised wall inhibit debris and roots from entering the emitter
- Check valves keep the line charged up to 2 m and prevent low-point drainage
- Proprietary emitter design with multiple inlet filters and a wide, turbulent labyrinth provides superior grit tolerance
- Use with barbed 16 mm PLD or PLD-LOC Fittings
- Continuous self-flushing emitter
- 

## OPERATING SPECIFICATIONS

- Operating range: 1.0 to 4.2 bar; 100 to 420 kPa
- Minimum filtration: 120 mesh (125 microns)
- Warranty period: 5 years

## PRODUCT SPECIFICATIONS

- Available flow rates: 2.4, 3.8 l/hr
- Available emitter spacing: 30 cm, 45 cm
- Tubing dimensions: 15.8 mm x 13.8 mm (outside/inside diameter)
- Wall thickness: 1.0 mm
- Available lengths: 400 m

LDL-PC: 2.4 l/hr

### Pressure Emitter Spacing (cm)

Pressure (bar)	Emitter Spacing (cm)	30	45
1.0 100	71	96	
2.0 200	104	142	
3.0 300	124	170	
4.0 400	140	190	

LDL-PC: 3.8 l hr



Pressure (bar)	Emitter Spacing (cm)	
(kPa)	30	45
<b>1.0</b>	100	52
<b>2.0</b>	200	77
<b>3.0</b>	300	92
<b>4.0</b>	400	103
		126
		144

#### Notes

Run lengths based on maintaining consistent flows.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/landscape-dripline-ldl020326>