

## I-35

### Operating Specifications

- Radius: 14.0 to 21.6 m
- Flow Rate: 1.65 to 7.24 m<sup>3</sup>/hr; 27.5 to 120.7 l/min
- Recommended pressure range: 2.5 to 7.0 bar; 250 to 700 kPa
- Operating pressure range: 2.5 to 7.0 bar; 250 to 700 kPa
- Precipitation rates: 12 mm/hr approx.
- Nozzle trajectory: 25 degrees





[I-35 Nozzle Rack](#)

**I-35 Nozzle**  
**Performance Data - Metric**

| Nozzle                                                                                                       | Pressure<br>Bars | Pressure<br>kPa | Radius<br>m | Flow<br>m3/hr | Flow<br>l/min | Precip mm/hr |    |
|--------------------------------------------------------------------------------------------------------------|------------------|-----------------|-------------|---------------|---------------|--------------|----|
|                                                                                                              |                  |                 |             |               |               | ■            | ▲  |
| <b>9</b><br><br>Lt. Brown | 2.5              | 250             | 14.0        | 1.65          | 27.5          | 17           | 19 |
|                                                                                                              | 3.0              | 300             | 14.3        | 1.81          | 30.1          | 18           | 20 |
|                                                                                                              | 3.5              | 350             | 14.9        | 1.94          | 32.3          | 17           | 20 |
|                                                                                                              | 4.0              | 400             | 15.2        | 2.05          | 34.2          | 18           | 20 |
|                                                                                                              | 4.5              | 450             | 15.2        | 2.16          | 36.0          | 19           | 22 |
|                                                                                                              | 5.0              | 500             | 15.5        | 2.27          | 37.8          | 19           | 22 |
| <b>12</b><br><br>Lt. Blue | 3.0              | 300             | 15.8        | 2.38          | 39.6          | 19           | 22 |
|                                                                                                              | 3.5              | 350             | 16.2        | 2.57          | 42.8          | 20           | 23 |
|                                                                                                              | 4.0              | 400             | 16.5        | 2.75          | 45.7          | 20           | 23 |
|                                                                                                              | 4.5              | 450             | 16.5        | 2.91          | 48.5          | 21           | 25 |
|                                                                                                              | 5.0              | 500             | 16.8        | 3.07          | 51.2          | 22           | 25 |
|                                                                                                              | 5.5              | 550             | 16.8        | 3.24          | 54.0          | 23           | 27 |
| <b>15</b><br><br>Grey     | 3.0              | 300             | 16.8        | 2.86          | 47.7          | 20           | 24 |
|                                                                                                              | 3.5              | 350             | 17.1        | 3.05          | 50.8          | 21           | 24 |
|                                                                                                              | 4.0              | 400             | 17.4        | 3.22          | 53.7          | 21           | 25 |
|                                                                                                              | 4.5              | 450             | 17.4        | 3.38          | 56.3          | 22           | 26 |
|                                                                                                              | 5.0              | 500             | 17.4        | 3.53          | 58.8          | 23           | 27 |
|                                                                                                              | 5.5              | 550             | 17.7        | 3.69          | 61.5          | 24           | 27 |
| <b>18</b><br><br>Red      | 3.0              | 300             | 17.4        | 3.08          | 51.4          | 20           | 24 |
|                                                                                                              | 3.5              | 350             | 17.7        | 3.31          | 55.2          | 21           | 24 |
|                                                                                                              | 4.0              | 400             | 18.0        | 3.52          | 58.7          | 22           | 25 |
|                                                                                                              | 4.5              | 450             | 18.3        | 3.72          | 62.0          | 22           | 26 |
|                                                                                                              | 5.0              | 500             | 18.9        | 3.91          | 65.2          | 22           | 25 |
|                                                                                                              | 5.5              | 550             | 19.2        | 4.11          | 68.5          | 22           | 26 |





[I-35 Nozzle Rack](#)

**I-35 High-Speed Nozzle**  
**Performance Data - Metric**

| Nozzle                                                                                                           | Pressure<br>Bars | Pressure<br>kPa | Radius<br>m | Flow<br>m3/hr | Flow<br>l/min | Precip mm/hr |    |
|------------------------------------------------------------------------------------------------------------------|------------------|-----------------|-------------|---------------|---------------|--------------|----|
|                                                                                                                  |                  |                 |             |               |               | ■            | ▲  |
| <b>9</b><br><br><br>Lt. Brown | 2.5              | 250             | 12.5        | 1.65          | 27.5          | 21           | 24 |
|                                                                                                                  | 3.0              | 300             | 12.8        | 1.81          | 30.1          | 22           | 25 |
|                                                                                                                  | 3.5              | 350             | 13.1        | 1.94          | 32.3          | 23           | 26 |
|                                                                                                                  | 4.0              | 400             | 13.4        | 2.05          | 34.2          | 23           | 26 |
|                                                                                                                  | 4.5              | 450             | 13.4        | 2.16          | 36.0          | 24           | 28 |
|                                                                                                                  | 5.0              | 500             | 13.7        | 2.27          | 37.8          | 24           | 28 |
| <b>12</b><br><br><br>Lt. Blue | 3.0              | 300             | 14.3        | 2.38          | 39.6          | 23           | 27 |
|                                                                                                                  | 3.5              | 350             | 14.6        | 2.57          | 42.8          | 24           | 28 |
|                                                                                                                  | 4.0              | 400             | 14.9        | 2.75          | 45.7          | 25           | 28 |
|                                                                                                                  | 4.5              | 450             | 15.2        | 2.91          | 48.5          | 25           | 29 |
|                                                                                                                  | 5.0              | 500             | 15.5        | 3.07          | 51.2          | 25           | 29 |
|                                                                                                                  | 5.5              | 550             | 15.5        | 3.24          | 54.0          | 27           | 31 |
| <b>15</b><br><br><br>Grey     | 3.0              | 300             | 14.6        | 2.86          | 47.7          | 27           | 31 |
|                                                                                                                  | 3.5              | 350             | 14.9        | 3.05          | 50.8          | 27           | 32 |
|                                                                                                                  | 4.0              | 400             | 15.2        | 3.22          | 53.7          | 28           | 32 |
|                                                                                                                  | 4.5              | 450             | 15.5        | 3.38          | 56.3          | 28           | 32 |
|                                                                                                                  | 5.0              | 500             | 16.2        | 3.53          | 58.8          | 27           | 31 |
|                                                                                                                  | 5.5              | 550             | 16.5        | 3.69          | 61.5          | 27           | 31 |
| <b>18</b><br><br><br>Red      | 3.0              | 300             | 14.9        | 3.08          | 51.4          | 28           | 32 |
|                                                                                                                  | 3.5              | 350             | 15.2        | 3.31          | 55.2          | 29           | 33 |
|                                                                                                                  | 4.0              | 400             | 15.5        | 3.52          | 58.7          | 29           | 34 |
|                                                                                                                  | 4.5              | 450             | 16.2        | 3.72          | 62.0          | 29           | 33 |
|                                                                                                                  | 5.0              | 500             | 16.8        | 3.91          | 65.2          | 28           | 32 |
|                                                                                                                  | 5.5              | 550             | 17.4        | 4.11          | 68.5          | 27           | 31 |





[I-35 Low Pressure Nozzle Rack](#)

**I-35 Low Pressure Nozzle**  
**Performance Data - Metric**

| Nozzle                                                                                                          | Pressure<br>Bars | Pressure<br>kPa | Radius<br>m | Flow<br>m <sup>3</sup> /hr | Flow<br>l/min | Precip mm/hr |    |
|-----------------------------------------------------------------------------------------------------------------|------------------|-----------------|-------------|----------------------------|---------------|--------------|----|
|                                                                                                                 |                  |                 |             |                            |               | ■            | ▲  |
| <b>7LP</b><br><br>Orange     | 2.5              | 250             | 13.1        | 1.60                       | 26.7          | 19           | 22 |
|                                                                                                                 | 3.0              | 300             | 13.4        | 1.80                       | 30.0          | 20           | 23 |
|                                                                                                                 | 3.5              | 350             | 13.7        | 1.96                       | 32.7          | 21           | 24 |
|                                                                                                                 | 4.0              | 400             | 14.0        | 2.11                       | 35.2          | 21           | 25 |
| <b>10LP</b><br><br>Lt. Green | 2.5              | 250             | 14.9        | 2.16                       | 35.9          | 19           | 22 |
|                                                                                                                 | 3.0              | 300             | 15.2        | 2.42                       | 40.4          | 21           | 24 |
|                                                                                                                 | 3.5              | 350             | 15.5        | 2.64                       | 44.1          | 22           | 25 |
|                                                                                                                 | 4.0              | 400             | 16.2        | 2.85                       | 47.5          | 22           | 25 |
| <b>13LP</b><br><br>Lt. Blue  | 2.5              | 250             | 15.8        | 2.65                       | 44.2          | 21           | 24 |
|                                                                                                                 | 3.0              | 300             | 16.2        | 2.97                       | 49.5          | 23           | 26 |
|                                                                                                                 | 3.5              | 350             | 16.5        | 3.23                       | 53.8          | 24           | 28 |
|                                                                                                                 | 4.0              | 400             | 16.8        | 3.47                       | 57.8          | 25           | 29 |
| <b>15LP</b><br><br>Grey      | 2.5              | 250             | 16.5        | 3.17                       | 52.8          | 23           | 27 |
|                                                                                                                 | 3.0              | 300             | 16.8        | 3.55                       | 59.2          | 25           | 29 |
|                                                                                                                 | 3.5              | 350             | 17.7        | 3.86                       | 64.4          | 25           | 29 |
|                                                                                                                 | 4.0              | 400             | 18.3        | 4.16                       | 69.3          | 25           | 29 |



**I-35-06**

|                  |        |
|------------------|--------|
| Overall Height   | 26 cm  |
| Pop-up Height    | 15 cm  |
| Exposed Diameter | 5 cm   |
| Inlet Size       | 1" BSP |

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/discontinued-models/i-35020326>