

X-Core™

This simple irrigation controller offers optional on-site smart ET watering adjustments and handheld remote operation.

KEY BENEFITS

- Number of stations: 2, 4, 6, or 8 (fixed models)
- Solar Sync™ accessory saves water based on local weather conditions
- Built-in key lock on outdoor models protects against vandalism
- 3 flexible programs with 4 start times each and up to 4-hour run times
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring
- Hide Programs setting shows 1 program and 1 start time for simplification
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve™ Memory backs up the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule adjustments without changing run times



Electrical Specifications

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Approvals: Plastic IP54 (outdoor), UL, cUL, FCC, CE, UKCA, RCM
- Warranty period: 2 years

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/controllers/x-coretm>
121525