

Node

This battery-powered, waterproof controller offers automatic irrigation control for temporary irrigation and sites without electricity.

KEY BENEFITS

- Number of stations: 1, 2, 4, or 6
- Battery-operated controller for automatic irrigation without AC power
- Battery-life indicator for battery replacement
- Waterproof enclosure seal protects against water ingress
- 3 flexible programs with 4 start times each and up to 6-hour run times
- Suspend irrigation up to 99 days during the off-season
- Easy Retrieve™ Memory backs up the full irrigation schedule if ever changed
- Delay Between Stations for slow-closing valves or pump recharge
- Seasonal adjustment for quicker schedule adjustments without changing run times
- Solar panel provides maintenance-free operation
- Mounts to Hunter solenoids, pipes, flat surfaces, or inside the valve box

Operating Specifications

- One or two 9V alkaline batteries or 1800 mAh solar panel with charging cell
- Operates DC-latching solenoids (P/N 458200)
- 30 m maximum wire runs, 1 mm² wire only
- Station output: 9-11 VDC
- P/MV output: 9-11 VDC
- Sensor inputs: 1
- Approvals: IP68, UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

Maximum Wire Run

Wire Size Max Distance (m)

1.0 mm ²	30
---------------------	----



Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/en-metric/irrigation-product/controllers/node020326>