



HDL-06-12-250-CV

Marca: Riego de jardines

Línea de productos: Riego Localizado

Modelo de productos: HDL

SKU: HDL0612250CV

Descripción: Línea de goteo Hunter, válvula de retención compensadora de presión, 2,1 l/h, espaciado de 30 cm, 75 m

Shipping Information

UPC-A: 0611698514580

Cantidad / Bolsa: 1

Origen: ENSAMBLADO EN EE. UU.

Palé oceánico: 44

Palé terrestre: 36

Cartón maestro: 1

Additional Information

Tasa de caudal: 0.6 GPH

Longitud de la bobina: 250'

Distancia entre emisores: 12"

Tasa de caudal: 0.6 GPH

Riego en línea: Drip irrigation

Riego en línea: Tubería

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	206
3.0	129	210	280
4.0	167	295	399

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	389

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/es/irrigation-product/hdl/hdl-06-12-250-cv>
020326