

HDL-06-12-1K-CV



Marque: Arrosage des espaces verts

Gamme de produit: Micro-irrigation

Modèle de produit: HDL

Référence: HDL06121KCV

Description: Goutte-à-goutte Hunter, clapet anti-vidange à compensation de pression, 2,1 l/h, espacement de 30 cm, 300 m

Shipping Information

UPC-A: 0611698514603

Qté./sac: 1

Palette pour transport maritime: 20

Palette pour transport terrestre: 16

Carton principal: 1

Additional Information

Débit: 0.6 GPH

Longueur de la bobine: 1,000'

Espacement entre les émetteurs: 12"

Débit: 0.6 GPH

Arrosage en ligne: Drip irrigation

Arrosage via Internet: Tuyauterie

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	206
3.0	129	210	280
4.0	167	295	399

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	389

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/fr/irrigation-product/hdl/hdl-06-12-1k-cv>
020326