

HDL-09-18-100-CV



Marque: Arrosage des espaces verts

Gamme de produit: Micro-irrigation

Modèle de produit: HDL

Référence: HDL0918100CV

Description: Goutte-à-goutte Hunter, clapet anti-vidange à compensation de pression, 3,4 l/h, espacement de 45 cm, 30 m

Shipping Information

UPC-A: 0611698514702

Qté./sac: 1

Palette pour transport maritime: 88

Palette pour transport terrestre: 68

Carton principal: 1

Additional Information

Débit: 0.9 GPH

Longueur de la bobine: 100'

Espacement entre les émetteurs: 18"

Débit: 0.9 GPH

Arrosage en ligne: Drip irrigation

Arrosage via Internet: Tuyauterie

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	186
3.0	129	170	200
4.0	167	195	209

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	289

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/fr/irrigation-product/hdl/hdl-09-18-100-cv>
121825