

PGV Jar-Top

These versatile and robust valves offer simple serviceability.

VANTAGGI PRINCIPALI

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Jar-top models provide easy access without tools
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximises efficiency and prolongs the life of the system

User-Installed Options

- Accu Sync™ pressure regulation at the valve*
- DC-latching solenoid for battery-powered controllers (P/N 458200)
- Solenoid conduit cover (P/N 464322)

Factory-Installed Options

- LS: Valve without solenoid
- DC: DC-latching solenoid for battery-powered controllers

Operating Specifications

- Flow: 0.05 to 9 m³ /hr; 0.7 to 150 l/min
- Recommended pressure range: 1.5 to 10 bar; 150 to 1,000 kPa
- Temperature rating: 66°C
- Warranty period: 2 years

Solenoid Specifications

- 24 VAC solenoid
 - 350 mA inrush, 190 mA holding, 60 Hz
 - 370 mA inrush, 210 mA holding, 50 Hz



VALVOLA PGV JAR TOP PERDITA DI CARICO IN BAR

Portata	1"
m³/ora	in linea
0,3	0,1
1,0	0,1
2,5	0,1
3,5	0,1
4,5	0,2
5,5	0,3
6,5	0,4
8,0	0,8
9,0	1,0

VALVOLA PGV JAR TOP PERDITA DI CARICO IN KPA

Portata	1"
l/min	in linea
4	8,2
20	9,7
40	13
55	11
75	22
95	31
115	62
135	112
150	139

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/it/irrigation-product/valvole/pgv-con-ghiera>
020326