



HDL-06-12-1K-CV

Marka: Nawadnianie terenu

Linia produktów: Micro

Model produktu: HDL

SKU: HDL06121KCV

Opis: Linia kroplująca Hunter, zawór zwrotny kompensacyjny ciśnienia, 2,1 l/godz., rozstaw 30 cm, 300 m

Shipping Information

UPC-A: 0611698514603

Liczba w torbie: 1

Paleta dostawy morskiej: 20

Paleta dostawy lądowej: 16

Karton główny: 1

Additional Information

Natężenie przepływu: 0.6 GPH

Długość cewki: 1,000'

Rozstaw emiterów: 12"

Natężenie przepływu: 0.6 GPH

Nawadnianie liniowe: Drip irrigation

Nawadnianie online: Rury

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	206
3.0	129	210	280
4.0	167	295	399

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	389

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/pl/irrigation-product/hdl/hdl-06-12-1k-cv>
020326