


Pro-Spray™ PRS40

To optimise MP Rotator Nozzle performance, the Pro-Spray PRS40 is pressure-regulated to 2.8 bar; 280 kPa.

KLUCZOWE KORZYŚCI

- Industry's strongest spray body for years of reliable performance
- Pressure-regulated to 2.8 bar; 280 kPa for the MP Rotator Nozzle
- Grey cap for easy field identification
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- Heavy-duty spring for consistent riser retraction
- FloGuard™ Technology option eliminates water waste in the event of a missing nozzle
- Interchangeable components for easier servicing, retrofits, and upgrades
- Check valve option eliminates low-head drainage



Operating Specifications

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- Warranty period: 5 years

Factory-Installed Options

- Check valve available for 10 cm, 15 cm, and 30 cm models (up to 4.3 m of elevation)
- Reclaimed water identification
- FloGuard™ Technology available for check valve models

User-Installed Options

- Drain Check Valve P/N: 437400SP
 - Up to 4.3 m of elevation for 10 cm, 15 cm, and 30 cm models
 - Up to 3 m of elevation for 7.5 cm model
- Reclaimed water ID cap P/N: 458562SP
- Snap-on reclaimed cover P/N: PROS-RC-CAP-SP
- Shutoff cap P/N: 213600SP
- Shutoff nozzle P/N: 916400SP

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/pl/irrigation-product/zraszacze/pro-spraytm-prs40>
020326