

STG-900

Top-quality STG-900 long-range rotors are specially designed to extend the life of small-to-midsize synthetic turf sports fields.

KEY BENEFITS

- Flexible arc adjustment from 40° to 360° offers narrow-to-wide coverage
- QuickCheck™ Arc Mechanism lets you verify the arc setting without waiting for the sprinkler to finish its rotation
- Through-the-top arc adjustment allows you to easily set the arc at the sprinkler head
- Water-lubricated gear drive delivers reliable operation without clogging
- User-installed rubber logo cap increases athlete safety on the field
- Nozzle trajectory: 22.5°



OPERATING SPECIFICATIONS

- Nozzle trajectory: 22.5°
- Radius: 103' to 120'
- Flow: 74.5 to 92.0 GPM
- Operating pressure range: 100 to 120 PSI
- Precipitation rate: 1.25 in/hr approximately
- Warranty period: 5 years for component parts

USER-INSTALLED OPTIONS

- Rubber Cover Kit STG-900: P/N 473900SP

STG-900 Nozzle Performance Data*

NOZZLE	Pressure PSI	Radius Ft.	Flow GPM	Precip in/hr	
73° ORANGE	100	103	74.5	1.35	1.56
	110	109	77	1.25	1.44
	120	115	79.6	1.16	1.34
83° TAN	100	112	84.2	1.29	1.49
	110	116	88.1	1.26	1.46
	120	120	92	1.23	1.42

Notes:

All precipitation rates calculated for 180° operation.

For precipitation rate of 360° sprinkler, divide by 2.

Requires minimum 100 PSI dynamic pressure supplied to swing joint inlet.

*All radius measurements taken at standard rotation speeds. Slowing rotation to minimum rotation speed will add 9' to radius.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/irrigation-product/st-system/stg-900>

020326