

G-995

Covering 75' to 104', the G-995 is the perfect combination of performance and reliability.

KEY BENEFITS

- G-995 is an adjustable part-circle model (40° to 360°)
- Higher-flow, longer-radius rotor designed for single-row systems
- Contour back-nozzle capability for special applications

MODEL SPECIFICATIONS

- Adjustable Arc (40° to 360°)

MODEL VARIATIONS

C = Check-O-Matic checks up to 25' in elevation change and readily converts to Normally Open Hydraulic with through the top connections.

D = Decoder Valve-In-Head with all "E" specifications below.

DD = 2-Station Decoder Valve-In-Head with all "E" specifications below.

E = Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 190mA (350mA inrush) solenoid with captive plunger and internal downstream bleed.

OPERATING SPECIFICATIONS

- Discharge rate: 29.5 to 83.8 GPM
- Radius: 75' to 104'
- Pressure range: 80 to 120 PSI
- Pressure rating: 150 PSI





G995

Overall Height	13-1/4"
Pop-up Height	3"
Flange Diameter	7-1/2"
Inlet Size	1-1/2" Female ACME

G995 NOZZLE PERFORMANCE DATA*

Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM		
25  Lt. Blue	80	75	29.5	0.50	0.58
	90	76	31.5	0.52	0.61
	100	77	33.2	0.54	0.62
	110	78	35.6	0.56	0.65
	120	79	37.5	0.58	0.67
33  Grey	80	77	36.2	0.59	0.68
	90	78	38.2	0.60	0.70
	100	79	40.4	0.62	0.72
	110	81	42.6	0.62	0.72
	120	82	44.8	0.64	0.74
38  Red	80	80	40.6	0.61	0.71
	90	82	43.0	0.62	0.71
	100	84	45.4	0.62	0.72
	110	85	47.6	0.63	0.73
	120	86	50.0	0.65	0.75
43  Dk. Brown	80	84	46.1	0.63	0.73
	90	85	48.5	0.65	0.75
	100	85	50.7	0.68	0.78
	110	86	53.4	0.69	0.80
	120	87	55.7	0.71	0.82
48  Dk. Green	80	88	50.2	0.62	0.72
	90	89	52.6	0.64	0.74
	100	90	55.1	0.65	0.76
	110	92	57.5	0.65	0.76
	120	92	60.5	0.69	0.79
53  Dk. Blue	80	91	54.9	0.64	0.74
	90	91	57.2	0.66	0.77
	100	92	59.5	0.68	0.78
	110	93	62.1	0.69	0.80
	120	92	64.4	0.73	0.85
63  Black	80	93	62.3	0.69	0.80
	90	94	65.5	0.71	0.82
	100	95	69.0	0.74	0.85
	110	96	71.9	0.75	0.87
	120	98	74.7	0.75	0.86
73  Orange	80	96	72.7	0.76	0.88
	90	98	75.4	0.76	0.87
	100	100	78.1	0.75	0.87
	110	102	80.9	0.75	0.86
	120	104	83.8	0.75	0.86

Note: *Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

** For low angle nozzle performance, reduce radius by 15%

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/irrigation-product/golf-rotors/g-995>
020326