



MP-800SR-360

Brand: Landscape Irrigation

Product Line: MP Rotator Nozzles


Product Model: MP Rotator® MP800 Nozzle

SKU: MP800SR360

Description: MP Rotator Nozzle, 0.8 in/hr precipitation rate, 6' to 12' radius, 360° arc, female thread, gray and lime green

Dimensions

Diameter: 1"



Operating Specifications

Arc: 360°

Operating Pressure: 40 PSI

Precipitation Rate: 0.8 in/hr

Radius: 8' to 12'

Flow: 0.66 to 0.98 GPM; 37.8 to 58.8 GPH

Shipping Information

UPC-A: 0611698029275

Qty. / Bag: 10/200

Ocean Pallet: 38400

Land Pallet: 32000

Master Carton: 200

Additional Information

Arc: 360°

Precipitation Rate: Approx 0.8 in/hr

Radius: 6' – 12'

MP-815

MP ROTATOR PERFORMANCE DATA

Radius: 8' to 16'
Adjustable Arc & Full Circle
Maroon and Grey: 90° to 210°
Lt. Blue and Grey: 210° to 270°
Olive and Grey: 360°

MP-800SR

Radius: 6' to 12'
Adjustable Arc & Full-Circle
Orange and Gray: 90° to 210°
Lime Green and Gray: 360°

Arc	Pressure	Min Radius		Max Radius					
		Radius	Flow	Radius	Flow	Precip in/hr			
	PSI	ft	GPM	ft	GPM		■	▲	
90°	30	6	0.13	8	0.17	0.90	1.04		
	35	7	0.15	9	0.21	0.89	1.03		
	40	8	0.16	10	0.23	0.83	0.96		
	45	8	0.18	11	0.25	0.80	0.92		
	50	9	0.19	11	0.27	0.79	0.92		
	55	10	0.20	12	0.28	0.80	0.93		
180°	30	6	0.26	8	0.33	0.88	1.02		
	35	7	0.29	9	0.38	0.85	0.99		
	40	8	0.32	10	0.42	0.81	0.93		
	45	8	0.36	11	0.46	0.77	0.88		
	50	9	0.38	11	0.48	0.76	0.88		
	55	10	0.40	12	0.50	0.73	0.84		
210°	30	6	0.30	8	0.35	0.80	0.93		
	35	7	0.34	9	0.38	0.77	0.89		
	40	8	0.37	10	0.43	0.81	0.91		
	45	8	0.42	10	0.45	0.82	0.95		
	50	9	0.44	11	0.49	0.73	0.85		
	55	10	0.47	12	0.56	0.70	0.81		
360°	30	6	0.47	8	0.66	0.89	1.03		
	35	7	0.52	9	0.71	0.80	0.92		
	40	8	0.56	10	0.78	0.79	0.91		
	45	8	0.59	10	0.85	0.78	0.90		
	50	9	0.63	11	0.88	0.73	0.85		
	55	10	0.70	12	0.98	0.70	0.81		

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 40 PSI.

* Flow and precipitation rates may change as a result of reducing radius.

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
90°	30	14	0.42	0.83	0.95
	35	15	0.46	0.79	0.91
	40	15	0.49	0.84	0.97
	45	16	0.52	0.78	0.90
	50	16	0.55	0.83	0.96
	55	16	0.58	0.87	1.01
180°	30	13	0.75	0.85	0.99
	35	14	0.86	0.84	0.98
	40	15	0.93	0.80	0.92
	45	15	0.96	0.82	0.95
	50	16	1.06	0.80	0.92
	55	16	1.11	0.83	0.96
210°	30	13	0.88	0.86	0.99
	35	14	0.96	0.81	0.93
	40	15	1.10	0.81	0.93
	45	15	1.16	0.85	0.98
	50	16	1.24	0.80	0.92
	55	16	1.30	0.84	0.97
270°	30	13	1.14	0.87	1.00
	35	14	1.24	0.81	0.94
	40	15	1.40	0.80	0.92
	45	15	1.47	0.84	0.97
	50	16	1.54	0.77	0.89
	55	16	1.61	0.81	0.93
360°	30	13	1.52	0.87	1.00
	35	14	1.70	0.83	0.96
	40	15	1.87	0.80	0.92
	45	15	2.00	0.86	0.99
	50	16	2.13	0.80	0.92
	55	16	2.26	0.85	0.98

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 40 PSI.

MP-820

Radius: 16' to 24'
Adjustable Arc & Full-Circle
Black and gray: 90° to 210°
Green and gray: 210° to 270°
Red and gray: 360°

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM		
90° 	30	20	0.85	0.82	0.94
	35	21	0.93	0.81	0.94
	40	22	0.97	0.77	0.89
	45	23	1.06	0.77	0.89
	50	24	1.11	0.74	0.85
	55	24	1.16	0.77	0.89
180° 	30	20	1.72	0.83	0.96
	35	21	1.82	0.79	0.91
	40	22	2.01	0.80	0.92
	45	22	2.06	0.82	0.95
	50	23	2.21	0.80	0.93
	55	24	2.36	0.79	0.91
210° 	30	20	1.94	0.80	0.92
	35	21	2.10	0.78	0.91
	40	22	2.36	0.81	0.93
	45	22	2.39	0.81	0.94
	50	23	2.52	0.79	0.91
	55	24	2.66	0.76	0.88
270° 	30	20	2.53	0.81	0.94
	35	21	2.74	0.80	0.92
	40	22	3.00	0.80	0.92
	45	22	3.12	0.83	0.96
	50	23	3.30	0.80	0.93
	55	24	3.48	0.78	0.90
360° 	30	20	3.40	0.82	0.94
	35	21	3.68	0.80	0.93
	40	22	3.97	0.79	0.91
	45	22	4.08	0.81	0.94
	50	23	4.30	0.78	0.90
	55	24	4.53	0.76	0.87

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40 Sprinkler Body, pressure regulated at 40 PSI.

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/irrigation-product/mp-rotatorrr-mp800-nozzle/mp-800sr-360>
020326